



Formerly Known As: **Shell Valvata J**

Shell Omala S1 W 460

Industrial Gear Oils

Shell Omala S1 W oils are quality refined, high viscosity mineral oils compounded with a small percentage of fatty oils. They are particularly suitable for the lubrication of low speed enclosed gears and worm drive application. They are also suitable for the lubrication of high temperature, high pressure steam cylinders.

- Reliable Protection
- Worm Drive Applications

DESIGNED TO MEET CHALLENGES

Performance, Features & Benefits

▪ Oil life – Maintenance saving

Shell Omala S1 W possesses low volatility and a natural resistance to the formation of gummy or carbonaceous deposits in high temperature conditions to give consistent performance through the lubrication maintenance intervals.

▪ Wear protection

Provides a reliable oil film under low speed operation such as worm gear drives.

Main Applications



▪ Enclosed industrial worm gear systems

Shell Omala S1 W may be used to advantage in worm gears prone to suffer extensive wear and to reduce the bulk oil temperature. Typical examples are gears running at low speed under stop-start conditions.

▪ Steam cylinder lubrication

Suitable for steam cylinder applications working under high temperature and high pressure conditions.

For highly-loaded worm drives Shell Omala S4 WE is recommended.

For industrial enclosed spur and helical gear systems the Shell Omala “G” series is recommended.

For automotive hypoid gears, the appropriate Shell Spirax Oil should be used.

Specifications, Approvals & Recommendations

▪ AGMA 9005-EO2 (CP)

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

Typical Physical Characteristics

Properties	Method	Omala S1 W 460
ISO Viscosity Grade	ISO 3448	460
Kinematic Viscosity @40°C	mm ² /s	460
Kinematic Viscosity @100°C	mm ² /s	31.2
Viscosity Index	ISO 2909	98
Density @15°C	kg/m ³	887
Flash Point (COC)	°C	318
Pour Point	°C	-6

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

▪ Health & Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <https://www.epc.shell.com>

▪ Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Additional Information

▪ Advice

Advice on applications not covered here may be obtained from your Shell representative.