

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

|         |                |              |                                |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 10.06.2024 |
| 3.3     | 13.09.2024     | 800001015845 | Print Date 14.09.2024          |

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

|                        |                         |
|------------------------|-------------------------|
| Trade name             | : Risella X 415         |
| Product code           | : 001E2773              |
| Registration number EU | : 01-0000020163-82-0001 |
| CAS-No.                | : 848301-69-9           |

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

|                                   |   |
|-----------------------------------|---|
| Use of the Sub-<br>stance/Mixture | : Process oil.<br>Please refer to Ch16 for the registered uses under REACH. |
|-----------------------------------|---|

|                      |   |
|----------------------|---|
| Uses advised against | :<br>This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier. |
|----------------------|---|

#### 1.3 Details of the supplier of the safety data sheet

|                                  |  |
|----------------------------------|--|
| Manufacturer/Supplier            | : <b>Shell UK Oil Products Limited</b><br>Shell Centre<br>London<br>SE1 7NA<br>United Kingdom    |
| Telephone                        | : (+44) 08007318888  |
| Telefax                          | :  |
| Contact for Safety Data<br>Sheet | : If you have any enquiries about the content of this SDS<br>please email lubricantSDS@shell.com |

#### 1.4 Emergency telephone number

: +44 (0) 20 7934 7778 (This telephone number is available 24  
hours per day, 7 days per week)

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

|                               |  |
|-------------------------------|--|
| Aspiration hazard, Category 1 | H304: May be fatal if swallowed and enters air-<br>ways. |
|-------------------------------|--|

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

|         |                |              |                                |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 10.06.2024 |
| 3.3     | 13.09.2024     | 800001015845 | Print Date 14.09.2024          |

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :  
PHYSICAL HAZARDS:  
Not classified as a physical hazard according to CLP criteria.  
HEALTH HAZARDS:  
H304 May be fatal if swallowed and enters airways.  
ENVIRONMENTAL HAZARDS:  
Not classified as environmental hazard according to CLP criteria.

Precautionary statements : **Prevention:**  
No precautionary phrases.

#### **Response:**

P331 Do NOT induce vomiting.  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

#### **Storage:**

P405 Store locked up.

#### **Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

Contains Distillates (Fischer - Tropsch), heavy, C18-50 - branched, cyclic and linear. CAS # 848301-69-9

### 2.3 Other hazards

The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Used oil may contain harmful impurities.  
Not classified as flammable but will burn.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version 3.3      Revision Date: 13.09.2024      SDS Number: 800001015845      Date of last issue: 10.06.2024  
Print Date 14.09.2024

### SECTION 3: Composition/information on ingredients

#### 3.1 Substances

Chemical nature : Fischer-Tropsch derived base oil, consisting largely of branched, cyclic and linear hydrocarbons having carbon numbers in the range of C18 to C50.

#### Components

| Chemical name   | CAS-No.<br>EC-No.        | Concentration (% w/w) |
|---|--------------------------|-----------------------|
| Distillates (Fischer - Trop-sch), heavy, C18-50 – branched, cyclic and linear | 848301-69-9<br>482-220-0 | <= 100                |

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.

If inhaled : No treatment necessary under normal conditions of use.  
If symptoms persist, obtain medical advice.

In case of skin contact : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.  
If persistent irritation occurs, obtain medical attention.

In case of eye contact : Flush eye with copious quantities of water.  
Remove contact lenses, if present and easy to do. Continue rinsing.  
If persistent irritation occurs, obtain medical attention.

If swallowed : Call emergency number for your location / facility.  
If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.  
If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

|         |                |              |                                |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 10.06.2024 |
| 3.3     | 13.09.2024     | 800001015845 | Print Date 14.09.2024          |

congestion, shortness of breath, and/or fever.  
The onset of respiratory symptoms may be delayed for several hours after exposure.  
Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance.  
Ingestion may result in nausea, vomiting and/or diarrhoea.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Potential for chemical pneumonitis.  
Call a doctor or poison control center for guidance.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media : Do not use water in a jet.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Hazardous combustion products may include:  
A complex mixture of airborne solid and liquid particulates and gases (smoke).  
Carbon monoxide may be evolved if incomplete combustion occurs.  
Unidentified organic and inorganic compounds.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : 6.1.1 For non emergency personnel:  
Avoid contact with skin and eyes.  
6.1.2 For emergency responders:  
Avoid contact with skin and eyes.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

|         |                |              |                                |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 10.06.2024 |
| 3.3     | 13.09.2024     | 800001015845 | Print Date 14.09.2024          |

---

### 6.2 Environmental precautions

Environmental precautions : Use appropriate containment to prevent uncontrolled release. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.

### 6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.,  
For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

|                         |   |
|-------------------------|---|
| Technical measures      | : Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.<br>Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material. |
| Advice on safe handling | : Avoid inhaling vapour and/or mists.<br>When handling product in drums, safety footwear should be worn and proper handling equipment should be used.<br>Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.   |
| Product Transfer        | : Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation.  |
| Hygiene measures        | : Exposure to this product should be reduced as low as reasonably practicable. Reference should be made to the Health and Safety Executive's publication "COSHH Essentials".  |

### 7.2 Conditions for safe storage, including any incompatibilities

|  |  |
|--|--|
| Further information on storage stability | : Keep container tightly closed and in a cool, well-ventilated place.<br>Use properly labeled and closable containers.<br>Store at ambient temperature.<br><br>Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.<br>The storage of this product may be subject to the Control of |
|--|--|

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version 3.3      Revision Date: 13.09.2024      SDS Number: 800001015845      Date of last issue: 10.06.2024  
Print Date 14.09.2024

Packaging material : Pollution (Oil Storage) (England) Regulations. Further guidance may be obtained from the local environmental agency office.  
: Suitable material: For containers or container linings, use mild steel or high density polyethylene.  
Unsuitable material: PVC.

Container Advice : Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

### 7.3 Specific end use(s)

Specific use(s) : Please refer to section 16 and/or the annexes for the registered uses under REACH.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

| Components        | CAS-No.      | Value type (Form of exposure)      | Control parameters | Basis                            |
|-------------------|--------------|------------------------------------|--------------------|----------------------------------|
| Oil mist, mineral | Not Assigned | TWA (inhalable fraction)           | 5 mg/m3            | US. ACGIH Threshold Limit Values |
| Oil mist, mineral |              | TWA (Inhalable particulate matter) | 5 mg/m3            | ACGIH                            |

#### Biological occupational exposure limits

#### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name | Environmental Compartment   | Value |
|----------------|---|-------|
| Remarks:       | Substance is a hydrocarbon with a complex, unknown or variable composition. Conventional methods of deriving PNECs are not appropriate and it is not possible to identify a single representative PNEC for such substances. |       |

### 8.2 Exposure controls

#### Engineering measures

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

#### General Information:

Define procedures for safe handling and maintenance of controls.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

|         |                |              |                                |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 10.06.2024 |
| 3.3     | 13.09.2024     | 800001015845 | Print Date 14.09.2024          |

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Do not ingest. If swallowed, then seek immediate medical assistance

### Personal protective equipment

The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : If material is handled such that it could be splashed into eyes, protective eyewear is recommended.  
Approved to EU Standard EN166.

Hand protection

Remarks : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.

Skin and body protection : Skin protection is not ordinarily required beyond standard work clothes.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

|         |                |              |                                |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 10.06.2024 |
| 3.3     | 13.09.2024     | 800001015845 | Print Date 14.09.2024          |

It is good practice to wear chemical resistant gloves.

Respiratory protection : No respiratory protection is ordinarily required under normal conditions of use.  
In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material.  
If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation.  
Check with respiratory protective equipment suppliers.  
Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.  
Select a filter suitable for combined particulate/organic gases and vapours [Type A/Type P boiling point > 65°C (149°F)] meeting EN14387 and EN143.

Thermal hazards : Not applicable

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : Liquid at room temperature.

Colour : clear

Odour : Slight hydrocarbon

Odour Threshold : Data not available

pour point : -39 °C  
Method: ISO 3016

Melting point/freezing point : Data not available

Initial boiling point and boiling range : > 280 °C  
Estimated value(s)

#### Flammability

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Not classified as flammable but will burn.

#### Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit /  
upper flammability limit : Not applicable

Lower explosion limit / : Not applicable



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

|         |                |              |                                |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 10.06.2024 |
| 3.3     | 13.09.2024     | 800001015845 | Print Date 14.09.2024          |

---

### Lower flammability limit

Flash point : 200 °C  
Method: ISO 2592

Auto-ignition temperature : > 320 °C

Decomposition temperature  
Decomposition temperature : Data not available

pH : Not applicable

Viscosity  
Viscosity, dynamic : Data not available

Viscosity, kinematic : 18 mm<sup>2</sup>/s (20 °C)  
Method: ISO 3104

9.3 mm<sup>2</sup>/s (40.0 °C)  
Method: ISO 3104

2.6 mm<sup>2</sup>/s (100 °C)  
Method: ISO 3104

Solubility(ies)  
Water solubility : negligible

Solubility in other solvents : Data not available

Partition coefficient: n-octanol/water : log Pow: > 6

Vapour pressure : < 0.5 Pa (20 °C)  
estimated value(s)

Relative density : 0.8042 (15 °C)

Density : 806 kg/m<sup>3</sup> (15.0 °C)  
Method: ISO 12185

Relative vapour density : > 5

Particle characteristics  
Particle size : Data not available

### 9.2 Other information

Explosive properties : Classification Code: Not classified.

Oxidizing properties : Data not available

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

|         |                |              |                                |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 10.06.2024 |
| 3.3     | 13.09.2024     | 800001015845 | Print Date 14.09.2024          |

---

|                        |   |   |
|------------------------|---|---|
| Flammability (liquids) | : | Not classified as flammable but will burn.                |
| Evaporation rate       | : | Data not available  |
| Conductivity           | : | This material is not expected to be a static accumulator. |

---

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

#### 10.2 Chemical stability

Stable.

No hazardous reaction is expected when handled and stored according to provisions

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with strong oxidising agents.

#### 10.4 Conditions to avoid

Conditions to avoid : Extremes of temperature and direct sunlight.

#### 10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

#### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

---

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

#### Acute toxicity

##### Product:

Acute oral toxicity : LD50 (rat): > 5,000 mg/kg  
Remarks: Low toxicity  
Based on available data, the classification criteria are not met.

Acute inhalation toxicity : LC 50 (Rat): > 5 mg/l  
Exposure time: 4 h  
Remarks: Low toxicity by inhalation.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version 3.3      Revision Date: 13.09.2024      SDS Number: 800001015845      Date of last issue: 10.06.2024  
Print Date 14.09.2024

Remarks: Low toxicity

### Skin corrosion/irritation

#### Product:

Remarks : Not irritating to skin.

### Serious eye damage/eye irritation

#### Product:

Remarks : Not irritating to eye.

### Respiratory or skin sensitisation

#### Product:

Remarks : For respiratory and skin sensitisation:  
Not a skin sensitiser.

### Germ cell mutagenicity

#### Product:

Genotoxicity in vivo : Remarks: Non mutagenic

Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.

### Carcinogenicity

#### Product:

Remarks : Not a carcinogen.  
Based on available data, the classification criteria are not met.

Carcinogenicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

| Material  | GHS/CLP Carcinogenicity Classification |
|---|--|
| Distillates (Fischer - Trop-sch), heavy, C18-50 – branched, cyclic and linear | No carcinogenicity classification.     |

### Reproductive toxicity

#### Product:

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

|         |                |              |                                |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 10.06.2024 |
| 3.3     | 13.09.2024     | 800001015845 | Print Date 14.09.2024          |

Effects on fertility : Remarks: Does not impair fertility., Not a developmental toxicant.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

### STOT - single exposure

#### Product:

Remarks : Based on available data, the classification criteria are not met.

### STOT - repeated exposure

#### Product:

Remarks : Based on available data, the classification criteria are not met.

### Aspiration toxicity

#### Product:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### Further information

#### Product:

Remarks : Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal.  
ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

Remarks : Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

|                |                              |                             |   |
|----------------|------------------------------|-----------------------------|---|
| Version<br>3.3 | Revision Date:<br>13.09.2024 | SDS Number:<br>800001015845 | Date of last issue: 10.06.2024<br>Print Date 14.09.2024 |
|----------------|------------------------------|-----------------------------|---|

---

### SECTION 12: Ecological information

#### 12.1 Toxicity

**Product:**

|  |   |   |
|--|---|---|
| Toxicity to fish   | : | Remarks: Practically non toxic:<br>LL/EL/IL50 > 100 mg/l  |
| Toxicity to daphnia and other aquatic invertebrates                    | : | Remarks: Practically non toxic:<br>LL/EL/IL50 > 100 mg/l  |
| Toxicity to algae/aquatic plants                                       | : | Remarks: Practically non toxic:<br>LL/EL/IL50 > 100 mg/l  |
| Toxicity to fish (Chronic toxicity)                                    | : | Remarks: Based on available data, the classification criteria are not met.<br>NOEC/NOEL > 100 mg/l                            |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : | Remarks: Based on available data, the classification criteria are not met.<br>NOEC/NOEL > 100 mg/l                            |
| Toxicity to microorganisms   | : | Remarks: Based on available data, the classification criteria are not met.<br>Practically non toxic:<br>LL/EL/IL50 > 100 mg/l |

#### 12.2 Persistence and degradability

**Product:**

|                  |   |                                 |
|------------------|---|---------------------------------|
| Biodegradability | : | Remarks: Readily biodegradable. |
|------------------|---|---------------------------------|

#### 12.3 Bioaccumulative potential

**Product:**

|                 |   |  |
|-----------------|---|--|
| Bioaccumulation | : | Remarks: Does not bioaccumulate significantly. |
|-----------------|---|--|

#### 12.4 Mobility in soil

**Product:**

|          |   |  |
|----------|---|--|
| Mobility | : | Remarks: Liquid under most environmental conditions., If it enters soil, it will adsorb to soil particles and will not be mobile.<br><br>Remarks: Floats on water. |
|----------|---|--|

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

|         |                |              |                                |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 10.06.2024 |
| 3.3     | 13.09.2024     | 800001015845 | Print Date 14.09.2024          |

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB..

### 12.6 Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

**Product:**

Additional ecological information : Does not have ozone depletion potential, photochemical ozone creation potential or global warming potential.  
Product is a mixture of non-volatile components, which will not be released to air in any significant quantities under normal conditions of use.

Films formed on water may affect oxygen transfer and damage organisms.

Causes physical fouling of aquatic organisms.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Recover or recycle if possible.  
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.  
Do not dispose into the environment, in drains or in water courses.  
  
Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.  
Waste, spills or used product is dangerous waste.  
Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.  
Do not dispose of tank water bottoms by allowing them to

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

|                |                              |                             |   |
|----------------|------------------------------|-----------------------------|---|
| Version<br>3.3 | Revision Date:<br>13.09.2024 | SDS Number:<br>800001015845 | Date of last issue: 10.06.2024<br>Print Date 14.09.2024 |
|----------------|------------------------------|-----------------------------|---|

drain into the ground. This will result in soil and groundwater contamination.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.

Contaminated packaging : Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local legislation

Waste catalogue

:

EU Waste Disposal Code (EWC):

Waste Code

:

13 08 99\*

Remarks

: Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Classification of waste is always the responsibility of the end user.

Hazardous Waste (England and Wales) Regulations 2005.

## SECTION 14: Transport information

### 14.1 UN number or ID number

|      |   |                                   |
|------|---|-----------------------------------|
| ADR  | : | Not regulated as a dangerous good |
| RID  | : | Not regulated as a dangerous good |
| IMDG | : | Not regulated as a dangerous good |
| IATA | : | Not regulated as a dangerous good |

### 14.2 UN proper shipping name

|     |   |                                   |
|-----|---|-----------------------------------|
| ADR | : | Not regulated as a dangerous good |
| RID | : | Not regulated as a dangerous good |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

|         |                |              |                                |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 10.06.2024 |
| 3.3     | 13.09.2024     | 800001015845 | Print Date 14.09.2024          |

|      |   |                                   |
|------|---|-----------------------------------|
| IMDG | : | Not regulated as a dangerous good |
| IATA | : | Not regulated as a dangerous good |

### 14.3 Transport hazard class(es)

|      |   |                                   |
|------|---|-----------------------------------|
| ADR  | : | Not regulated as a dangerous good |
| RID  | : | Not regulated as a dangerous good |
| IMDG | : | Not regulated as a dangerous good |
| IATA | : | Not regulated as a dangerous good |

### 14.4 Packing group

|      |   |                                   |
|------|---|-----------------------------------|
| ADR  | : | Not regulated as a dangerous good |
| RID  | : | Not regulated as a dangerous good |
| IMDG | : | Not regulated as a dangerous good |
| IATA | : | Not regulated as a dangerous good |

### 14.5 Environmental hazards

|      |   |                                   |
|------|---|-----------------------------------|
| ADR  | : | Not regulated as a dangerous good |
| RID  | : | Not regulated as a dangerous good |
| IMDG | : | Not regulated as a dangerous good |

### 14.6 Special precautions for user

|         |   |  |
|---------|---|--|
| Remarks | : | Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport. |
|---------|---|--|

### 14.7 Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

|  |   |                |
|--|---|----------------|
| REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) | : | Not applicable |
|--|---|----------------|

|   |   |  |
|---|---|--|
| REACH - List of substances subject to authorisation (Annex XIV) | : | Product is not subject to Authorisation under REACH. |
|---|---|--|

|                            |   |   |
|----------------------------|---|---|
| Volatile organic compounds | : | Volatile organic compounds (VOC) content: 0 % |
|----------------------------|---|---|

Volatile organic compounds (VOC) content: 0 %



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

|         |                |              |                                |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 10.06.2024 |
| 3.3     | 13.09.2024     | 800001015845 | Print Date 14.09.2024          |

### Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Environmental Protection Act 1990 (as amended). Health and Safety at Work etc. Act 1974. Consumers Protection Act 1987. Pollution Prevention and Control Act 1999. Environment Act 1995. Factories Act 1961. The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment (Amendment) Regulations 2011. Chemicals (Hazard Information and Packaging for Supply) Regulations 2009. Control of Substances Hazardous to Health Regulations 2002 (as amended). Merchant Shipping (Dangerous Goods and Marine Pollutants) Regulations 1997. Reporting of Injuries, Diseases and Dangerous Occurrences Regulations 1995 (as amended). Personal Protective Equipment Regulations 2002. Personal Protective Equipment at Work Regulations 1992. Hazardous Waste (England and Wales) Regulations 2005(as amended). Control of Major Accident Hazards Regulations 1999 (as amended). Renewable Transport Fuel Obligations Order 2007 (as amended). Energy Act 2011. Environmental Permitting (England and Wales) Regulations 2010 (as amended). Waste (England and Wales) Regulations 2011 (as amended). Planning (Hazardous Substances) Act 1990 and associated regulations. The Environmental Protection (Controls on Ozone-Depleting Substances) Regulations 2011.

### The components of this product are reported in the following inventories:

REACH : All components listed or polymer exempt.

TSCA : All components listed.

## 15.2 Chemical safety assessment

A Chemical Safety Assessment was performed for this substance.

## SECTION 16: Other information

### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
ACGIH / TWA : 8-hour, time-weighted average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

|         |                |              |                                |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 10.06.2024 |
| 3.3     | 13.09.2024     | 800001015845 | Print Date 14.09.2024          |

- Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Training advice : Provide adequate information, instruction and training for operators.

Other information : A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID data base, EC 1272 regulation, etc).

### Classification of the mixture:

Asp. Tox. 1 H304

### Classification procedure:

Expert judgement and weight of evidence determination.

### Identified Uses according to the Use Descriptor System

#### Uses - Worker

Title : Distribution of substance  
- Industrial

#### Uses - Worker

Title : Formulation & (re)packing of substances and mixtures  
- Industrial

#### Uses - Worker

Title : Metal working fluids / rolling oils  
- Industrial

#### Uses - Worker

Title : Metal working fluids / rolling oils

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

|         |                |              |                                |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 10.06.2024 |
| 3.3     | 13.09.2024     | 800001015845 | Print Date 14.09.2024          |

---

- Professional  
High Environmental Release

### Uses - Worker

Title : Use as binders and release agents  
- Industrial

### Uses - Worker

Title : Use as binders and release agents  
- Professional

### Uses - Worker

Title : Use in agrochemicals  
- Professional

### Uses - Worker

Title : Lubricants  
- Industrial

### Uses - Worker

Title : Lubricants  
- Professional  
Low Environmental Release

### Uses - Worker

Title : Lubricants  
- Professional  
High Environmental Release

### Uses - Worker

Title : Use in laboratories  
- Industrial

### Uses - Worker

Title : Functional Fluids  
- Industrial

### Uses - Worker

Title : Functional Fluids  
- Professional

### Identified Uses according to the Use Descriptor System

#### Uses - Consumer

Title : Use in agrochemicals

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

|         |                |              |                                |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 10.06.2024 |
| 3.3     | 13.09.2024     | 800001015845 | Print Date 14.09.2024          |

---

- Consumer

### Uses - Consumer

Title : Use as a fuel  
- Consumer

### Uses - Consumer

Title : Use in lubricants  
- Consumer  
Low Environmental Release

### Uses - Consumer

Title : Use in lubricants  
- Consumer  
High Environmental Release

### Uses - Consumer

Title : Functional Fluids  
- Consumer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version 3.3      Revision Date: 13.09.2024      SDS Number: 800001015845      Date of last issue: 10.06.2024  
Print Date 14.09.2024

### Exposure Scenario - Worker

**300000010363**

| SECTION 1        | EXPOSURE SCENARIO TITLE  |
|------------------|--|
| Title            | Distribution of substance- Industrial  |
| Use Descriptor   | <b>Sector of Use:</b> SU3<br><b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15<br><b>Environmental Release Categories:</b> ERC4, ERC5, ERC6a, ERC6b, ERC6c, ERC6d, ERC7, ESVOC SpERC 1.1b.v1    |
| Scope of process | Loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its sampling, storage, unloading distribution and associated laboratory activities. |

| SECTION 2  | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES                      |
|--|--|
| Section 2.1  | Control of Worker Exposure   |
| <b>Product Characteristics</b>   |  |
| Physical form of product   | Liquid, vapour pressure < 0.5 kPa with potential for aerosol generation. |
| Concentration of the Substance in Mixture/Article  | Covers use of substance/product up to 100% (unless stated differently)., |
| <b>Frequency and Duration of Use</b>   |  |
| Covers daily exposures up to 8 hours (unless stated differently).  |  |
| <b>Other Operational Conditions affecting Exposure</b>   |  |
| Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented. |  |
| <b>Contributing Scenarios</b>  | <b>Risk Management Measures</b>  |
| General measures (Aspiration)  | Do not ingest. If swallowed, then seek immediate medical assistance      |
| General exposures (closed systems)   | No other specific measures identified.                                   |
| General exposures (open systems)   | No other specific measures identified.                                   |
| Process sampling   | No other specific measures identified.                                   |
| Laboratory activities  | No other specific measures identified.                                   |
| Bulk transfers(closed systems)   | No other specific measures identified.                                   |
| Bulk transfers(open systems)   | No other specific measures identified.                                   |
| Drum and small package filling   | No other specific measures identified.                                   |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version  
3.3

Revision Date:  
13.09.2024

SDS Number:  
800001015845

Date of last issue: 10.06.2024  
Print Date 14.09.2024

|   |  |
|---|--|
| Equipment cleaning and maintenance  | Drain down system prior to equipment opening or maintenance. |
| Bulk product storage  | Store substance within a closed system.                      |
| <b>Section 2.2</b>  | <b>Control of Environmental Exposure</b>                     |
| Substance is complex UVCB.  |  |
| Predominantly hydrophobic.  |  |
| <b>Amounts Used</b>   |  |
| Fraction of EU tonnage used in region:  | 0.1  |
| Regional use tonnage (tonnes/year):   | 8.5E+05  |
| Fraction of Regional tonnage used locally:  | 1  |
| Annual site tonnage (tonnes/year):  | 1.7E+03  |
| Maximum daily site tonnage (kg/day):  | 1.7E+04  |
| <b>Frequency and Duration of Use</b>  |  |
| Continuous release.   |  |
| Emission Days (days/year):  | 100  |
| <b>Environmental factors not influenced by risk management</b>  |  |
| Local freshwater dilution factor:   | 10   |
| Local marine water dilution factor:   | 100  |
| <b>Other Operational Conditions affecting Environmental Exposure</b>  |  |
| Release fraction to air from process (initial release prior to RMM):  | 1.0E-04  |
| Release fraction to wastewater from process (initial release prior to RMM):   | 1.0E-07  |
| Release fraction to soil from process (initial release prior to RMM):   | 1E-05  |
| <b>Technical conditions and measures at process level (source) to prevent release</b>                               |  |
| Common practices vary across sites thus conservative process release estimates used.                                |  |
| <b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>   |  |
| Risk from environmental exposure is driven by freshwater sediment.  |  |
| Prevent discharge of undissolved substance to or recover from onsite wastewater.                                    |  |
| If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.                         |  |
| Treat air emission to provide a typical removal efficiency of (%)   | 90   |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)   | 64.4   |
| If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%) | 0.0  |
| <b>Organisational measures to prevent/limit release from site</b>   |  |
| Do not apply industrial sludge to natural soils.  |  |
| Sludge should be incinerated, contained or reclaimed.   |  |
| <b>Conditions and Measures related to municipal sewage treatment plant</b>  |  |
| Estimated substance removal from wastewater via domestic sewage treatment (%)                                       | 94.7   |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)            | 94.7   |
| Maximum allowable site tonnage (MSafe) based on release following   | 1.1E+05  |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version 3.3      Revision Date: 13.09.2024      SDS Number: 800001015845      Date of last issue: 10.06.2024  
Print Date 14.09.2024

|   |       |
|---|-------|
| total wastewater treatment removal (kg/d)   |       |
| Assumed domestic sewage treatment plant flow (m3/d)   | 2,000 |
| <b>Conditions and Measures related to external treatment of waste for disposal</b>                        |       |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations. |       |
| <b>Conditions and measures related to external recovery of waste</b>                                      |       |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations. |       |

|   |                            |
|---|----------------------------|
| <b>SECTION 3</b>  | <b>EXPOSURE ESTIMATION</b> |
| <b>Section 3.1 - Health</b>   |                            |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated. |                            |
| Risk Management Measures are based on qualitative risk characterisation.                      |                            |

|  |  |
|--|--|
| <b>Section 3.2 -Environment</b>  |  |
| The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model. |  |

|   |  |
|---|--|
| <b>SECTION 4</b>  | <b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b> |
| <b>Section 4.1 - Health</b>   |  |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.<br>Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. |  |

|  |  |
|--|--|
| <b>Section 4.2 -Environment</b>  |  |
| Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.                               |  |
| Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.  |  |
| Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.  |  |
| Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org/en/reach-for-industries-libraries.html">http://cefic.org/en/reach-for-industries-libraries.html</a> ). |  |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version  
3.3

Revision Date:  
13.09.2024

SDS Number:  
800001015845

Date of last issue: 10.06.2024  
Print Date 14.09.2024

### Exposure Scenario - Worker

**300000010364**

| SECTION 1        | EXPOSURE SCENARIO TITLE   |
|------------------|---|
| Title            | Formulation & (re)packing of substances and mixtures- Industrial  |
| Use Descriptor   | <b>Sector of Use:</b> SU10<br><b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC14, PROC15<br><b>Environmental Release Categories:</b> ERC2, ESVOC SpERC 2.2.v1  |
| Scope of process | Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tableting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities. |

| SECTION 2  | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES   |
|--|---|
| Section 2.1  | Control of Worker Exposure  |
| Product Characteristics  |   |
| Physical form of product   | Liquid, vapour pressure < 0.5 kPa with potential for aerosol generation.  |
| Concentration of the Substance in Mixture/Article  | Covers use of substance/product up to 100% (unless stated differently).,  |
| Frequency and Duration of Use  |   |
| Covers daily exposures up to 8 hours (unless stated differently).  |   |
| Other Operational Conditions affecting Exposure  |   |
| Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented. |   |
| Contributing Scenarios   | Risk Management Measures  |
| General measures (Aspiration)  | Do not ingest. If swallowed, then seek immediate medical assistance<br>Risk Management Measures are based on qualitative risk characterisation. |
| General exposures (closed systems)   | No other specific measures identified.  |
| General exposures (open systems)   | No other specific measures identified.  |
| Batch processes at elevated temperatures<br>Use in contained batch processes   | No other specific measures identified.  |
| Process sampling   | No other specific measures identified.  |
| Laboratory activities  | No other specific measures identified.  |



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version  
3.3

Revision Date:  
13.09.2024

SDS Number:  
800001015845

Date of last issue: 10.06.2024  
Print Date 14.09.2024

|   |  |
|---|--|
| Bulk transfersDedicated facility  | No other specific measures identified.                       |
| Mixing operations (open systems)  | No other specific measures identified.                       |
| ManualTransfer from/pouring from containersNon-dedicated facility   | No other specific measures identified.                       |
| Drum/batch transfersDedicated facility  | No other specific measures identified.                       |
| Production or preparation of articles by tableting, compression, extrusion or pelletisation                       | No other specific measures identified.                       |
| Drum and small package filling  | No other specific measures identified.                       |
| Equipment cleaning and maintenance  | Drain down system prior to equipment opening or maintenance. |
| Storage.  | Store substance within a closed system.                      |
| <b>Section 2.2</b>  | <b>Control of Environmental Exposure</b>                     |
| Substance is complex UVCB.  |  |
| Predominantly hydrophobic.  |  |
| <b>Amounts Used</b>   |  |
| Fraction of EU tonnage used in region:  | 0.1  |
| Regional use tonnage (tonnes/year):   | 8.5E+05  |
| Fraction of Regional tonnage used locally:  | 1  |
| Annual site tonnage (tonnes/year):  | 3.0E+04  |
| Maximum daily site tonnage (kg/day):  | 1.0E+05  |
| <b>Frequency and Duration of Use</b>  |  |
| Continuous release.   |  |
| Emission Days (days/year):  | 300  |
| <b>Environmental factors not influenced by risk management</b>  |  |
| Local freshwater dilution factor:   | 10   |
| Local marine water dilution factor:   | 100  |
| <b>Other Operational Conditions affecting Environmental Exposure</b>  |  |
| Release fraction to air from process (initial release prior to RMM):  | 2.5E-03  |
| Release fraction to wastewater from process (initial release prior to RMM):                                       | 5.0E-06  |
| Release fraction to soil from process (initial release prior to RMM):   | 0.0001   |
| <b>Technical conditions and measures at process level (source) to prevent release</b>                             |  |
| Common practices vary across sites thus conservative process release estimates used.                              |  |
| <b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b> |  |
| Risk from environmental exposure is driven by freshwater sediment.  |  |
| Prevent discharge of undissolved substance to or recover from onsite wastewater.                                  |  |
| If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.                       |  |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version 3.3      Revision Date: 13.09.2024      SDS Number: 800001015845      Date of last issue: 10.06.2024  
Print Date 14.09.2024

|   |         |
|---|---------|
| Treat air emission to provide a typical removal efficiency of (%)   | 0       |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of $\geq$ (%) | 69.5    |
| If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%)   | 0.0     |
| <b>Organisational measures to prevent/limit release from site</b>   |         |
| Do not apply industrial sludge to natural soils.  |         |
| Sludge should be incinerated, contained or reclaimed.   |         |
| <b>Conditions and Measures related to municipal sewage treatment plant</b>  |         |
| Estimated substance removal from wastewater via domestic sewage treatment (%)   | 94.7    |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)              | 94.7    |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)           | 5.7E+05 |
| Assumed domestic sewage treatment plant flow (m3/d)   | 2,000   |
| <b>Conditions and Measures related to external treatment of waste for disposal</b>                                    |         |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations.             |         |
| <b>Conditions and measures related to external recovery of waste</b>  |         |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations.             |         |

|   |                            |
|---|----------------------------|
| <b>SECTION 3</b>  | <b>EXPOSURE ESTIMATION</b> |
| <b>Section 3.1 - Health</b>   |                            |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated. |                            |

|  |  |
|--|--|
| <b>Section 3.2 -Environment</b>  |  |
| The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model. |  |

|   |  |
|---|--|
| <b>SECTION 4</b>  | <b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b> |
| <b>Section 4.1 - Health</b>   |  |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.<br>Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. |  |

|  |  |
|--|--|
| <b>Section 4.2 -Environment</b>  |  |
| Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. |  |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version  
3.3

Revision Date:  
13.09.2024

SDS Number:  
800001015845

Date of last issue: 10.06.2024  
Print Date 14.09.2024

---

|   |
|---|
| Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. |
|---|

|   |
|---|
| Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination. |
|---|

|  |
|--|
| Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org/en/reach-for-industries-libraries.html">http://cefic.org/en/reach-for-industries-libraries.html</a> ). |
|--|

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version  
3.3

Revision Date:  
13.09.2024

SDS Number:  
800001015845

Date of last issue: 10.06.2024  
Print Date 14.09.2024

### Exposure Scenario - Worker

**300000010372**

| SECTION 1        | EXPOSURE SCENARIO TITLE   |
|------------------|---|
| Title            | Metal working fluids / rolling oils- Industrial   |
| Use Descriptor   | <b>Sector of Use:</b> SU3<br><b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC17<br><b>Environmental Release Categories:</b> ERC4, ESVOC SpERC 4.7a.v1   |
| Scope of process | Covers the use in formulated MWFs/rolling oils including transfer operations, rolling and annealing activities, cutting/machining activities, automated and manual application of corrosion protections (including brushing, dipping and spraying), equipment maintenance, draining and disposal of waste oils. |

| SECTION 2  | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES                      |
|--|--|
| Section 2.1  | Control of Worker Exposure   |
| <b>Product Characteristics</b>   |  |
| Physical form of product   | Liquid, vapour pressure < 0.5 kPa with potential for aerosol generation. |
| Concentration of the Substance in Mixture/Article  | Covers use of substance/product up to 100% (unless stated differently)., |
| <b>Frequency and Duration of Use</b>   |  |
| Covers daily exposures up to 8 hours (unless stated differently).  |  |
| <b>Other Operational Conditions affecting Exposure</b>   |  |
| Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented. |  |
| <b>Contributing Scenarios</b>  | <b>Risk Management Measures</b>  |
| General measures (Aspiration)  | Do not ingest. If swallowed, then seek immediate medical assistance      |
| General exposures (closed systems)   | No other specific measures identified.                                   |
| General exposures (open systems)   | No other specific measures identified.                                   |
| Bulk transfersDedicated facility   | No other specific measures identified.                                   |
| Filling/ preparation of equipment from drums or containers.Dedicated facility  | No other specific measures identified.                                   |
| Process sampling   | No other specific measures identified.                                   |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version  
3.3

Revision Date:  
13.09.2024

SDS Number:  
800001015845

Date of last issue: 10.06.2024  
Print Date 14.09.2024

|   |   |
|---|---|
| Metal machining operations  | Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings. |
| Treatment by dipping and pouring  | No other specific measures identified.  |
| Spraying  | Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings. |
| Manual Rolling, Brushing  | No other specific measures identified.  |
| Automated metal rolling/forming<br>Use in contained system<br>elevated temperature    | No other specific measures identified.  |
| Semi-automated metal rolling/forming<br>elevated temperature                          | Provide extraction ventilation at points where emissions occur.   |
| Semi-automated metal rolling/forming  | No other specific measures identified.  |
| Equipment cleaning and maintenance<br>Dedicated facility                              | Drain down system prior to equipment opening or maintenance.  |
| Equipment cleaning and maintenance<br>Non-dedicated facility                          | Drain down system prior to equipment opening or maintenance.  |
| Storage.  | Store substance within a closed system.   |
| <b>Section 2.2</b>  | <b>Control of Environmental Exposure</b>  |
| Substance is complex UVCB.  |   |
| Predominantly hydrophobic.  |   |
| <b>Amounts Used</b>   |   |
| Fraction of EU tonnage used in region:  | 0.1   |
| Regional use tonnage (tonnes/year):   | 4.2E+03   |
| Fraction of Regional tonnage used locally:  | 1   |
| Annual site tonnage (tonnes/year):  | 1.0E+02   |
| Maximum daily site tonnage (kg/day):  | 5.0E+03   |
| <b>Frequency and Duration of Use</b>  |   |
| Continuous release.   |   |
| Emission Days (days/year):  | 20  |
| <b>Environmental factors not influenced by risk management</b>                        |   |
| Local freshwater dilution factor:   | 10  |
| Local marine water dilution factor:   | 100   |
| <b>Other Operational Conditions affecting Environmental Exposure</b>                  |   |
| Release fraction to air from process (initial release prior to RMM):                  | 0.02  |
| Release fraction to wastewater from process (initial release prior to RMM):           | 1.0E-06   |
| Release fraction to soil from process (initial release prior to RMM):                 | 0   |
| <b>Technical conditions and measures at process level (source) to prevent release</b> |   |
| Common practices vary across sites thus conservative process release estimates used.  |   |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version 3.3      Revision Date: 13.09.2024      SDS Number: 800001015845      Date of last issue: 10.06.2024  
Print Date 14.09.2024

|   |         |
|---|---------|
| <b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>   |         |
| Risk from environmental exposure is driven by freshwater sediment.  |         |
| Prevent discharge of undissolved substance to or recover from onsite wastewater.                                    |         |
| If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.                         |         |
| Treat air emission to provide a typical removal efficiency of (%)   | 70      |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)   | 64.5    |
| If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%) | 0.0     |
| <b>Organisational measures to prevent/limit release from site</b>   |         |
| Do not apply industrial sludge to natural soils.  |         |
| Sludge should be incinerated, contained or reclaimed.   |         |
| <b>Conditions and Measures related to municipal sewage treatment plant</b>  |         |
| Estimated substance removal from wastewater via domestic sewage treatment (%)                                       | 94.7    |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)            | 94.7    |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)         | 3.3E+04 |
| Assumed domestic sewage treatment plant flow (m3/d)   | 2,000   |
| <b>Conditions and Measures related to external treatment of waste for disposal</b>                                  |         |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations.           |         |
| <b>Conditions and measures related to external recovery of waste</b>  |         |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations.           |         |

|   |                            |
|---|----------------------------|
| <b>SECTION 3</b>  | <b>EXPOSURE ESTIMATION</b> |
| <b>Section 3.1 - Health</b>   |                            |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated. |                            |
| Risk Management Measures are based on qualitative risk characterisation.                      |                            |

|  |  |
|--|--|
| <b>Section 3.2 -Environment</b>  |  |
| The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model. |  |

|   |  |
|---|--|
| <b>SECTION 4</b>  | <b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b> |
| <b>Section 4.1 - Health</b>   |  |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management |  |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version  
3.3

Revision Date:  
13.09.2024

SDS Number:  
800001015845

Date of last issue: 10.06.2024  
Print Date 14.09.2024

Measures/Operational Conditions outlined in Section 2 are implemented.  
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version  
3.3

Revision Date:  
13.09.2024

SDS Number:  
800001015845

Date of last issue: 10.06.2024  
Print Date 14.09.2024

### Exposure Scenario - Worker

**300000010373**

| SECTION 1        | EXPOSURE SCENARIO TITLE   |
|------------------|---|
| Title            | Metal working fluids / rolling oils- ProfessionalHigh Environmental Release   |
| Use Descriptor   | <b>Sector of Use:</b> SU22<br><b>Process Categories:</b> PROC1, PROC2, PROC3, PROC5, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC17<br><b>Environmental Release Categories:</b> ERC8a, ERC8d, ESVOC SpERC 8.7c.v1   |
| Scope of process | Covers the use in formulated MWFs/rolling oils including transfer operations, rolling and annealing activities, cutting/machining activities, automated and manual application of corrosion protections (including brushing, dipping and spraying), equipment maintenance, draining and disposal of waste oils.<br>Covers the use in formulated MWFs/rolling oils within closed or contained systems including incidental exposures during transfer operations, rolling and annealing activities, cutting/machining activities, automated application of corrosion protections, equipment maintenance, draining and disposal of waste oils. |

| SECTION 2  | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES                      |
|--|--|
| Section 2.1  | Control of Worker Exposure   |
| <b>Product Characteristics</b>   |  |
| Physical form of product   | Liquid, vapour pressure < 0.5 kPa with potential for aerosol generation. |
| Concentration of the Substance in Mixture/Article  | Covers use of substance/product up to 100% (unless stated differently)., |
| <b>Frequency and Duration of Use</b>   |  |
| Covers daily exposures up to 8 hours (unless stated differently).  |  |
| <b>Other Operational Conditions affecting Exposure</b>   |  |
| Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented. |  |
| <b>Contributing Scenarios</b>  | <b>Risk Management Measures</b>  |
| General measures (Aspiration)  | Do not ingest. If swallowed, then seek immediate medical assistance      |
| General exposures (closed systems)(closed systems)   | No other specific measures identified.                                   |
| Bulk transfersDedicated facility   | No other specific measures identified.                                   |
| Filling/ preparation of  | No other specific measures identified.                                   |



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version  
3.3

Revision Date:  
13.09.2024

SDS Number:  
800001015845

Date of last issue: 10.06.2024  
Print Date 14.09.2024

|   |  |
|---|--|
| equipment from drums or containers.Dedicated facility                             |  |
| Filling/ preparation of equipment from drums or containers.Non-dedicated facility | Avoid carrying out activities involving exposure for more than 1 hour.   |
| Process sampling  | No other specific measures identified.   |
| Metal machining operations  | Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour).<br>Avoid carrying out activities involving exposure for more than 4 hours<br>Limit the substance content in the product to 25 %.                            |
| Spraying  | Avoid carrying out activities involving exposure for more than 1 hour.<br>Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).<br>, or:<br>Wear a respirator conforming to EN140 with Type A/P2 filter or better. |
| ManualRolling, Brushing   | No other specific measures identified.   |
| Treatment by dipping and pouring  | No other specific measures identified.   |
| Equipment cleaning and maintenance  | Drain down system prior to equipment opening or maintenance.   |
| Storage.  | Store substance within a closed system.  |
| <b>Section 2.2</b>  | <b>Control of Environmental Exposure</b>   |
| Substance is complex UVCB.  |  |
| Predominantly hydrophobic.  |  |
| <b>Amounts Used</b>   |  |
| Fraction of EU tonnage used in region:  | 0.1  |
| Regional use tonnage (tonnes/year):   | 9.0E+02  |
| Fraction of Regional tonnage used locally:  | 1  |
| Annual site tonnage (tonnes/year):  | 4.5E-01  |
| Maximum daily site tonnage (kg/day):  | 1.2E+00  |
| <b>Frequency and Duration of Use</b>  |  |
| Continuous release.   |  |
| Emission Days (days/year):  | 365  |
| <b>Environmental factors not influenced by risk management</b>                    |  |
| Local freshwater dilution factor:   | 10   |
| Local marine water dilution factor:   | 100  |
| <b>Other Operational Conditions affecting Environmental Exposure</b>              |  |
| Release fraction to air from process (initial release prior to RMM):              | 5.0E-03  |
| Release fraction to wastewater from process (initial release prior to RMM):       | 0.05   |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version 3.3      Revision Date: 13.09.2024      SDS Number: 800001015845      Date of last issue: 10.06.2024  
Print Date 14.09.2024

|   |         |
|---|---------|
| Release fraction to soil from process (initial release prior to RMM):   | 0.05    |
| <b>Technical conditions and measures at process level (source) to prevent release</b>                               |         |
| Common practices vary across sites thus conservative process release estimates used.                                |         |
| <b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>   |         |
| Risk from environmental exposure is driven by freshwater sediment.  |         |
| If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.                         |         |
| Treat air emission to provide a typical removal efficiency of (%)   | 0       |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)   | 65.1    |
| If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%) | 0.0     |
| <b>Organisational measures to prevent/limit release from site</b>   |         |
| Do not apply industrial sludge to natural soils.  |         |
| Sludge should be incinerated, contained or reclaimed.   |         |
| <b>Conditions and Measures related to municipal sewage treatment plant</b>  |         |
| Estimated substance removal from wastewater via domestic sewage treatment (%)                                       | 94.7    |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)            | 94.7    |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)         | 8.1E+00 |
| Assumed domestic sewage treatment plant flow (m3/d)   | 2,000   |
| <b>Conditions and Measures related to external treatment of waste for disposal</b>                                  |         |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations.           |         |
| <b>Conditions and measures related to external recovery of waste</b>  |         |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations.           |         |

|   |                            |
|---|----------------------------|
| <b>SECTION 3</b>  | <b>EXPOSURE ESTIMATION</b> |
| <b>Section 3.1 - Health</b>   |                            |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated. |                            |

|  |  |
|--|--|
| <b>Section 3.2 -Environment</b>  |  |
| The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model. |  |

|   |  |
|---|--|
| <b>SECTION 4</b>  | <b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b> |
| <b>Section 4.1 - Health</b>   |  |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management |  |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

|         |                |              |                                |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 10.06.2024 |
| 3.3     | 13.09.2024     | 800001015845 | Print Date 14.09.2024          |

Measures/Operational Conditions outlined in Section 2 are implemented.  
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version  
3.3

Revision Date:  
13.09.2024

SDS Number:  
800001015845

Date of last issue: 10.06.2024  
Print Date 14.09.2024

### Exposure Scenario - Worker

**300000010374**

| SECTION 1        | EXPOSURE SCENARIO TITLE   |
|------------------|---|
| Title            | Use as binders and release agents- Industrial   |
| Use Descriptor   | <b>Sector of Use:</b> SU3<br><b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC6, PROC7, PROC8b, PROC10, PROC13, PROC14<br><b>Environmental Release Categories:</b> ERC4, ESVOC SpERC 4.10a.v1 |
| Scope of process | Covers the use as binders and release agents including material transfers, mixing, application by spraying, brushing, and handling of waste.  |

| SECTION 2  | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES   |
|--|---|
| Section 2.1  | Control of Worker Exposure  |
| Product Characteristics  |   |
| Physical form of product   | Liquid, vapour pressure < 0.5 kPa with potential for aerosol generation.  |
| Concentration of the Substance in Mixture/Article  | Covers use of substance/product up to 100% (unless stated differently).,  |
| Frequency and Duration of Use  |   |
| Covers daily exposures up to 8 hours (unless stated differently).  |   |
| Other Operational Conditions affecting Exposure  |   |
| Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented. |   |
| Contributing Scenarios   | Risk Management Measures  |
| General measures (Aspiration)  | Do not ingest. If swallowed, then seek immediate medical assistance   |
| Material transfers(closed systems)   | No other specific measures identified.  |
| Drum/batch transfersDedicated facility   | No other specific measures identified.  |
| Mixing operations (closed systems)   | No other specific measures identified.  |
| Mixing operations (open systems)   | No other specific measures identified.  |
| Dipping, immersion and pouring   | No other specific measures identified.  |
| Mold forming   | No other specific measures identified.  |
| Casting operations(open systems)elevated temperature   | Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings. |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version 3.3      Revision Date: 13.09.2024      SDS Number: 800001015845      Date of last issue: 10.06.2024  
Print Date 14.09.2024

|   |   |
|---|---|
| Spraying  | Carry out in a vented booth or extracted enclosure.<br>, or:<br>Wear a full face respirator conforming to EN140 with Type A filter or better. |
| ManualRolling, Brushing   | No other specific measures identified.  |
| Treatment by dipping and pouring  | No other specific measures identified.  |
| Equipment cleaning and maintenance  | Drain down system prior to equipment opening or maintenance.  |
| Storage.  | Store substance within a closed system.   |
| <b>Section 2.2</b>  | <b>Control of Environmental Exposure</b>  |
| Substance is complex UVCB.  |   |
| Predominantly hydrophobic.  |   |
| <b>Amounts Used</b>   |   |
| Fraction of EU tonnage used in region:  | 0.1   |
| Regional use tonnage (tonnes/year):   | 3.7E+03   |
| Fraction of Regional tonnage used locally:  | 1   |
| Annual site tonnage (tonnes/year):  | 2.5E+03   |
| Maximum daily site tonnage (kg/day):  | 2.5E+04   |
| <b>Frequency and Duration of Use</b>  |   |
| Continuous release.   |   |
| Emission Days (days/year):  | 100   |
| <b>Environmental factors not influenced by risk management</b>  |   |
| Local freshwater dilution factor:   | 10  |
| Local marine water dilution factor:   | 100   |
| <b>Other Operational Conditions affecting Environmental Exposure</b>  |   |
| Release fraction to air from process (initial release prior to RMM):  | 1.0   |
| Release fraction to wastewater from process (initial release prior to RMM):   | 1.0E-07   |
| Release fraction to soil from process (initial release prior to RMM):   | 0.0   |
| <b>Technical conditions and measures at process level (source) to prevent release</b>                               |   |
| Common practices vary across sites thus conservative process release estimates used.                                |   |
| <b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>   |   |
| Risk from environmental exposure is driven by freshwater sediment.  |   |
| Prevent discharge of undissolved substance to or recover from onsite wastewater.                                    |   |
| If discharging to domestic sewage treatment plant, no onsite wastewater treatment required.                         |   |
| Treat air emission to provide a typical removal efficiency of (%)   | 80  |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)   | 64.4  |
| If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%) | 0   |
| <b>Organisational measures to prevent/limit release from site</b>   |   |
| Do not apply industrial sludge to natural soils.  |   |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version 3.3      Revision Date: 13.09.2024      SDS Number: 800001015845      Date of last issue: 10.06.2024  
Print Date 14.09.2024

|   |         |
|---|---------|
| Sludge should be incinerated, contained or reclaimed.   |         |
| <b>Conditions and Measures related to municipal sewage treatment plant</b>                                  |         |
| Estimated substance removal from wastewater via domestic sewage treatment (%)                               | 94.7    |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)    | 94.7    |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) | 1.4E+05 |
| Assumed domestic sewage treatment plant flow (m3/d)   | 2,000   |
| <b>Conditions and Measures related to external treatment of waste for disposal</b>                          |         |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations.   |         |
| <b>Conditions and measures related to external recovery of waste</b>  |         |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations.   |         |

|   |                            |
|---|----------------------------|
| <b>SECTION 3</b>  | <b>EXPOSURE ESTIMATION</b> |
| <b>Section 3.1 - Health</b>   |                            |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated. |                            |
| Risk Management Measures are based on qualitative risk characterisation.                      |                            |

|  |  |
|--|--|
| <b>Section 3.2 -Environment</b>  |  |
| The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model. |  |

|   |  |
|---|--|
| <b>SECTION 4</b>  | <b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b> |
| <b>Section 4.1 - Health</b>   |  |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.<br>Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. |  |

|  |  |
|--|--|
| <b>Section 4.2 -Environment</b>  |  |
| Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. |  |
| Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.  |  |
| Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.  |  |
| Further details on scaling and control technologies are provided in SpERC factsheet  |  |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version  
3.3

Revision Date:  
13.09.2024

SDS Number:  
800001015845

Date of last issue: 10.06.2024  
Print Date 14.09.2024

---

(<http://cefic.org/en/reach-for-industries-libraries.html>).

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version  
3.3

Revision Date:  
13.09.2024

SDS Number:  
800001015845

Date of last issue: 10.06.2024  
Print Date 14.09.2024

### Exposure Scenario - Worker

**300000010378**

| SECTION 1        | EXPOSURE SCENARIO TITLE   |
|------------------|---|
| Title            | Use as binders and release agents- Professional   |
| Use Descriptor   | <b>Sector of Use:</b> SU22<br><b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC6, PROC8a, PROC8b, PROC10, PROC11, PROC14<br><b>Environmental Release Categories:</b> ERC8a, ERC8d, ESVOC SpERC 8.10b.v1 |
| Scope of process | Covers the use as binders and release agents including material transfers, mixing, application by spraying, brushing, and handling of waste.  |

| SECTION 2  | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES                      |
|--|--|
| Section 2.1  | Control of Worker Exposure   |
| Product Characteristics  |  |
| Physical form of product   | Liquid, vapour pressure < 0.5 kPa with potential for aerosol generation. |
| Concentration of the Substance in Mixture/Article  | Covers use of substance/product up to 100% (unless stated differently)., |
| Frequency and Duration of Use  |  |
| Covers daily exposures up to 8 hours (unless stated differently).  |  |
| Other Operational Conditions affecting Exposure  |  |
| Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented. |  |
| Contributing Scenarios   | Risk Management Measures   |
| General measures (Aspiration)  | Do not ingest. If swallowed, then seek immediate medical assistance      |
| Material transfers(closed systems)   | No other specific measures identified.                                   |
| Drum/batch transfersDedicated facility   | No other specific measures identified.                                   |
| Drum/batch transfersNon-dedicated facility   | Avoid carrying out activities involving exposure for more than 1 hour.   |
| Mixing operations (closed systems)   | No other specific measures identified.                                   |
| Mixing operations (open systems)   | No other specific measures identified.                                   |
| Mold forming   | No other specific measures identified.                                   |
| Casting operations(open systems)elevated tempera-  | Provide extraction ventilation at points where emissions occur.          |



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version  
3.3

Revision Date:  
13.09.2024

SDS Number:  
800001015845

Date of last issue: 10.06.2024  
Print Date 14.09.2024

|   |   |
|---|---|
| ture  |   |
| SprayingMachine   | Carry out in a vented booth or extracted enclosure.<br>Avoid carrying out activities involving exposure for more than 4 hours   |
| SprayingManual  | Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).<br>Avoid carrying out activities involving exposure for more than 1 hour.<br>, or:<br>Wear a respirator conforming to EN140 with Type A filter or better. |
| ManualRolling, Brushing   | No other specific measures identified.  |
| Equipment cleaning and maintenance  | Drain down system prior to equipment opening or maintenance.  |
| Storage.  | Store substance within a closed system.   |
| <b>Section 2.2</b>  | <b>Control of Environmental Exposure</b>  |
| Substance is complex UVCB.  |   |
| Predominantly hydrophobic.  |   |
| <b>Amounts Used</b>   |   |
| Fraction of EU tonnage used in region:  | 0.1   |
| Regional use tonnage (tonnes/year):   | 2.7E+03   |
| Fraction of Regional tonnage used locally:  | 1   |
| Annual site tonnage (tonnes/year):  | 1.3E+00   |
| Maximum daily site tonnage (kg/day):  | 3.7E+00   |
| <b>Frequency and Duration of Use</b>  |   |
| Continuous release.   |   |
| Emission Days (days/year):  | 365   |
| <b>Environmental factors not influenced by risk management</b>  |   |
| Local freshwater dilution factor:   | 10  |
| Local marine water dilution factor:   | 100   |
| <b>Other Operational Conditions affecting Environmental Exposure</b>  |   |
| Release fraction to air from wide dispersive use (regional only):   | 0.95  |
| Release fraction to wastewater from wide dispersive use:  | 0.025   |
| Release fraction to soil from wide dispersive use (regional only):  | 0.025   |
| <b>Technical conditions and measures at process level (source) to prevent release</b>                               |   |
| Common practices vary across sites thus conservative process release estimates used.                                |   |
| <b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>   |   |
| Risk from environmental exposure is driven by freshwater sediment.  |   |
| Treat air emission to provide a typical removal efficiency of (%)   | 0   |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)   | 65.5  |
| If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%) | 0   |
| <b>Organisational measures to prevent/limit release from site</b>   |   |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version 3.3      Revision Date: 13.09.2024      SDS Number: 800001015845      Date of last issue: 10.06.2024  
Print Date 14.09.2024

|   |         |
|---|---------|
| Do not apply industrial sludge to natural soils.  |         |
| Sludge should be incinerated, contained or reclaimed.   |         |
| <b>Conditions and Measures related to municipal sewage treatment plant</b>                                  |         |
| Estimated substance removal from wastewater via domestic sewage treatment (%)                               | 94.7    |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMS (%)    | 94.7    |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) | 2.4E+01 |
| Assumed domestic sewage treatment plant flow (m3/d)   | 2,000   |
| <b>Conditions and Measures related to external treatment of waste for disposal</b>                          |         |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations.   |         |
| <b>Conditions and measures related to external recovery of waste</b>  |         |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations.   |         |

|   |                            |
|---|----------------------------|
| <b>SECTION 3</b>  | <b>EXPOSURE ESTIMATION</b> |
| <b>Section 3.1 - Health</b>   |                            |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated. |                            |
| Risk Management Measures are based on qualitative risk characterisation.                      |                            |

|  |  |
|--|--|
| <b>Section 3.2 -Environment</b>  |  |
| The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model. |  |

|   |  |
|---|--|
| <b>SECTION 4</b>  | <b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b> |
| <b>Section 4.1 - Health</b>   |  |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.<br>Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. |  |

|  |  |
|--|--|
| <b>Section 4.2 -Environment</b>  |  |
| Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. |  |
| Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.  |  |
| Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.  |  |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version  
3.3

Revision Date:  
13.09.2024

SDS Number:  
800001015845

Date of last issue: 10.06.2024  
Print Date 14.09.2024

---

|  |
|--|
| Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org/en/reach-for-industries-libraries.html">http://cefic.org/en/reach-for-industries-libraries.html</a> ). |
|--|

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version  
3.3

Revision Date:  
13.09.2024

SDS Number:  
800001015845

Date of last issue: 10.06.2024  
Print Date 14.09.2024

### Exposure Scenario - Worker

**300000010379**

| SECTION 1        | EXPOSURE SCENARIO TITLE   |
|------------------|---|
| Title            | Use in agrochemicals- Professional  |
| Use Descriptor   | <b>Sector of Use:</b> SU22<br><b>Process Categories:</b> PROC1, PROC2, PROC4, PROC8a, PROC8b, PROC11, PROC13<br><b>Environmental Release Categories:</b> ERC8a, ERC8d, ESVOC SpERC 8.11a.v1 |
| Scope of process | Use as an agrochemical excipient for application by manual or machine spraying, smokes and fogging; including equipment clean-downs and disposal.   |

| SECTION 2  | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES   |
|--|---|
| Section 2.1  | Control of Worker Exposure  |
| <b>Product Characteristics</b>   |   |
| Physical form of product   | Liquid, vapour pressure < 0.5 kPa with potential for aerosol generation.  |
| Concentration of the Substance in Mixture/Article  | Covers use of substance/product up to 100% (unless stated differently).,  |
| <b>Frequency and Duration of Use</b>   |   |
| Covers daily exposures up to 8 hours (unless stated differently).  |   |
| <b>Other Operational Conditions affecting Exposure</b>   |   |
| Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented. |   |
| <b>Contributing Scenarios</b>  | <b>Risk Management Measures</b>   |
| General measures (Aspiration)  | Do not ingest. If swallowed, then seek immediate medical assistance   |
| Transfer from/pouring from containersDedicated facility  | No other specific measures identified.  |
| Mixing operations (open systems)   | No other specific measures identified.  |
| Spraying/ fogging by manual application  | Wear a respirator conforming to EN140 with Type A filter or better.   |
| Spraying/ fogging by machine application   | Apply within a vented cab supplied with filtered air under positive pressure and with a protection factor of >20. |
| Ad hoc manual application via trigger sprays, dipping, etc.  | No other specific measures identified.  |
| Equipment cleaning and maintenance   | Drain down system prior to equipment opening or maintenance.  |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version  
3.3

Revision Date:  
13.09.2024

SDS Number:  
800001015845

Date of last issue: 10.06.2024  
Print Date 14.09.2024

|   |  |
|---|--|
| Storage.  | Store substance within a closed system.  |
| <b>Section 2.2</b>  | <b>Control of Environmental Exposure</b> |
| Substance is complex UVCB.  |  |
| Predominantly hydrophobic.  |  |
| <b>Amounts Used</b>   |  |
| Fraction of EU tonnage used in region:  | 0.1                                      |
| Regional use tonnage (tonnes/year):   | 7.5E+03                                  |
| Fraction of Regional tonnage used locally:  | 1  |
| Annual site tonnage (tonnes/year):  | 1.5E+01                                  |
| Maximum daily site tonnage (kg/day):  | 4.1E+01                                  |
| <b>Frequency and Duration of Use</b>  |  |
| Continuous release.   |  |
| Emission Days (days/year):  | 365                                      |
| <b>Environmental factors not influenced by risk management</b>  |  |
| Local freshwater dilution factor:   | 10                                       |
| Local marine water dilution factor:   | 100                                      |
| <b>Other Operational Conditions affecting Environmental Exposure</b>  |  |
| Release fraction to air from wide dispersive use (regional only):   | 0.9                                      |
| Release fraction to wastewater from wide dispersive use:  | 0.01                                     |
| Release fraction to soil from wide dispersive use (regional only):  | 0.09                                     |
| <b>Technical conditions and measures at process level (source) to prevent release</b>                               |  |
| Common practices vary across sites thus conservative process re-release estimates used.                             |  |
| <b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>   |  |
| Risk from environmental exposure is driven by freshwater sediment.  |  |
| Treat air emission to provide a typical removal efficiency of (%)   | 0  |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)   | 68.7                                     |
| If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%) | 0  |
| <b>Organisational measures to prevent/limit release from site</b>   |  |
| Do not apply industrial sludge to natural soils.  |  |
| Sludge should be incinerated, contained or reclaimed.   |  |
| <b>Conditions and Measures related to municipal sewage treatment plant</b>  |  |
| Estimated substance removal from wastewater via domestic sewage treatment (%)                                       | 94.7                                     |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)            | 94.7                                     |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)         | 2.4E+02                                  |
| Assumed domestic sewage treatment plant flow (m3/d)   | 2,000                                    |
| <b>Conditions and Measures related to external treatment of waste for disposal</b>                                  |  |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations.           |  |
| <b>Conditions and measures related to external recovery of waste</b>  |  |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

|         |                |              |                                |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 10.06.2024 |
| 3.3     | 13.09.2024     | 800001015845 | Print Date 14.09.2024          |

External recovery and recycling of waste should comply with applicable local and/or regional regulations.

### SECTION 3 EXPOSURE ESTIMATION

#### Section 3.1 - Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Risk Management Measures are based on qualitative risk characterisation.

#### Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

### SECTION 4 GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

#### Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.  
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

#### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version  
3.3

Revision Date:  
13.09.2024

SDS Number:  
800001015845

Date of last issue: 10.06.2024  
Print Date 14.09.2024

### Exposure Scenario - Worker

|                         |  |
|-------------------------|--|
| <b>300000010388</b>     |  |
| <b>SECTION 1</b>        | <b>EXPOSURE SCENARIO TITLE</b>   |
| <b>Title</b>            | Lubricants- Industrial   |
| <b>Use Descriptor</b>   | <b>Sector of Use:</b> SU3<br><b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC17, PROC18<br><b>Environmental Release Categories:</b> ERC4, ERC7, ESVOC SpERC 4.6a.v1       |
| <b>Scope of process</b> | Covers the use of formulated lubricants in closed and open systems including transfer operations, operation of machinery/engines and similar articles, reworking on reject articles, equipment maintenance and disposal of wastes. |

|  |  |
|--|--|
| <b>SECTION 2</b>   | <b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>               |
| <b>Section 2.1</b>   | <b>Control of Worker Exposure</b>  |
| <b>Product Characteristics</b>   |  |
| Physical form of product   | Liquid, vapour pressure < 0.5 kPa with potential for aerosol generation. |
| Concentration of the Substance in Mixture/Article  | Covers use of substance/product up to 100% (unless stated differently)., |
| <b>Frequency and Duration of Use</b>   |  |
| Covers daily exposures up to 8 hours (unless stated differently).  |  |
| <b>Other Operational Conditions affecting Exposure</b>   |  |
| Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented. |  |
| <b>Contributing Scenarios</b>  | <b>Risk Management Measures</b>  |
| General measures (Aspiration)  | Do not ingest. If swallowed, then seek immediate medical assistance      |
| General exposures (closed systems)   | No other specific measures identified.                                   |
| General exposures (open systems)   | No other specific measures identified.                                   |
| Bulk transfersDedicated facility   | No other specific measures identified.                                   |
| Filling/ preparation of equipment from drums or containers.Non-dedicated facility  | No other specific measures identified.                                   |
| Initial factory fill of equipment  | No other specific measures identified.                                   |
| Operation and lubrication of   | Provide extraction ventilation at points where emissions oc-             |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version  
3.3

Revision Date:  
13.09.2024

SDS Number:  
800001015845

Date of last issue: 10.06.2024  
Print Date 14.09.2024

|   |   |
|---|---|
| high energy open equipment  | cur.  |
| ManualRolling, Brushing   | No other specific measures identified.  |
| Treatment by dipping and pouring  | No other specific measures identified.  |
| Spraying  | Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings. |
| Maintenance (of larger plant items) and machine set upDedicated facilityelevated temperature                        | No other specific measures identified.  |
| Maintenance of small itemsNon-dedicated facility  | No other specific measures identified.  |
| Remanufacture of reject articles  | No other specific measures identified.  |
| Storage.  | Store substance within a closed system.   |
| <b>Section 2.2</b>  | <b>Control of Environmental Exposure</b>  |
| Substance is complex UVCB.  |   |
| Predominantly hydrophobic.  |   |
| <b>Amounts Used</b>   |   |
| Fraction of EU tonnage used in region:  | 0.1   |
| Regional use tonnage (tonnes/year):   | 3.1E+05   |
| Fraction of Regional tonnage used locally:  | 1   |
| Annual site tonnage (tonnes/year):  | 1.0E+02   |
| Maximum daily site tonnage (kg/day):  | 5.0E+03   |
| <b>Frequency and Duration of Use</b>  |   |
| Continuous release.   |   |
| Emission Days (days/year):  | 20  |
| <b>Environmental factors not influenced by risk management</b>  |   |
| Local freshwater dilution factor:   | 10  |
| Local marine water dilution factor:   | 100   |
| <b>Other Operational Conditions affecting Environmental Exposure</b>  |   |
| Release fraction to air from process (initial release prior to RMM):  | 5.0E-04   |
| Release fraction to wastewater from process (initial release prior to RMM):   | 1.0E-06   |
| Release fraction to soil from process (initial release prior to RMM):   | 0.001   |
| <b>Technical conditions and measures at process level (source) to prevent release</b>                               |   |
| Common practices vary across sites thus conservative process release estimates used.                                |   |
| <b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>   |   |
| Risk from environmental exposure is driven by freshwater sediment.  |   |
| Treat air emission to provide a typical removal efficiency of (%)   | 70  |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)   | 64.5  |
| If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%) | 0.0   |
| <b>Organisational measures to prevent/limit release from site</b>   |   |



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version 3.3      Revision Date: 13.09.2024      SDS Number: 800001015845      Date of last issue: 10.06.2024  
Print Date 14.09.2024

Do not apply industrial sludge to natural soils.  
Sludge should be incinerated, contained or reclaimed.

### Conditions and Measures related to municipal sewage treatment plant

|   |      |
|---|------|
| Estimated substance removal from wastewater via domestic sewage treatment (%) | 94.7 |
|---|------|

|  |      |
|--|------|
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%) | 94.7 |
|--|------|

|   |         |
|---|---------|
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) | 3.3E+04 |
|---|---------|

|   |       |
|---|-------|
| Assumed domestic sewage treatment plant flow (m3/d) | 2,000 |
|---|-------|

### Conditions and Measures related to external treatment of waste for disposal

External treatment and disposal of waste should comply with applicable local and/or regional regulations.

### Conditions and measures related to external recovery of waste

External recovery and recycling of waste should comply with applicable local and/or regional regulations.

## SECTION 3

### EXPOSURE ESTIMATION

#### Section 3.1 - Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Risk Management Measures are based on qualitative risk characterisation.

#### Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

## SECTION 4

### GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

#### Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.  
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

#### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

|         |                |              |                                |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 10.06.2024 |
| 3.3     | 13.09.2024     | 800001015845 | Print Date 14.09.2024          |

---

|  |
|--|
| ( <a href="http://cefic.org/en/reach-for-industries-libraries.html">http://cefic.org/en/reach-for-industries-libraries.html</a> ). |
|--|

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version  
3.3

Revision Date:  
13.09.2024

SDS Number:  
800001015845

Date of last issue: 10.06.2024  
Print Date 14.09.2024

### Exposure Scenario - Worker

**300000010389**

| SECTION 1        | EXPOSURE SCENARIO TITLE   |
|------------------|---|
| Title            | Lubricants- ProfessionalLow Environmental Release   |
| Use Descriptor   | <b>Sector of Use:</b> SU22<br><b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC13, PROC17, PROC20<br><b>Environmental Release Categories:</b> ERC9a, ERC9b, ESVOC SpERC 9.6b.v1            |
| Scope of process | Covers the use of formulated lubricants in closed and open systems including transfer operations, operation of engines and similar articles, reworking on reject articles, equipment maintenance and disposal of waste oil. |

| SECTION 2  | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES                      |
|--|--|
| Section 2.1  | Control of Worker Exposure   |
| <b>Product Characteristics</b>   |  |
| Physical form of product   | Liquid, vapour pressure < 0.5 kPa with potential for aerosol generation. |
| Concentration of the Substance in Mixture/Article  | Covers use of substance/product up to 100% (unless stated differently)., |
| <b>Frequency and Duration of Use</b>   |  |
| Covers daily exposures up to 8 hours (unless stated differently).  |  |
| <b>Other Operational Conditions affecting Exposure</b>   |  |
| Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented. |  |
| <b>Contributing Scenarios</b>  | <b>Risk Management Measures</b>  |
| General measures (Aspiration)  | Do not ingest. If swallowed, then seek immediate medical assistance      |
| General exposures (closed systems)   | No other specific measures identified.                                   |
| Operation of equipment containing engine oils and similar.(closed systems)   | No other specific measures identified.                                   |
| General exposures (open systems)   | No other specific measures identified.                                   |
| Bulk transfersDedicated facility   | No other specific measures identified.                                   |
| Filling/ preparation of equipment from drums or containers.Dedicated facility  | No other specific measures identified.                                   |
| Filling/ preparation of  | Avoid carrying out activities involving exposure for more than           |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version  
3.3

Revision Date:  
13.09.2024

SDS Number:  
800001015845

Date of last issue: 10.06.2024  
Print Date 14.09.2024

|  |   |
|--|---|
| equipment from drums or containers.Non-dedicated facility                                    | 1 hour.   |
| Operation and lubrication of high energy open equipmentIndoor                                | Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings.   |
| Operation and lubrication of high energy open equipmentOutdoor                               | Ensure operation is undertaken outdoors.<br>Avoid carrying out operation for more than 4 hours.<br>Limit the substance content in the product to 25 %.  |
| Maintenance (of larger plant items) and machine set upDedicated facilityelevated temperature | Drain down system prior to equipment opening or maintenance.<br>Provide extract ventilation to emission points when contact with warm (>50oC) product is likely.  |
| Maintenance of small itemsNon-dedicated facilityelevated temperature                         | Drain or remove substance from equipment prior to break-in or maintenance.<br>Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).   |
| Engine lubricant service   | No other specific measures identified.  |
| ManualRolling, Brushing  | No other specific measures identified.  |
| Spraying   | Carry out in a vented booth or extracted enclosure.<br>, or:<br>Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings.<br>Avoid carrying out activities involving exposure for more than 1 hour.<br>, or:<br>Wear a respirator conforming to EN140 with Type A filter or better. |
| Treatment by dipping and pouring   | No other specific measures identified.  |
| Storage.   | Store substance within a closed system.   |
| <b>Section 2.2</b>   | <b>Control of Environmental Exposure</b>  |
| Substance is complex UVCB.   |   |
| Predominantly hydrophobic.   |   |
| <b>Amounts Used</b>  |   |
| Fraction of EU tonnage used in region:   | 0.1   |
| Regional use tonnage (tonnes/year):  | 1.1E+05   |
| Fraction of Regional tonnage used locally:   | 1   |
| Annual site tonnage (tonnes/year):   | 5.3E+01   |
| Maximum daily site tonnage (kg/day):   | 365   |
| <b>Frequency and Duration of Use</b>   |   |
| Continuous release.  |   |
| Emission Days (days/year):   | 365   |
| <b>Environmental factors not influenced by risk management</b>                               |   |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version 3.3      Revision Date: 13.09.2024      SDS Number: 800001015845      Date of last issue: 10.06.2024  
Print Date 14.09.2024

|  |         |
|--|---------|
| Local freshwater dilution factor:  | 10      |
| Local marine water dilution factor:  | 100     |
| <b>Other Operational Conditions affecting Environmental Exposure</b>   |         |
| Release fraction to air from wide dispersive use (regional only):  | 0.01    |
| Release fraction to wastewater from wide dispersive use:   | 0.01    |
| Release fraction to soil from wide dispersive use (regional only):   | 0.01    |
| <b>Technical conditions and measures at process level (source) to prevent release</b>                                |         |
| Common practices vary across sites thus conservative process re-lease estimates used.                                |         |
| <b>Technical onsite conditions and measures to reduce or limit discharges, air emis-sions and releases to soil</b>   |         |
| Risk from environmental exposure is driven by freshwater sediment.   |         |
| Treat air emission to provide a typical removal efficiency of (%)  | 0       |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)    | 76.1    |
| If discharging to domestic sewage treatment plant, provide the re-quired onsite wastewater removal efficiency of (%) | 0.0     |
| <b>Organisational measures to prevent/limit release from site</b>  |         |
| Do not apply industrial sludge to natural soils.<br>Sludge should be incinerated, contained or reclaimed.            |         |
| <b>Conditions and Measures related to municipal sewage treatment plant</b>   |         |
| Estimated substance removal from wastewater via domestic sewage treatment (%)  | 94.7    |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)             | 94.7    |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)          | 6.5E+02 |
| Assumed domestic sewage treatment plant flow (m3/d)  | 2,000   |
| <b>Conditions and Measures related to external treatment of waste for disposal</b>                                   |         |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations.            |         |
| <b>Conditions and measures related to external recovery of waste</b>   |         |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations.            |         |

|  |                            |
|--|----------------------------|
| <b>SECTION 3</b>   | <b>EXPOSURE ESTIMATION</b> |
| <b>Section 3.1 - Health</b>  |                            |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.            |                            |
| Risk Management Measures are based on qualitative risk characterisation.                                 |                            |
| <b>Section 3.2 -Environment</b>  |                            |
| The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model. |                            |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version  
3.3

Revision Date:  
13.09.2024

SDS Number:  
800001015845

Date of last issue: 10.06.2024  
Print Date 14.09.2024

| SECTION 4   | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
|---|---|
| <b>Section 4.1 - Health</b>   |   |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.<br>Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. |   |
| <b>Section 4.2 -Environment</b>   |   |
| Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.  |   |
| Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.   |   |
| Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.   |   |
| Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org/en/reach-for-industries-libraries.html">http://cefic.org/en/reach-for-industries-libraries.html</a> ).  |   |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version  
3.3

Revision Date:  
13.09.2024

SDS Number:  
800001015845

Date of last issue: 10.06.2024  
Print Date 14.09.2024

### Exposure Scenario - Worker

**300000010390**

| SECTION 1        | EXPOSURE SCENARIO TITLE   |
|------------------|---|
| Title            | Lubricants- ProfessionalHigh Environmental Release  |
| Use Descriptor   | <b>Sector of Use:</b> SU22<br><b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC13, PROC17, PROC20<br><b>Environmental Release Categories:</b> ERC8a, ERC8d, ESVOC SpERC 8.6c.v1            |
| Scope of process | Covers the use of formulated lubricants in closed and open systems including transfer operations, operation of engines and similar articles, reworking on reject articles, equipment maintenance and disposal of waste oil. |

| SECTION 2  | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES                      |
|--|--|
| Section 2.1  | Control of Worker Exposure   |
| <b>Product Characteristics</b>   |  |
| Physical form of product   | Liquid, vapour pressure < 0.5 kPa with potential for aerosol generation. |
| Concentration of the Substance in Mixture/Article  | Covers use of substance/product up to 100% (unless stated differently)., |
| <b>Frequency and Duration of Use</b>   |  |
| Covers daily exposures up to 8 hours (unless stated differently).  |  |
| <b>Other Operational Conditions affecting Exposure</b>   |  |
| Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented. |  |
| <b>Contributing Scenarios</b>  | <b>Risk Management Measures</b>  |
| General measures (Aspiration)  | Do not ingest. If swallowed, then seek immediate medical assistance      |
| General exposures (closed systems)   | No other specific measures identified.                                   |
| Operation of equipment containing engine oils and similar.(closed systems)   | No other specific measures identified.                                   |
| General exposures (open systems)   | No other specific measures identified.                                   |
| Bulk transfersDedicated facility   | No other specific measures identified.                                   |
| Filling/ preparation of equipment from drums or containers.Dedicated facility  | No other specific measures identified.                                   |
| Filling/ preparation of  | Avoid carrying out activities involving exposure for more than           |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version 3.3      Revision Date: 13.09.2024      SDS Number: 800001015845      Date of last issue: 10.06.2024  
Print Date 14.09.2024

|  |   |
|--|---|
| equipment from drums or containers.Non-dedicated facility                                    | 1 hour.   |
| Operation and lubrication of high energy open equipmentIndoor                                | Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings.   |
| Operation and lubrication of high energy open equipmentOutdoor                               | Ensure operation is undertaken outdoors.<br>Avoid carrying out operation for more than 4 hours.<br>Limit the substance content in the product to 25 %.  |
| Maintenance (of larger plant items) and machine set upDedicated facilityelevated temperature | Drain down system prior to equipment opening or maintenance.<br>Provide extract ventilation to emission points when contact with warm (>50oC) product is likely.  |
| Maintenance of small itemsNon-dedicated facilityelevated temperature                         | Drain or remove substance from equipment prior to break-in or maintenance.<br>Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).   |
| Engine lubricant service   | No other specific measures identified.  |
| ManualRolling, Brushing  | No other specific measures identified.  |
| Spraying   | Carry out in a vented booth or extracted enclosure.<br>, or:<br>Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings.<br>Avoid carrying out activities involving exposure for more than 1 hour.<br>, or:<br>Wear a respirator conforming to EN140 with Type A filter or better. |
| Treatment by dipping and pouring   | No other specific measures identified.  |
| Storage.   | Store substance within a closed system.   |
| <b>Section 2.2</b>   | <b>Control of Environmental Exposure</b>  |
| Substance is complex UVCB.   |   |
| Predominantly hydrophobic.   |   |
| <b>Amounts Used</b>  |   |
| Fraction of EU tonnage used in region:   | 0.1   |
| Regional use tonnage (tonnes/year):  | 8.1E+04   |
| Fraction of Regional tonnage used locally:   | 1   |
| Annual site tonnage (tonnes/year):   | 4.0E+01   |
| Maximum daily site tonnage (kg/day):   | 1.1E+02   |
| <b>Frequency and Duration of Use</b>   |   |
| Continuous release.  |   |
| Emission Days (days/year):   | 365   |
| <b>Environmental factors not influenced by risk management</b>                               |   |



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version 3.3      Revision Date: 13.09.2024      SDS Number: 800001015845      Date of last issue: 10.06.2024  
Print Date 14.09.2024

|   |         |
|---|---------|
| Local freshwater dilution factor:   | 10      |
| Local marine water dilution factor:   | 100     |
| <b>Other Operational Conditions affecting Environmental Exposure</b>  |         |
| Release fraction to air from wide dispersive use (regional only):   | 5.0E-03 |
| Release fraction to wastewater from wide dispersive use:  | 0.05    |
| Release fraction to soil from wide dispersive use (regional only):  | 0.05    |
| <b>Technical conditions and measures at process level (source) to prevent release</b>                               |         |
| Common practices vary across sites thus conservative process release estimates used.                                |         |
| <b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>   |         |
| Risk from environmental exposure is driven by freshwater sediment.  |         |
| Treat air emission to provide a typical removal efficiency of (%)   | 0       |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)   | 87.6    |
| If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%) | 0.0     |
| <b>Organisational measures to prevent/limit release from site</b>   |         |
| Do not apply industrial sludge to natural soils.<br>Sludge should be incinerated, contained or reclaimed.           |         |
| <b>Conditions and Measures related to municipal sewage treatment plant</b>  |         |
| Estimated substance removal from wastewater via domestic sewage treatment (%)                                       | 94.7    |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)            | 94.7    |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)         | 2.6E+02 |
| Assumed domestic sewage treatment plant flow (m3/d)   | 2,000   |
| <b>Conditions and Measures related to external treatment of waste for disposal</b>                                  |         |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations.           |         |
| <b>Conditions and measures related to external recovery of waste</b>  |         |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations.           |         |

|  |                            |
|--|----------------------------|
| <b>SECTION 3</b>   | <b>EXPOSURE ESTIMATION</b> |
| <b>Section 3.1 - Health</b>  |                            |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.            |                            |
| Risk Management Measures are based on qualitative risk characterisation.                                 |                            |
| <b>Section 3.2 -Environment</b>  |                            |
| The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model. |                            |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version  
3.3

Revision Date:  
13.09.2024

SDS Number:  
800001015845

Date of last issue: 10.06.2024  
Print Date 14.09.2024

| SECTION 4   | GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO |
|---|---|
| <b>Section 4.1 - Health</b>   |   |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.<br>Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. |   |
| <b>Section 4.2 -Environment</b>   |   |
| Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.  |   |
| Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.   |   |
| Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.   |   |
| Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org/en/reach-for-industries-libraries.html">http://cefic.org/en/reach-for-industries-libraries.html</a> ).  |   |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version 3.3      Revision Date: 13.09.2024      SDS Number: 800001015845      Date of last issue: 10.06.2024  
Print Date 14.09.2024

### Exposure Scenario - Worker

|                         |  |
|-------------------------|--|
| <b>300000010393</b>     |  |
| <b>SECTION 1</b>        | <b>EXPOSURE SCENARIO TITLE</b>   |
| <b>Title</b>            | Use in laboratories- Industrial  |
| <b>Use Descriptor</b>   | <b>Sector of Use:</b> SU3<br><b>Process Categories:</b> PROC10, PROC15<br><b>Environmental Release Categories:</b> ERC4, |
| <b>Scope of process</b> | Use of the substance within laboratory settings, including material transfers and equipment cleaning.                    |

|  |  |         |
|--|--|---------|
| SECTION 2  | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES                      |         |
| Section 2.1  | Control of Worker Exposure   |         |
| Product Characteristics  |  |         |
| Physical form of product   | Liquid, vapour pressure < 0.5 kPa with potential for aerosol generation. |         |
| Concentration of the Substance in Mixture/Article  | Covers use of substance/product up to 100% (unless stated differently)., |         |
| Frequency and Duration of Use  |  |         |
| Covers daily exposures up to 8 hours (unless stated differently).  |  |         |
| Other Operational Conditions affecting Exposure  |  |         |
| Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented. |  |         |
| Contributing Scenarios   | Risk Management Measures   |         |
| General measures (Aspiration)  | Do not ingest. If swallowed, then seek immediate medical assistance      |         |
| Laboratory activities  | No other specific measures identified.                                   |         |
| Section 2.2  | Control of Environmental Exposure  |         |
| Substance is complex UVCB.   |  |         |
| Predominantly hydrophobic.   |  |         |
| Amounts Used   |  |         |
| Fraction of EU tonnage used in region:   |  | 0.1     |
| Regional use tonnage (tonnes/year):  |  | 1.2E+03 |
| Fraction of Regional tonnage used locally:   |  | 1       |
| Annual site tonnage (tonnes/year):   |  | 2.0E+00 |
| Maximum daily site tonnage (kg/day):   |  | 1.0E+02 |
| Frequency and Duration of Use  |  |         |
| Continuous release.  |  |         |
| Emission Days (days/year):   |  | 20      |
| Environmental factors not influenced by risk management  |  |         |
| Local freshwater dilution factor:  |  | 10      |
| Local marine water dilution factor:  |  | 100     |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version 3.3      Revision Date: 13.09.2024      SDS Number: 800001015845      Date of last issue: 10.06.2024  
Print Date 14.09.2024

|   |         |
|---|---------|
| <b>Other Operational Conditions affecting Environmental Exposure</b>  |         |
| Release fraction to air from process (initial release prior to RMM):  | 0.025   |
| Release fraction to wastewater from process (initial release prior to RMM):   | 0.02    |
| Release fraction to soil from process (initial release prior to RMM):   | 0.0001  |
| <b>Technical conditions and measures at process level (source) to prevent release</b>                               |         |
| Common practices vary across sites thus conservative process re-release estimates used.                             |         |
| <b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>   |         |
| Risk from environmental exposure is driven by freshwater sediment.  |         |
| Treat air emission to provide a typical removal efficiency of (%)   | 0       |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)   | 78.7    |
| If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%) | 0.0     |
| <b>Organisational measures to prevent/limit release from site</b>   |         |
| Do not apply industrial sludge to natural soils.<br>Sludge should be incinerated, contained or reclaimed.           |         |
| <b>Conditions and Measures related to municipal sewage treatment plant</b>  |         |
| Estimated substance removal from wastewater via domestic sewage treatment (%)                                       | 94.7    |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)            | 94.7    |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)         | 4.0E+02 |
| Assumed domestic sewage treatment plant flow (m3/d)   | 2,000   |
| <b>Conditions and Measures related to external treatment of waste for disposal</b>                                  |         |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations.           |         |
| <b>Conditions and measures related to external recovery of waste</b>  |         |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations.           |         |

|   |                            |
|---|----------------------------|
| <b>SECTION 3</b>  | <b>EXPOSURE ESTIMATION</b> |
| <b>Section 3.1 - Health</b>   |                            |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated. |                            |
| Risk Management Measures are based on qualitative risk characterisation.                      |                            |

|  |  |
|--|--|
| <b>Section 3.2 -Environment</b>  |  |
| The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model. |  |

|                  |  |
|------------------|--|
| <b>SECTION 4</b> | <b>GUIDANCE TO CHECK COMPLIANCE WITH THE</b> |
|------------------|--|

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

|         |                |              |                                |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 10.06.2024 |
| 3.3     | 13.09.2024     | 800001015845 | Print Date 14.09.2024          |

| EXPOSURE SCENARIO   |
|---|
| <b>Section 4.1 - Health</b>   |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.<br>Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. |
| <b>Section 4.2 -Environment</b>   |
| Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.  |
| Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.   |
| Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.   |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version  
3.3

Revision Date:  
13.09.2024

SDS Number:  
800001015845

Date of last issue: 10.06.2024  
Print Date 14.09.2024

### Exposure Scenario - Worker

**300000010400**

| SECTION 1        | EXPOSURE SCENARIO TITLE   |
|------------------|---|
| Title            | Functional Fluids- Industrial   |
| Use Descriptor   | <b>Sector of Use:</b> SU3<br><b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9<br><b>Environmental Release Categories:</b> ERC7, ESVOC SpERC 7.13a.v1            |
| Scope of process | Use as functional fluids e.g. cable oils, transfer oils, coolants, insulators, refrigerants, hydraulic fluids in industrial equipment including maintenance and related material transfers. |

| SECTION 2  | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES   |
|--|---|
| Section 2.1  | Control of Worker Exposure  |
| <b>Product Characteristics</b>   |   |
| Physical form of product   | Liquid, vapour pressure < 0.5 kPa with potential for aerosol generation.  |
| Concentration of the Substance in Mixture/Article  | Covers use of substance/product up to 100% (unless stated differently).,  |
| <b>Frequency and Duration of Use</b>   |   |
| Covers daily exposures up to 8 hours (unless stated differently).  |   |
| <b>Other Operational Conditions affecting Exposure</b>   |   |
| Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented. |   |
| <b>Contributing Scenarios</b>  | <b>Risk Management Measures</b>   |
| General measures (Aspiration)  | Do not ingest. If swallowed, then seek immediate medical assistance   |
| Bulk transfers(closed systems)   | No other specific measures identified.  |
| Drum/batch transfersDedicated facility   | No other specific measures identified.  |
| Filling of articles/equipment(closed systems)  | No other specific measures identified.  |
| Filling/ preparation of equipment from drums or containers.Non-dedicated facility  | No other specific measures identified.  |
| General exposures (closed systems)   | No other specific measures identified.  |
| General exposures (open systems)elevated tempera-  | Restrict area of openings and provide extract ventilation to emission points when substance handled at elevated temper- |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version 3.3      Revision Date: 13.09.2024      SDS Number: 800001015845      Date of last issue: 10.06.2024  
Print Date 14.09.2024

|   |  |
|---|--|
| ture  | atures   |
| Remanufacture of reject articles  | No other specific measures identified.                       |
| Equipment cleaning and maintenance  | Drain down system prior to equipment opening or maintenance. |
| Storage.  | Store substance within a closed system.                      |
| <b>Section 2.2</b>  | <b>Control of Environmental Exposure</b>                     |
| Substance is complex UVCB.  |  |
| Predominantly hydrophobic.  |  |
| <b>Amounts Used</b>   |  |
| Fraction of EU tonnage used in region:  | 0.1  |
| Regional use tonnage (tonnes/year):   | 1.2E+03  |
| Fraction of Regional tonnage used locally:  | 1  |
| Annual site tonnage (tonnes/year):  | 1.0E+01  |
| Maximum daily site tonnage (kg/day):  | 5.0E+02  |
| <b>Frequency and Duration of Use</b>  |  |
| Continuous release.   |  |
| Emission Days (days/year):  | 20   |
| <b>Environmental factors not influenced by risk management</b>  |  |
| Local freshwater dilution factor:   | 10   |
| Local marine water dilution factor:   | 100  |
| <b>Other Operational Conditions affecting Environmental Exposure</b>  |  |
| Release fraction to air from process (initial release prior to RMM):  | 5.0E-04  |
| Release fraction to wastewater from process (initial release prior to RMM):   | 1.0E-06  |
| Release fraction to soil from process (initial release prior to RMM):   | 0.001  |
| <b>Technical conditions and measures at process level (source) to prevent release</b>                               |  |
| Common practices vary across sites thus conservative process release estimates used.                                |  |
| <b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>   |  |
| Risk from environmental exposure is driven by freshwater sediment.  |  |
| Treat air emission to provide a typical removal efficiency of (%)   | 0  |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)   | 64.4   |
| If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%) | 0.0  |
| <b>Organisational measures to prevent/limit release from site</b>   |  |
| Do not apply industrial sludge to natural soils.<br>Sludge should be incinerated, contained or reclaimed.           |  |
| <b>Conditions and Measures related to municipal sewage treatment plant</b>  |  |
| Estimated substance removal from wastewater via domestic sewage treatment (%)                                       | 94.7   |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)            | 98.9   |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)         | 3.3E+03  |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version 3.3      Revision Date: 13.09.2024      SDS Number: 800001015845      Date of last issue: 10.06.2024  
Print Date 14.09.2024

|   |       |
|---|-------|
| Assumed domestic sewage treatment plant flow (m3/d)   | 2,000 |
| <b>Conditions and Measures related to external treatment of waste for disposal</b>                        |       |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations. |       |
| <b>Conditions and measures related to external recovery of waste</b>                                      |       |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations. |       |

|   |                            |
|---|----------------------------|
| <b>SECTION 3</b>  | <b>EXPOSURE ESTIMATION</b> |
| <b>Section 3.1 - Health</b>   |                            |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated. |                            |
| Risk Management Measures are based on qualitative risk characterisation.                      |                            |

|  |  |
|--|--|
| <b>Section 3.2 -Environment</b>  |  |
| The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model. |  |

|   |  |
|---|--|
| <b>SECTION 4</b>  | <b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b> |
| <b>Section 4.1 - Health</b>   |  |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.<br>Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. |  |

|  |  |
|--|--|
| <b>Section 4.2 -Environment</b>  |  |
| Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.                               |  |
| Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.  |  |
| Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.  |  |
| Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org/en/reach-for-industries-libraries.html">http://cefic.org/en/reach-for-industries-libraries.html</a> ). |  |



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version 3.3      Revision Date: 13.09.2024      SDS Number: 800001015845      Date of last issue: 10.06.2024  
Print Date 14.09.2024

### Exposure Scenario - Worker

**300000010397**

| SECTION 1        | EXPOSURE SCENARIO TITLE   |
|------------------|---|
| Title            | Functional Fluids- Professional   |
| Use Descriptor   | <b>Sector of Use:</b> SU22<br><b>Process Categories:</b> PROC1, PROC2, PROC3, PROC8a, PROC9, PROC20<br><b>Environmental Release Categories:</b> ERC9a, ERC9b, ESVOC SpERC 9.13b.v1            |
| Scope of process | Use as functional fluids e.g. cable oils, transfer oils, coolants, insulators, refrigerants, hydraulic fluids in professional equipment including maintenance and related material transfers. |

| SECTION 2  | OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES   |
|--|---|
| Section 2.1  | Control of Worker Exposure  |
| Product Characteristics  |   |
| Physical form of product   | Liquid, vapour pressure < 0.5 kPa with potential for aerosol generation.  |
| Concentration of the Substance in Mixture/Article  | Covers use of substance/product up to 100% (unless stated differently).,  |
| Frequency and Duration of Use  |   |
| Covers daily exposures up to 8 hours (unless stated differently).  |   |
| Other Operational Conditions affecting Exposure  |   |
| Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented. |   |
| Contributing Scenarios   | Risk Management Measures  |
| General measures (Aspiration)  | Do not ingest. If swallowed, then seek immediate medical assistance   |
| Bulk transfers(closed systems)   | No other specific measures identified.  |
| Drum/batch transfersDedicated facility   | No other specific measures identified.  |
| Filling of articles/equipment(closed systems)  | No other specific measures identified.  |
| Filling/ preparation of equipment from drums or containers.Non-dedicated facility  | No other specific measures identified.  |
| General exposures (closed systems)   | No other specific measures identified.  |
| General exposures (open systems)elevated tempera-  | Restrict area of openings and provide extract ventilation to emission points when substance handled at elevated temper- |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version 3.3      Revision Date: 13.09.2024      SDS Number: 800001015845      Date of last issue: 10.06.2024  
Print Date 14.09.2024

|   |  |
|---|--|
| ture  | atures   |
| Remanufacture of reject articles  | No other specific measures identified.                       |
| Equipment cleaning and maintenance  | Drain down system prior to equipment opening or maintenance. |
| Storage.  | Store substance within a closed system.                      |
| <b>Section 2.2</b>  | <b>Control of Environmental Exposure</b>                     |
| Substance is complex UVCB.  |  |
| Predominantly hydrophobic.  |  |
| <b>Amounts Used</b>   |  |
| Fraction of EU tonnage used in region:  | 0.1  |
| Regional use tonnage (tonnes/year):   | 1.2E+03  |
| Fraction of Regional tonnage used locally:  | 1  |
| Annual site tonnage (tonnes/year):  | 6.0E-01  |
| Maximum daily site tonnage (kg/day):  | 1.6E+00  |
| <b>Frequency and Duration of Use</b>  |  |
| Continuous release.   |  |
| Emission Days (days/year):  | 365  |
| <b>Environmental factors not influenced by risk management</b>  |  |
| Local freshwater dilution factor:   | 10   |
| Local marine water dilution factor:   | 100  |
| <b>Other Operational Conditions affecting Environmental Exposure</b>  |  |
| Release fraction to air from process (initial release prior to RMM):  | 0.05   |
| Release fraction to wastewater from process (initial release prior to RMM):   | 0.025  |
| Release fraction to soil from process (initial release prior to RMM):   | 0.025  |
| <b>Technical conditions and measures at process level (source) to prevent release</b>                               |  |
| Common practices vary across sites thus conservative process release estimates used.                                |  |
| <b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>   |  |
| Risk from environmental exposure is driven by freshwater sediment.  |  |
| Treat air emission to provide a typical removal efficiency of (%)   | 0  |
| Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)   | 64.9   |
| If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%) | 0.0  |
| <b>Organisational measures to prevent/limit release from site</b>   |  |
| Do not apply industrial sludge to natural soils.<br>Sludge should be incinerated, contained or reclaimed.           |  |
| <b>Conditions and Measures related to municipal sewage treatment plant</b>  |  |
| Estimated substance removal from wastewater via domestic sewage treatment (%)                                       | 94.7   |
| Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)            | 94.7   |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)         | 1.1E+01  |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version 3.3      Revision Date: 13.09.2024      SDS Number: 800001015845      Date of last issue: 10.06.2024  
Print Date 14.09.2024

|   |       |
|---|-------|
| Assumed domestic sewage treatment plant flow (m3/d)   | 2,000 |
| <b>Conditions and Measures related to external treatment of waste for disposal</b>                        |       |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations. |       |
| <b>Conditions and measures related to external recovery of waste</b>                                      |       |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations. |       |

|   |                            |
|---|----------------------------|
| <b>SECTION 3</b>  | <b>EXPOSURE ESTIMATION</b> |
| <b>Section 3.1 - Health</b>   |                            |
| The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated. |                            |
| Risk Management Measures are based on qualitative risk characterisation.                      |                            |

|  |  |
|--|--|
| <b>Section 3.2 -Environment</b>  |  |
| The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model. |  |

|   |  |
|---|--|
| <b>SECTION 4</b>  | <b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b> |
| <b>Section 4.1 - Health</b>   |  |
| Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.<br>Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. |  |

|  |  |
|--|--|
| <b>Section 4.2 -Environment</b>  |  |
| Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.                               |  |
| Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.  |  |
| Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.  |  |
| Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org/en/reach-for-industries-libraries.html">http://cefic.org/en/reach-for-industries-libraries.html</a> ). |  |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version 3.3      Revision Date: 13.09.2024      SDS Number: 800001015845      Date of last issue: 10.06.2024  
Print Date 14.09.2024

### Exposure Scenario - Consumer

|                         |  |
|-------------------------|--|
| <b>300000010380</b>     |  |
| <b>SECTION 1</b>        | <b>EXPOSURE SCENARIO TITLE</b>   |
| <b>Title</b>            | Use in agrochemicals - Consumer  |
| <b>Use Descriptor</b>   | <b>Sector of Use:</b> SU21<br><b>Product Categories:</b> PC12, PC27<br><b>Environmental Release Categories:</b> ERC8a, ERC8d, ESVOC SpERC 8.11b.v1 |
| <b>Scope of process</b> | Covers the consumer use in agrochemicals in liquid and solid forms.  |

|                                |   |
|--------------------------------|---|
| <b>SECTION 2</b>               | <b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>          |
| <b>Section 2.1</b>             | <b>Control of Consumer Exposure</b>                                 |
| <b>Product Characteristics</b> |   |
| <b>Product Categories</b>      | <b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>          |
| General measures (Aspiration)  | Do not ingest. If swallowed, then seek immediate medical assistance |

| Section 2.2   | Control of Environmental Exposure |         |
|---|-----------------------------------|---------|
| Substance is complex UVCB.  |                                   |         |
| Predominantly hydrophobic.  |                                   |         |
| Amounts Used  |                                   |         |
| Fraction of EU tonnage used in region:  |                                   | 0.1     |
| Regional use tonnage (tonnes/year):   |                                   | 2.0E+03 |
| Fraction of Regional tonnage used locally:  |                                   | 0.0005  |
| Annual site tonnage (tonnes/year):  |                                   | 4.1E+00 |
| Maximum daily site tonnage (kg/day):  |                                   | 1.1E+01 |
| Frequency and Duration of Use   |                                   |         |
| Continuous release.   |                                   |         |
| Emission Days (days/year):  |                                   | 365     |
| Environmental factors not influenced by risk management   |                                   |         |
| Local freshwater dilution factor:   |                                   | 10      |
| Local marine water dilution factor:   |                                   | 100     |
| Other Operational Conditions affecting Environmental Exposure   |                                   |         |
| Release fraction to air from wide dispersive use (regional only):   |                                   | 0.9     |
| Release fraction to wastewater from wide dispersive use:  |                                   | 0.01    |
| Release fraction to soil from wide dispersive use (regional only):  |                                   | 0.09    |
| Conditions and Measures related to municipal sewage treatment plant   |                                   |         |
| Estimated substance removal from wastewater via domestic sewage treatment (%)                               |                                   | 94.7    |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) |                                   | 7.2E+01 |
| Assumed domestic sewage treatment plant flow (m3/d)   |                                   | 2,000   |
| Conditions and Measures related to external treatment of waste for disposal                                 |                                   |         |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

|         |                |              |                                |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 10.06.2024 |
| 3.3     | 13.09.2024     | 800001015845 | Print Date 14.09.2024          |

External treatment and disposal of waste should comply with applicable local and/or regional regulations.

### Conditions and measures related to external recovery of waste

External recovery and recycling of waste should comply with applicable local and/or regional regulations.

## SECTION 3

### EXPOSURE ESTIMATION

#### Section 3.1 - Health

Risk Management Measures are based on qualitative risk characterisation.

#### Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

## SECTION 4

### GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

#### Section 4.1 - Health

Not applicable.

#### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version  
3.3

Revision Date:  
13.09.2024

SDS Number:  
800001015845

Date of last issue: 10.06.2024  
Print Date 14.09.2024

### Exposure Scenario - Consumer

|                         |  |
|-------------------------|--|
| <b>300000010387</b>     |  |
| <b>SECTION 1</b>        | <b>EXPOSURE SCENARIO TITLE</b>   |
| <b>Title</b>            | Use as a fuel - Consumer   |
| <b>Use Descriptor</b>   | <b>Sector of Use:</b> SU21<br><b>Product Categories:</b> PC13<br><b>Environmental Release Categories:</b> ERC9a, ERC9b, ESVOC SpERC 9.12c.v1 |
| <b>Scope of process</b> | Covers consumer uses in liquid fuels.  |

|                                |   |
|--------------------------------|---|
| <b>SECTION 2</b>               | <b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>          |
| <b>Section 2.1</b>             | <b>Control of Consumer Exposure</b>                                 |
| <b>Product Characteristics</b> |   |
| <b>Product Categories</b>      | <b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>          |
| General measures (Aspiration)  | Do not ingest. If swallowed, then seek immediate medical assistance |

|   |  |         |
|---|--|---------|
| <b>Section 2.2</b>  | <b>Control of Environmental Exposure</b> |         |
| Substance is complex UVCB.  |  |         |
| Predominantly hydrophobic.  |  |         |
| <b>Amounts Used</b>   |  |         |
| Fraction of EU tonnage used in region:  |  | 0.1     |
| Regional use tonnage (tonnes/year):   |  | 1.0E+04 |
| Fraction of Regional tonnage used locally:  |  | 0.0005  |
| Annual site tonnage (tonnes/year):  |  | 5.0E+00 |
| Maximum daily site tonnage (kg/day):  |  | 1.4E+01 |
| <b>Frequency and Duration of Use</b>  |  |         |
| Continuous release.   |  |         |
| Emission Days (days/year):  |  | 365     |
| <b>Environmental factors not influenced by risk management</b>  |  |         |
| Local freshwater dilution factor:   |  | 10      |
| Local marine water dilution factor:   |  | 100     |
| <b>Other Operational Conditions affecting Environmental Exposure</b>  |  |         |
| Release fraction to air from wide dispersive use (regional only):   |  | 1.0E-04 |
| Release fraction to wastewater from wide dispersive use:  |  | 1.0E-05 |
| Release fraction to soil from wide dispersive use (regional only):  |  | 1.0E-05 |
| <b>Conditions and Measures related to municipal sewage treatment plant</b>                                  |  |         |
| Estimated substance removal from wastewater via domestic sewage treatment (%)                               |  | 94.7    |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) |  | 9.1E+01 |
| Assumed domestic sewage treatment plant flow (m3/d)   |  | 2,000   |
| <b>Conditions and Measures related to external treatment of waste for disposal</b>                          |  |         |
| Combustion emissions limited by required exhaust emission controls.   |  |         |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

|         |                |              |                                |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 10.06.2024 |
| 3.3     | 13.09.2024     | 800001015845 | Print Date 14.09.2024          |

Waste combustion emissions considered in regional exposure assessment.  
External treatment and disposal of waste should comply with applicable local and/or regional regulations.

### Conditions and measures related to external recovery of waste

This substance is consumed during use and no waste of substance is generated.

## SECTION 3

### EXPOSURE ESTIMATION

#### Section 3.1 - Health

Risk Management Measures are based on qualitative risk characterisation.

#### Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

## SECTION 4

### GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

#### Section 4.1 - Health

Not applicable.

#### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version  
3.3

Revision Date:  
13.09.2024

SDS Number:  
800001015845

Date of last issue: 10.06.2024  
Print Date 14.09.2024

### Exposure Scenario - Consumer

|                         |   |
|-------------------------|---|
| <b>300000010391</b>     |   |
| <b>SECTION 1</b>        | <b>EXPOSURE SCENARIO TITLE</b>  |
| <b>Title</b>            | Use in lubricants - Consumer Low Environmental Release  |
| <b>Use Descriptor</b>   | <b>Sector of Use:</b> SU21<br><b>Product Categories:</b> PC1, PC24, PC31<br><b>Environmental Release Categories:</b> ERC9a, ERC9b, ESVOC SpERC 9.6d.v1  |
| <b>Scope of process</b> | Covers the consumer use of formulated lubricants in closed and open systems including transfer operations, application, operation of engines and similar articles, equipment maintenance and disposal of waste oil. |

|                                |   |
|--------------------------------|---|
| <b>SECTION 2</b>               | <b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>          |
| <b>Section 2.1</b>             | <b>Control of Consumer Exposure</b>                                 |
| <b>Product Characteristics</b> |   |
| <b>Product Categories</b>      | <b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>          |
| General measures (Aspiration)  | Do not ingest. If swallowed, then seek immediate medical assistance |

| Section 2.2   | Control of Environmental Exposure |         |
|---|-----------------------------------|---------|
| Substance is complex UVCB.  |                                   |         |
| Predominantly hydrophobic.  |                                   |         |
| Amounts Used  |                                   |         |
| Fraction of EU tonnage used in region:  |                                   | 0.1     |
| Regional use tonnage (tonnes/year):   |                                   | 1.1E+05 |
| Fraction of Regional tonnage used locally:  |                                   | 0.0005  |
| Annual site tonnage (tonnes/year):  |                                   | 5.7E+01 |
| Maximum daily site tonnage (kg/day):  |                                   | 1.6E+02 |
| Frequency and Duration of Use   |                                   |         |
| Continuous release.   |                                   |         |
| Emission Days (days/year):  |                                   | 365     |
| Environmental factors not influenced by risk management   |                                   |         |
| Local freshwater dilution factor:   |                                   | 10      |
| Local marine water dilution factor:   |                                   | 100     |
| Other Operational Conditions affecting Environmental Exposure   |                                   |         |
| Release fraction to air from wide dispersive use (regional only):   |                                   | 0.01    |
| Release fraction to wastewater from wide dispersive use:  |                                   | 0.01    |
| Release fraction to soil from wide dispersive use (regional only):  |                                   | 0.01    |
| Conditions and Measures related to municipal sewage treatment plant   |                                   |         |
| Estimated substance removal from wastewater via domestic sewage treatment (%)                               |                                   | 94.7    |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) |                                   | 6.9E+02 |



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version 3.3      Revision Date: 13.09.2024      SDS Number: 800001015845      Date of last issue: 10.06.2024  
Print Date 14.09.2024

|   |       |
|---|-------|
| Assumed domestic sewage treatment plant flow (m3/d)   | 2,000 |
| <b>Conditions and Measures related to external treatment of waste for disposal</b>                        |       |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations. |       |
| <b>Conditions and measures related to external recovery of waste</b>                                      |       |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations. |       |

|  |                            |
|--|----------------------------|
| <b>SECTION 3</b>   | <b>EXPOSURE ESTIMATION</b> |
| <b>Section 3.1 - Health</b>  |                            |
| Risk Management Measures are based on qualitative risk characterisation. |                            |

|  |  |
|--|--|
| <b>Section 3.2 -Environment</b>  |  |
| The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model. |  |

|                             |  |
|-----------------------------|--|
| <b>SECTION 4</b>            | <b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b> |
| <b>Section 4.1 - Health</b> |  |
| Not applicable.             |  |

|  |  |
|--|--|
| <b>Section 4.2 -Environment</b>  |  |
| Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. |  |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version  
3.3

Revision Date:  
13.09.2024

SDS Number:  
800001015845

Date of last issue: 10.06.2024  
Print Date 14.09.2024

### Exposure Scenario - Consumer

|                         |   |
|-------------------------|---|
| <b>300000010392</b>     |   |
| <b>SECTION 1</b>        | <b>EXPOSURE SCENARIO TITLE</b>  |
| <b>Title</b>            | Use in lubricants - Consumer High Environmental Release   |
| <b>Use Descriptor</b>   | <b>Sector of Use:</b> SU21<br><b>Product Categories:</b> PC1, PC24, PC31<br><b>Environmental Release Categories:</b> ERC8a, ERC8d, ESVOC SpERC 8.6e.v1  |
| <b>Scope of process</b> | Covers the consumer use of formulated lubricants in closed and open systems including transfer operations, application, operation of engines and similar articles, equipment maintenance and disposal of waste oil. |

|                                |   |
|--------------------------------|---|
| <b>SECTION 2</b>               | <b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>          |
| <b>Section 2.1</b>             | <b>Control of Consumer Exposure</b>                                 |
| <b>Product Characteristics</b> |   |
| <b>Product Categories</b>      | <b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>          |
| General measures (Aspiration)  | Do not ingest. If swallowed, then seek immediate medical assistance |

|   |  |
|---|--|
| <b>Section 2.2</b>  | <b>Control of Environmental Exposure</b> |
| Substance is complex UVCB.  |  |
| Predominantly hydrophobic.  |  |
| <b>Amounts Used</b>   |  |
| Fraction of EU tonnage used in region:  | 0.1                                      |
| Regional use tonnage (tonnes/year):   | 2.9E+04                                  |
| Fraction of Regional tonnage used locally:  | 0.0005                                   |
| Annual site tonnage (tonnes/year):  | 1.4E+01                                  |
| Maximum daily site tonnage (kg/day):  | 3.9E+01                                  |
| <b>Frequency and Duration of Use</b>  |  |
| Continuous release.   |  |
| Emission Days (days/year):  | 365                                      |
| <b>Environmental factors not influenced by risk management</b>  |  |
| Local freshwater dilution factor:   | 10                                       |
| Local marine water dilution factor:   | 100                                      |
| <b>Other Operational Conditions affecting Environmental Exposure</b>  |  |
| Release fraction to air from wide dispersive use (regional only):   | 5.0E-03                                  |
| Release fraction to wastewater from wide dispersive use:  | 0.05                                     |
| Release fraction to soil from wide dispersive use (regional only):  | 0.05                                     |
| <b>Conditions and Measures related to municipal sewage treatment plant</b>                                  |  |
| Estimated substance removal from wastewater via domestic sewage treatment (%)                               | 94.7                                     |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) | 1.6E+02                                  |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version 3.3      Revision Date: 13.09.2024      SDS Number: 800001015845      Date of last issue: 10.06.2024  
Print Date 14.09.2024

|   |       |
|---|-------|
| Assumed domestic sewage treatment plant flow (m3/d)   | 2,000 |
| <b>Conditions and Measures related to external treatment of waste for disposal</b>                        |       |
| External treatment and disposal of waste should comply with applicable local and/or regional regulations. |       |
| <b>Conditions and measures related to external recovery of waste</b>                                      |       |
| External recovery and recycling of waste should comply with applicable local and/or regional regulations. |       |

|  |                            |
|--|----------------------------|
| <b>SECTION 3</b>   | <b>EXPOSURE ESTIMATION</b> |
| <b>Section 3.1 - Health</b>  |                            |
| Risk Management Measures are based on qualitative risk characterisation. |                            |

|  |  |
|--|--|
| <b>Section 3.2 -Environment</b>  |  |
| The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model. |  |

|                             |  |
|-----------------------------|--|
| <b>SECTION 4</b>            | <b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b> |
| <b>Section 4.1 - Health</b> |  |
| Not applicable.             |  |

|  |  |
|--|--|
| <b>Section 4.2 -Environment</b>  |  |
| Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. |  |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

Version 3.3      Revision Date: 13.09.2024      SDS Number: 800001015845      Date of last issue: 10.06.2024  
Print Date 14.09.2024

### Exposure Scenario - Consumer

|                         |  |
|-------------------------|--|
| <b>300000010401</b>     |  |
| <b>SECTION 1</b>        | <b>EXPOSURE SCENARIO TITLE</b>   |
| <b>Title</b>            | Functional Fluids - Consumer   |
| <b>Use Descriptor</b>   | <b>Sector of Use:</b> SU21<br><b>Product Categories:</b> PC16, PC17<br><b>Environmental Release Categories:</b> ERC9a, ERC9b, ESVOC SpERC 9.13c.v1 |
| <b>Scope of process</b> | Use of sealed items containing functional fluids e.g. transfer oils, hydraulic fluids, refrigerants.   |

|                                |   |
|--------------------------------|---|
| <b>SECTION 2</b>               | <b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>          |
| <b>Section 2.1</b>             | <b>Control of Consumer Exposure</b>                                 |
| <b>Product Characteristics</b> |   |
| <b>Product Categories</b>      | <b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>          |
| General measures (Aspiration)  | Do not ingest. If swallowed, then seek immediate medical assistance |

| Section 2.2   | Control of Environmental Exposure |         |
|---|-----------------------------------|---------|
| Substance is complex UVCB.  |                                   |         |
| Predominantly hydrophobic.  |                                   |         |
| Amounts Used  |                                   |         |
| Fraction of EU tonnage used in region:  |                                   | 0.1     |
| Regional use tonnage (tonnes/year):   |                                   | 1.2E+03 |
| Fraction of Regional tonnage used locally:  |                                   | 0.0005  |
| Annual site tonnage (tonnes/year):  |                                   | 6.0E-01 |
| Maximum daily site tonnage (kg/day):  |                                   | 1.6E+00 |
| Frequency and Duration of Use   |                                   |         |
| Continuous release.   |                                   |         |
| Emission Days (days/year):  |                                   | 365     |
| Environmental factors not influenced by risk management   |                                   |         |
| Local freshwater dilution factor:   |                                   | 10      |
| Local marine water dilution factor:   |                                   | 100     |
| Other Operational Conditions affecting Environmental Exposure   |                                   |         |
| Release fraction to air from wide dispersive use (regional only):   |                                   | 0.05    |
| Release fraction to wastewater from wide dispersive use:  |                                   | 0.025   |
| Release fraction to soil from wide dispersive use (regional only):  |                                   | 0.025   |
| Conditions and Measures related to municipal sewage treatment plant   |                                   |         |
| Estimated substance removal from wastewater via domestic sewage treatment (%)                               |                                   | 94.7    |
| Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d) |                                   | 1.1E+01 |
| Assumed domestic sewage treatment plant flow (m3/d)   |                                   | 2,000   |
| Conditions and Measures related to external treatment of waste for disposal                                 |                                   |         |

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## Risella X 415

|         |                |              |                                |
|---------|----------------|--------------|--------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 10.06.2024 |
| 3.3     | 13.09.2024     | 800001015845 | Print Date 14.09.2024          |

External treatment and disposal of waste should comply with applicable local and/or regional regulations.

### Conditions and measures related to external recovery of waste

External recovery and recycling of waste should comply with applicable local and/or regional regulations.

## SECTION 3

### EXPOSURE ESTIMATION

#### Section 3.1 - Health

Risk Management Measures are based on qualitative risk characterisation.

#### Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

## SECTION 4

### GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

#### Section 4.1 - Health

Not applicable.

#### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.