Shell Argina S3 40 Local

Version 1.2	Revision Date 08.03.2021	Print Date 25.05.2023		
1. PRODUCT AND COMPANY IDENTIFICATION				
Product name	: Shell Argina S3 40 Local			
Product code	: 001G1530			
Manufacturer or supplier's o	letails			
Supplier	 Shell Singapore Pte. Ltd. (196000089G) The Metropolis Tower 1, 9 North Buona Vista Drive, #07-01 Singapore 138588 Singapore 			
Telephone	: (+65) 62632975			
Telefax	: (+65) 62632049			
Emergency telephone number	: +65 6263 2975			
Email Contact for Safety Data Sheet	: If you have any enquiries about the please email lubricantSDS@shell.c			
Recommended use of the chemical and restrictions on use				

Recommended use : Engine oil.

2. HAZARDS IDENTIFICATION

GHS Classification				
Based on available data this	Based on available data this substance / mixture does not meet the classification criteria.			
GHS label elements				
Hazard pictograms	: No Hazard Symbol required			
Signal word	: No signal word			
Hazard statements	 PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS criteria. 			
Precautionary statements	: Prevention: No precautionary phrases. Response: No precautionary phrases. Storage: No precautionary phrases.			

Shell Argina S3 40 Local

Version 1.2

Revision Date 08.03.2021

Print Date 25.05.2023

Disposal:

No precautionary phrases.

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.Used oil may contain harmful impurities.Not classified as flammable but will burn.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	:	Mixture
Chemical nature	:	Highly refined mineral oils and additives. The highly refined mineral oil contains <3% (w/w) DMSO- extract, according to IP346. Classification based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).
	:	* contains one or more of the following CAS-numbers: 64742- 53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69- 9, 68649-12-7, 151006-60-9, 163149-28-8.

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%
			w/w)
Interchangeable low viscosity base oil (<20,5 cSt @40°C) *	Not Assigned	Asp. Tox.1; H304	0 - 90

For explanation of abbreviations see section 16.

4. FIRST-AID MEASURES

If inhaled	: No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	 Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
In case of eye contact	 Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.
If swallowed	: In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.

Shell Argina S3 40 Local

Version 1.2	Revision Date 08.03.2021	Print Date 25.05.2023
Most important symptoms and effects, both acute and delayed	: Oil acne/folliculitis signs and sym of black pustules and spots on th Ingestion may result in nausea, v	e skin of exposed areas.
Protection of first-aiders	: When administering first aid, ens appropriate personal protective e incident, injury and surroundings.	quipment according to the
Notes to physician	: Treat symptomatically.	
5. FIRE-FIGHTING MEASURES		
Suitable extinguishing media	: Foam, water spray or fog. Dry ch dioxide, sand or earth may be us	
Unsuitable extinguishing media	: Do not use water in a jet.	
Specific hazards during firefighting	 Hazardous combustion products A complex mixture of airborne so gases (smoke). Carbon monoxide may be evolve occurs. Unidentified organic and inorganic 	lid and liquid particulates and d if incomplete combustion
Specific extinguishing methods	: Use extinguishing measures that circumstances and the surroundi	
Special protective equipment for firefighters	: Proper protective equipment inclu- gloves are to be worn; chemical u large contact with spilled product Breathing Apparatus must be wo a confined space. Select fire figh- relevant Standards (e.g. Europe	resistant suit is indicated if is expected. Self-Contained rn when approaching a fire in ter's clothing approved to

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Avoid contact with skin and eyes.
Environmental precautions	: Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
	Local authorities should be advised if significant spillages cannot be contained.

Shell Argina S3 40 Local

Version 1.2	Revision Date 08.03.2021	Print Date 25.05.2023
Methods and materials for containment and cleaning up	 Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or othe suitable material and dispose of properly. 	
Additional advice	: For guidance on selection of personal see Section 8 of this Safety Data 5 For guidance on disposal of spiller this Safety Data Sheet.	Sheet.

7. HANDLING AND STORAGE

General Precautions	:	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Advice on safe handling	:	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.
Avoidance of contact	:	Strong oxidising agents.
Product Transfer	:	Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation.
Storage		
Other data	:	Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers.
		Store at ambient temperature.
Packaging material	:	Suitable material: For containers or container linings, use mild steel or high density polyethylene. Unsuitable material: PVC.
Container Advice	:	Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Shell Argina S3 40 Local

Version 1.2	Revision Da	ate 08.03.2021	Print Da	te 25.05.2023
Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	PEL (long term) (Mist)	5 mg/m3	SG OEL
Oil mist, mineral	Not Assigned	PEL (short term) (Mist)	10 mg/m3	SG OEL
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1
Oil mist, mineral	Not Assigned	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures	 The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations. Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.
	General Information: Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with this product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective

Version 1.2	Revision Date 08.03.2021	Print Date 25.05.2023
	equipment, local exhaust ventilation	on.
	Drain down system prior to equipn	nent break-in or
	maintenance.	
	Retain drain downs in sealed stora subsequent recycle.	age pending disposal or
	Always observe good personal hyd washing hands after handling the drinking, and/or smoking. Routine protective equipment to remove co contaminated clothing and footwea Practice good housekeeping.	material and before eating, ly wash work clothing and ontaminants. Discard

Personal protective equipment

Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory protection :	No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point >65°C (149°F)].
Hand protection Remarks :	Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.
	For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough

Version 1.2	Revision Date 08.03.2021	Print Date 25.05.2023
	time maybe acceptable so long as and replacement regimes are follow a good predictor of glove resistance dependent on the exact composition Glove thickness should be typically depending on the glove make and	wed. Glove thickness is not e to a chemical as it is on of the glove material. greater than 0.35 mm
Eye protection	: If material is handled such that it con protective eyewear is recommende	
Skin and body protection	: Skin protection is not ordinarily req work clothes. It is good practice to wear chemica	
Thermal hazards	: Not applicable	

Environmental exposure controls

General advice :	Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Section 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.
------------------	---

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Colour	:	amber
Odour	:	Data not available
Odour Threshold	:	Data not available
рН	:	Not applicable
pour point	:	<= -9 °C / <= 16 °FMethod: ASTM D97
Melting / freezing point		Data not available
Initial boiling point and boiling range	:	> 280 °C / 536 °Festimated value(s)
Flash point	:	230 °C / 446 °F
		Method: ASTM D93 (PMCC)
Evaporation rate	:	Data not available
Flammability (solid, gas)	:	Data not available
Upper explosion limit	:	Typical 10 %(V)

Shell Argina S3 40 Local

pical 1 %(V) 0.5 Pa (20 °C / 68 °F) timated value(s) 1 estimated value(s) 900 (15 °C / 59 °F) 0 kg/m3 (15.0 °C / 59.0 °F) ethod: ASTM D4052 gligible ata not available g Pow: > 6(based on information on similar products)
timated value(s) 1estimated value(s) 900 (15 °C / 59 °F) 0 kg/m3 (15.0 °C / 59.0 °F) ethod: ASTM D4052 gligible ata not available
900 (15 °C / 59 °F) 0 kg/m3 (15.0 °C / 59.0 °F) ethod: ASTM D4052 gligible ata not available
0 kg/m3 (15.0 °C / 59.0 °F) ethod: ASTM D4052 gligible ata not available
ethod: ASTM D4052 gligible ata not available
ata not available
ata not available
g Pow: > 6(based on information on similar products)
320 °C / 608 °F
ata not available
ata not available
.2 mm2/s (100 °C / 212 °F) ethod: ASTM D445
8 mm2/s (40.0 °C / 104.0 °F) ethod: Unspecified
ot classified
ata not available

Reactivity	: The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	: Stable.
Possibility of hazardous reactions	: Reacts with strong oxidising agents.

Version 1.2		Revision Date 08.03.2021 Print Date 25.05.2023
Conditions to avoid	:	Extremes of temperature and direct sunlight.
Incompatible materials	:	Strong oxidising agents.
Hazardous decomposition products	:	No decomposition if stored and applied as directed.
11. TOXICOLOGICAL INFORMAT	101	N
Basis for assessment	:	Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
Information on likely routes of exposure	:	Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.
Acute toxicity		
Product:		
Acute oral toxicity	:	LD50 rat: > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classification criteria are not met.
Acute inhalation toxicity	:	Remarks: Based on available data, the classification criteria are not met.
Acute dermal toxicity	:	LD50 Rabbit: > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

Shell Argina S3 40 Local

Version 1.2	Revision Date 08.03.2021	Print Date 25.05.2023
Germ cell mutagenicity		
Product:		
	: Remarks: Non mutagenic, Based classification criteria are not met.	on available data, the
Carcinogenicity		
Product:		

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

Material	GHS/CLP Carcinogenicity Classification
Highly refined mineral oil	No carcinogenicity classification.

Reproductive toxicity

Product:

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The

Shell Argina S3 40 Local

Version 1.2	Revision Date 08.03.2021	Print Date 25.05.2023
concentration of suc	h impurities will depend on use and they may pre	sent risks to health and the
environment on disp	osal., ALL used oil should be handled with cautio	n and skin contact avoided
as far as possible.		

Remarks: Continuous contact with used engine oils has caused skin cancer in animal tests.

Remarks: Slightly irritating to respiratory system.

12. ECOLOGICAL INFORMATION

Basis for assessment	 Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).
Ecotoxicity	
Product:	
Toxicity to fish (Acute toxicity)	: Remarks: Based on available data, the classification criteria are not met. Practically non toxic: LL/EL/IL50 > 100 mg/I
Toxicity to crustacean (Acute toxicity)	: Remarks: Based on available data, the classification criteria are not met. Practically non toxic: LL/EL/IL50 > 100 mg/I
Toxicity to algae/aquatic plants (Acute toxicity)	: Remarks: Based on available data, the classification criteria are not met. Practically non toxic: LL/EL/IL50 > 100 mg/I
Toxicity to fish (Chronic toxicity)	: Remarks: Based on available data, the classification criteria are not met.
Toxicity to crustacean (Chronic toxicity)	: Remarks: Based on available data, the classification criteria are not met.
Toxicity to microorganisms (Acute toxicity)	: Remarks: Based on available data, the classification criteria are not met.

Persistence and degradability

Shell Argina S3 40 Local

Version 1.2	Revision Date 08.03.2021	Print Date 25.05.2023
Product:		
Biodegradability	: Remarks: Not readily biodegradable inherently biodegradable, but cont persist in the environment., Persis International Oil Pollution Compen definition: "A non-persistent oil is of shipment, consists of hydrocarbon of which, by volume, distills at a te and (b) at least 95% of which, by v temperature of 370°C (700°F) whe Method D-86/78 or any subsequer	ains components that may tent per IMO criteria., Isation (IOPC) Fund bil, which, at the time of fractions, (a) at least 50% mperature of 340°C (645°F) volume, distils at a en tested by the ASTM
Bioaccumulative potential		
Product:		
Bioaccumulation	: Remarks: Contains components w bioaccumulate.	ith the potential to
Partition coefficient: n- octanol/water	: log Pow: > 6Remarks: (based on i products)	nformation on similar
Mobility in soil		
Product:		
Mobility	 Remarks: Liquid under most enviro enters soil, it will adsorb to soil par mobile. Remarks: Floats on water. 	
Other adverse effects		
no data available <u>Product:</u>		
Additional ecological information	 Does not have ozone depletion po ozone creation potential or global is a mixture of non-volatile compor released to air in any significant qu conditions of use. Poorly soluble mixture., Causes pl organisms. Mineral oil does not cause chronic organisms at concentrations less t 	warming potential., Product nents, which will not be uantities under normal nysical fouling of aquatic toxicity to aquatic
13. DISPOSAL CONSIDERATIO	NS	
Disposal methods		

Waste from residues	 Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.
---------------------	---

Version 1.2	Revision Date 08.03.2021	Print Date 25.05.2023
	courses Do not dispose of tank wate drain into the ground. This w contamination.	ollector or contractor. The
	MARPOL - see International Pollution from Ships (MARP technical aspects at controlli	, ,
Contaminated packaging	to a recognized collector or the collector or contractor sh	prevailing regulations, preferably contractor. The competence of hould be established beforehand. dance with applicable regional, regulations.
Local legislation Remarks	: Disposal should be in accord national, and local laws and	dance with applicable regional, regulations.

14. TRANSPORT INFORMATION

International Regulations

ADR

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or

rsion 1.2	Revision Date	e 08.03.2021	Print Date 25.05.2023
mixture			
Local Regulations			
Workplace Safety and Healt Safety and Health (General Regulations		This product is n in the Act/Regula	ot subject to the requirements ations.
Fire Safety Act and Fire Safety (Petroleum & Flammable Materials) Regulations		This product is not in the Act/Regula	ot subject to the requirements ations.
Maritime and Port Authority of Singapore (Dangerous Goods, Petroleum and Explosives) Regulations		This product is n in the Act/Regula	ot subject to the requirements ations.
Environmental Protection an and Environmental Protection Management (Hazardous Su Regulations	on and	This product is n Act/ Regulation.	not subject to control under thi
	s not intended to be a	comprehensive. Of	ther regulations may apply to

The components of this product are reported in the following inventories:

	p
REACH	: All components listed or polymer exempt.
TSCA	: All components listed.

16. OTHER INFORMATION

Full text of H-Statements

H304 May be fatal if swallowed and enters airways. Full text of other abbreviations

Asp. Tox. Aspiration hazard

Abbreviations and Acronyms

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -

Shell Argina S3 40 Local

Version 1.2	Revision Date 08.03.2021	Print Date 25.05.2023
	n for Standardization; KECI - Korea Ex	
	50 % of a test population; LD50 - Letha	
	MARPOL - International Convention for	
	wise Specified; Nch - Chilean Norm; N	
	D(A)EL - No Observed (Adverse) Effe	
0,	0M - Official Mexican Norm; NTP - Nat	0, 0,
,	of Chemicals; OECD - Organization	
	Office of Chemical Safety and Pollu	
	xic substance; PICCS - Philippines Inv	
	(Quantitative) Structure Activity Relation	
	European Parliament and of the Cou	
	n and Restriction of Chemicals; SADT	
	fety Data Sheet; TCSI - Taiwan Chei	
	rous Goods; TSCA - Toxic Substance	
	G - United Nations Recommendation	
	Persistent and Very Bioaccumulative;	WHMIS - Workplace Hazardous
Materials Information Sy	stem	
Further information		

Further information

Training advice	•	Provide adequate information, instruction and training for operators.
Other information	:	A vertical bar () in the left margin indicates an amendment from the previous version.
Sources of key data used to compile the Safety Data Sheet	:	The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

SG / EN