Shell Gas Compressor Oil S3 PY 220

Version 1.0	Revision Date 07.09.2024	Print Date 08.09.2024
1. PRODUCT AND COMPANY IDE	NTIFICATION	
Product name	: Shell Gas Compressor Oil S3 PY 220	
Product code	: 001D8384	
Manufacturer or supplier's d	etails	
Supplier	 Shell Singapore Pte. Ltd. (196000089G) The Metropolis Tower 1, 9 North Buona Vista Drive, #07-01 Singapore 138588 Singapore 	
Telephone Telefax	: (+65) 62632975 : (+65) 62632049	
Emergency telephone	: +65 6263 2975	
Contact for Safety Data Sheet	: If you have any enquiries about the oplease email lubricantSDS@shell.co	
Recommended use of the ch	emical and restrictions on use	
Recommended use	: Compressor oil.	
Restrictions on use	: This product must not be used in appl listed in Section 1 without first seeking supplier.	
2. HAZARDS IDENTIFICATION		

GHS Classification

Based on available data this substance / mixture does not meet the classification criteria.

GHS label elements

Hazard pictograms	: No Hazard Symbol required	
Signal word	: No signal word	
Hazard statements	 PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS criteria. 	

Version 1.0	Revision Date 07.09.2024	Print Date 08.09.2024
Precautionary statements	:	
	Prevention:	
	No precautionary phrases.	
	Response:	
	No precautionary phrases.	
	no precadionary prirases.	
	Storage:	
	No precautionary phrases.	
	Disposal:	
	No precautionary phrases.	

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.Used oil may contain harmful impurities.Not classified as flammable but will burn.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	:	Mixture
3.2 Mixtures		
Chemical nature	:	Highly refined mineral oils and additives. The highly refined mineral oil contains <3% (w/w) DMSO- extract, according to IP346. Classification based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).

Components

Contains no hazardous ingredients according to GHS

4. FIRST-AID MEASURES	
If inhaled	: No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	: Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.

Shell Gas Compressor Oil S3 PY 220

Version 1.0		Revision Date 07.09.2024	Print Date 08.09.2024
In case of eye contact	:	Flush eye with copious quantities of wa Remove contact lenses, if present and rinsing. If persistent irritation occurs, obtain me	l easy to do. Continue
If swallowed	:	In general no treatment is necessary u are swallowed, however, get medical a	
Most important symptoms and effects, both acute and delayed	:	Oil acne/folliculitis signs and symptoms of black pustules and spots on the skir Ingestion may result in nausea, vomitir	n of exposed areas.
Protection of first-aiders	:	When administering first aid, ensure th appropriate personal protective equipn incident, injury and surroundings.	
Notes to physician	:	Treat symptomatically.	
5. FIRE-FIGHTING MEASURES			
Suitable extinguishing media	:	Foam, water spray or fog. Dry chemica dioxide, sand or earth may be used for	
Unsuitable extinguishing media	:	Do not use water in a jet.	
Specific hazards during firefighting	:	Hazardous combustion products may i A complex mixture of airborne solid an gases (smoke). Carbon monoxide may be evolved if in occurs. Unidentified organic and inorganic con	d liquid particulates and complete combustion

Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.	
Special protective equipment for firefighters	: Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire ir a confined space. Select fire fighter's clothing approved to	

6. ACCIDENTAL RELEASE MEASURES

Personal precautions,	: Avoid contact with skin and eyes.
protective equipment and	

relevant Standards (e.g. Europe: EN469).

	Revision Date 07.09.2024	Print Date 08.09.202
emergency procedures Environmental precautions	Prevent from spreading or en using sand, earth, or other a	t to prevent uncontrolled release ntering drains, ditches or rivers b ppropriate barriers. advised if significant spillages
	cannot be contained.	
Methods and materials for containment and cleaning up	Prevent from spreading by m or other containment materia Reclaim liquid directly or in a	an absorbent. sorbent such as clay, sand or oth
Additional advice	see Section 8 of this Safety	f personal protective equipment Data Sheet. spilled material see Section 13 c
ANDLING AND STORAGE		
General Precautions	: Use local exhaust ventilation vapours, mists or aerosols. Use the information in this data assessment of local circums appropriate controls for safe this material.	ata sheet as input to a risk
Advice on safe handling	: Avoid prolonged or repeated Avoid inhaling vapour and/or	r mists.
	When handling product in dr worn and proper handling ec Properly dispose of any cont materials in order to prevent	taminated rags or cleaning
Avoidance of contact	worn and proper handling ec Properly dispose of any cont	quipment should be used. taminated rags or cleaning
Avoidance of contact Product Transfer	 worn and proper handling economic Properly dispose of any continuaterials in order to prevent Strong oxidising agents. Proper grounding and bonding 	quipment should be used. taminated rags or cleaning fires. ng procedures should be used
	 worn and proper handling economic Properly dispose of any continuaterials in order to prevent Strong oxidising agents. Proper grounding and bonding 	quipment should be used. taminated rags or cleaning fires. ng procedures should be used
Product Transfer	 worn and proper handling ed Properly dispose of any cont materials in order to prevent Strong oxidising agents. Proper grounding and bondin during all bulk transfer opera 	quipment should be used. taminated rags or cleaning fires. ng procedures should be used ations to avoid static accumulatio

Version 1.0	Revision Date 07.09.2024	Print Date 08.09.2024
Packaging material	: Suitable material: For containers o steel or high density polyethylene. Unsuitable material: PVC.	r container linings, use mild
Container Advice	: Polyethylene containers should no temperatures because of possible	

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	PEL (long term) (Mist)	5 mg/m3	SG OEL
Oil mist, mineral	Not Assigned	PEL (short term) (Mist)	10 mg/m3	SG OEL
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1
Oil mist, mineral	Not Assigned	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures

: The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances.

 Appropriate measures include: Adequate ventilation to control airborne control airborne control airborne control airborne control airborne concentration General Information: Define procedures for safe handling and n controls. Educate and train workers in the hazards measures relevant to normal activities ass product. Ensure appropriate selection, testing and not control to the selection of t	formed, there is ns to be generated. naintenance of and control
Where material is heated, sprayed or mist greater potential for airborne concentration General Information: Define procedures for safe handling and n controls. Educate and train workers in the hazards measures relevant to normal activities ass product.	formed, there is ns to be generated. naintenance of and control
greater potential for airborne concentration General Information: Define procedures for safe handling and n controls. Educate and train workers in the hazards measures relevant to normal activities ass product.	ns to be generated. naintenance of and control
Define procedures for safe handling and n controls. Educate and train workers in the hazards measures relevant to normal activities ass product.	and control
measures relevant to normal activities ass product.	
Ensure appropriate selection testing and	
equipment used to control exposure, e.g. equipment, local exhaust ventilation.	
Drain down system prior to equipment bre	ak-in or
Retain drain downs in sealed storage pen subsequent recycle.	ding disposal or
Always observe good personal hygiene m washing hands after handling the material drinking, and/or smoking. Routinely wash protective equipment to remove contamina contaminated clothing and footwear that c Practice good housekeeping.	and before eating, work clothing and ants. Discard
	 equipment, local exhaust ventilation. Drain down system prior to equipment bremaintenance. Retain drain downs in sealed storage pensubsequent recycle. Always observe good personal hygiene mwashing hands after handling the material drinking, and/or smoking. Routinely washing protective equipment to remove contaminated clothing and footwear that or contaminated clothing and f

Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory protection	No respiratory protection is ordinarily required und conditions of use. In accordance with good industrial hygiene practic precautions should be taken to avoid breathing of f engineering controls do not maintain airborne concentrations to a level which is adequate to pro health, select respiratory protection equipment su specific conditions of use and meeting relevant leg Check with respiratory protective equipment supp Where air-filtering respirators are suitable, select a appropriate combination of mask and filter. Select a filter suitable for the combination of organ and vapours and particles [Type A/Type P boiling 149°F)].	es, material. tect worker table for the gislation. liers. an
Hand protection Remarks	Where hand contact with the product may occur th ploves approved to relevant standards (e.g. Europ JS: F739) made from the following materials may suitable chemical protection. PVC, neoprene or n	e: EN374, provide

Version 1.0	Revision Date 07.09.2024	Print Date 08.09.2024
	gloves Suitability and durability o usage, e.g. frequency and durati- resistance of glove material, dext from glove suppliers. Contamina- replaced. Personal hygiene is a care. Gloves must only be worn o gloves, hands should be washed Application of a non-perfumed m For continuous contact we recom- breakthrough time of more than 2	on of contact, chemical terity. Always seek advice ted gloves should be key element of effective hand on clean hands. After using and dried thoroughly. oisturizer is recommended.
	for > 480 minutes where suitable short-term/splash protection we recognize that suitable gloves off may not be available and in this of time maybe acceptable so long a and replacement regimes are foll a good predictor of glove resistant dependent on the exact composite Glove thickness should be typicate depending on the glove make an	ecommend the same but fering this level of protection case a lower breakthrough as appropriate maintenance lowed. Glove thickness is not note to a chemical as it is tion of the glove material. Illy greater than 0.35 mm
Eye protection	: If material is handled such that it protective eyewear is recommen	
Skin and body protection	: Skin protection is not ordinarily re work clothes. It is good practice to wear chemic	
Thermal hazards	: Not applicable	
Environmental exposure con	trols	
General advice	: Take appropriate measures to fur relevant environmental protection contamination of the environment Section 6. If necessary, prevent being discharged to waste water treated in a municipal or industria before discharge to surface water Local guidelines on emission limit must be observed for the dischar vapour.	n legislation. Avoid t by following advice given in undissolved material from . Waste water should be al waste water treatment plant r. its for volatile substances
9. PHYSICAL AND CHEMICAL PR	OPERTIES	
Appearance	: Liquid at room temperature.	
Colour	: yellow	
Odour	: Data not available	
Odour Threshold	: Data not available	

sion 1.0 pH	Revision Date 07.09.2024 : Not applicable	Print Date 08.09.20
pour point	: -12 °C / 10 °F	
	Method: ASTM D97	
Melting / freezing point	Data not available	
Initial boiling point and boiling range	: > 280 °C / 536 °Festimated v	value(s)
Flash point	: >= 240 °C / >= 464 °F Method: ASTM D92 (COC)	
Evaporation rate	: Data not available	
Flammability (solid, gas)	: Not applicable	
Flammability (liquids)	: Not classified as flammable t	out will burn.
Upper explosion limit	: Typical 10 %(V)	
Lower explosion limit	: Typical 1 %(V)	
Vapour pressure	: < 0.5 Pa (20 °C / 68 °F) estimated value(s)	
Relative vapour density	: >5	
Relative density	: 0.874	
Density	: 874 kg/m3 (15.0 °C / 59.0 °F Method: ASTM D1298)
Solubility(ies)		
Water solubility	: negligible	
Solubility in other solvents	: Data not available	
Partition coefficient: n- octanol/water	: log Pow: > 6 (based on information on sim	nilar products)
Auto-ignition temperature	: > 320 °C / 608 °F	
Decomposition temperature	: Data not available	
Viscosity		
Viscosity, dynamic	: Data not available	
Viscosity, kinematic	: 225 mm2/s (40.0 °C / 104.0 ° Method: ASTM D445	°F)
	20.5 mm2/s (100 °C / 212 °F)

Version 1.0		Revision Date 07.09.2024 Method: ASTM D445	Print Date 08.09.2024
Particle characteristics Particle size	:	: Data not available	
Explosive properties	:	Classification Code: Not classified	
Oxidizing properties	:	Data not available	
Conductivity	:	This material is not expected to be a st	tatic accumulator.
10. STABILITY AND REACTIVITY			
Reactivity	:	The product does not pose any further addition to those listed in the following	
Chemical stability	:	Stable.	
Possibility of hazardous reactions	:	Reacts with strong oxidising agents.	
Conditions to avoid	:	Extremes of temperature and direct su	nlight.
Incompatible materials	:	Strong oxidising agents.	
Hazardous decomposition products	:	No decomposition if stored and applied	d as directed.
11. TOXICOLOGICAL INFORMAT	10	Ν	
Basis for assessment	:	Information given is based on data on the toxicology of similar products.Unles the data presented is representative of whole, rather than for individual compo	ss indicated otherwise, the product as a
Information on likely routes of exposure	:	Skin and eye contact are the primary realthough exposure may occur following	
Acute toxicity			
Product:			
Acute oral toxicity	:	LD50 rat: > 5,000 mg/kg Remarks: Low toxicity Based on available data, the classifica	tion criteria are not met.

Version 1.0	Revision Date 07.09.2024	Print Date 08.09.2024
Acute inhalation toxicity	: Remarks: Based on available data, are not met.	the classification criteria
Acute dermal toxicity	: LD50 Rabbit: > 5,000 mg/kg Remarks: Low toxicity Based on available data, the classifi	cation criteria are not met.

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

Material	GHS/CLP Carcinogenicity Classification
Highly refined mineral oil	No carcinogenicity classification.

Reproductive toxicity

Shell Gas Compressor Oil S3 **PY 220**

Version 1.0 Revision Date 07.09.2024 Print Date 08.09.2024 Product:

> Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

12. ECOLOGICAL INFORMATION	
Basis for assessment	 Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
Ecotoxicity	
Product:	
Toxicity to fish (Acute toxicity)	: Remarks: Based on available data, the classification criteria
11 / 16	800001006687

SG

ersion 1.0	Revision Date 07.09.2024	Print Date 08.09.2024
	are not met. Practically non toxic: LL/EL/IL50 > 100 mg/l	
Toxicity to crustacean (Acute toxicity)	: Remarks: Based on available da	ta the classification criteria
	are not met. Practically non toxic: LL/EL/IL50 > 100 mg/l	
Toxicity to algae/aquatic plants (Acute toxicity)	: Remarks: Based on available da are not met. Practically non toxic: LL/EL/IL50 > 100 mg/l	ta, the classification criteria
Toxicity to fish (Chronic toxicity)	: Remarks: Based on available da are not met.	ta, the classification criteria
Toxicity to crustacean (Chronic toxicity)	: Remarks: Based on available da are not met.	ta, the classification criteria
Toxicity to microorganisms (Acute toxicity)	: Remarks: Based on available da are not met.	ta, the classification criteria
ersistence and degradability		
Product:		
Biodegradability	: Remarks: Not readily biodegrada inherently biodegradable, but co persist in the environment., Pers International Oil Pollution Compe definition: "A non-persistent oil is shipment, consists of hydrocarbo of which, by volume, distills at a and (b) at least 95% of which, by temperature of 370°C (700°F) wh Method D-86/78 or any subseque	ntains components that may istent per IMO criteria., ensation (IOPC) Fund s oil, which, at the time of on fractions, (a) at least 50% temperature of 340°C (645°F v volume, distils at a nen tested by the ASTM
oaccumulative potential		
Product:		
Bioaccumulation	: Remarks: Contains components bioaccumulate.	with the potential to
Partition coefficient: n- octanol/water	: log Pow: > 6Remarks: (based or products)	n information on similar
obility in soil		
Product:		
	: Remarks: Liquid under most env	

Version 1.0	Revision Date 07.09.2024 Print Date 08.09.2024
	enters soil, it will adsorb to soil particles and will not be mobile.
	Remarks: Floats on water.
Other adverse effects	
no data available Product:	
Additional ecological information	 Does not have ozone depletion potential, photochemical ozone creation potential or global warming potential., Product is a mixture of non-volatile components, which will not be released to air in any significant quantities under normal conditions of use. Poorly soluble mixture., Causes physical fouling of aquatic organisms. Mineral oil does not cause chronic toxicity to aquatic organisms at concentrations less than 1 mg/l.
13. DISPOSAL CONSIDERATION	S
Disposal methods	
Waste from residues	 Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Do not dispose into the environment, in drains or in water courses. Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination. Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand. MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.
Contaminated packaging	: Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.
Local legislation Remarks	: All relevant environmental regulations in Singapore must be
13/16	800001006687

Version 1.0

Revision Date 07.09.2024 complied with.

Print Date 08.09.2024

14. TRANSPORT INFORMATION

International Regulations

ADR

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Local Regulations

Workplace Safety and Health Act & Workplace Safety and Health (General Provision) Regulations	This product is not subject to the requirements in the Act/Regulations.
Fire Safety Act and Fire Safety (Petroleum & Flammable Materials) Regulations	This product is not subject to the requirements in the Act/Regulations.
Maritime and Port Authority of Singapore (Dangerous Goods, Petroleum and Explosives) Regulations	This product is not subject to the requirements in the Act/Regulations.
Environmental Protection and Management Act and Environmental Protection and Management (Hazardous Substances) Regulations	This product is not subject to control under this Act/ Regulation.
The regulatory information is not intended to be of this material.	comprehensive. Other regulations may apply to

Version 1.0

Revision Date 07.09.2024

Print Date 08.09.2024

Other international regulations

The components of this product are reported in the following inventories:

TSCA

: All components listed.

16. OTHER INFORMATION

Abbreviations and Acronyms

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response: ELx - Loading rate associated with x% response: EmS - Emergency Schedule: ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose): MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC -New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG -Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Further information

Training advice	:	Provide adequate information, instruction and training for operators.
Other information	:	A vertical bar () in the left margin indicates an amendment from the previous version.

Shell Gas Compressor Oil S3 PY 220

Version 1.0	Revision Date 07.09.2024	Print Date 08.09.2024
Sources of key data used to compile the Safety Data Sheet	: The quoted data are from, but not sources of information (e.g. toxico Health Services, material supplier IUCLID date base, EC 1272 regul	logical data from Shell s' data, CONCAWE, EU

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

SG / EN