Regulation 1907/2006/EC

AeroShell SSF

Version 4.0 Revision Date 08.07.2015 Print Date 10.07.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : AeroShell SSF Product code : 001A0078

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Mineral shock-absorber fluid for aircraft., For further details

Substance/Mixture consult the AeroShell Book on www.shell.com/aviation.

Uses advised against : This product must be used, handled and applied in

accordance with the requirements of the equipment

manufacturer's manuals, bulletins and other documentation. This product must not be used in applications other than those

listed in Section 1 without first seeking the advice of the

supplier.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier : Shell Italia Oil Products SRL

Via Vittor Pisani 16 I-20124 Milano MI

Telephone : (+39) 0200695000 Telefax : (+39) 022484260

Email Contact for Safety Data : If you have any enquiries about the content of this SDS

Sheet please email lubricantSDS@shell.com

1.4 Emergency telephone number

: (+39) 02 3800.4461/2 (available 24h a day)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters

airways.

Chronic aquatic toxicity, Category 3 H412: Harmful to aquatic life with long lasting

effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Version 4.0 Revision Date 08.07.2015 Print Date 10.07.2015

Hazard pictograms :

Signal word : Dange

Hazard statements : PHYSICAL HAZARDS:

Not classified as a physical hazard

according to CLP criteria. HEALTH HAZARDS:

H304 May be fatal if swallowed and enters

airways.

ENVIRONMENTAL HAZARDS:

H412 Harmful to aquatic life with long lasting

effects.

Precautionary statements : **Prevention**:

P273 Avoid release to the environment.

Response:

P301 + P310 IF SWALLOWED: Immediately call a

POISON CENTER/doctor.
P331 Do NOT induce vomiting.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an

approved waste disposal plant.

Hazardous components which must be listed on the label:

Contains Distillates (petroleum), hydrotreated light naphthenic.

2.3 Other hazards

This mixture does not contain any REACH registered substances that are assessed to be a PBT or a

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used oil may contain harmful impurities.

High-pressure injection under the skin may cause serious damage including local necrosis.

Not classified as flammable but will burn.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Highly refined mineral oils and additives.

The highly refined mineral oil contains <3% (w/w) DMSO-

extract, according to IP346.

Hazardous components

Version 4.0 Revision Date 08.07.2015 Print Date 10.07.2015

Chemical Name	CAS-No.	Classification	Concentration
CC.IIIIGAI I IGAIIIG	EC-No.	(REGULATION	[%]
	Registration	(EC) No	[]
	number	1272/2008)	
Distillates	64742-53-6	Asp. Tox.1; H304	60 - 80
(petroleum),	265-156-6 / 01-		
hydrotreated light	2119480375-34		
naphthenic			
Distillates	64742-47-8	Asp. Tox.1; H304	15 - 25
(petroleum),	265-149-8 / 01-		
hydrotreated light	2119484819-18		
Barium alkaryl	25619-56-1	Acute Tox.4; H332	1 - 5
sulphonate	247-132-7	Acute Tox.4; H302	
		2; H315	
Zinc alkyl	68649-42-3	Skin Irrit.2; H315	1 - 2,49
dithiophosphate	272-028-3	Eye Dam.1; H318	
		Aquatic Chronic2;	
		H411	
Butylated	128-37-0	Aquatic Chronic1;	0,25 - 0,99
hydroxytoluene	204-881-4 / 01-	H410	
	2119565113-46	Aquatic Acute1;	
		H400	
Triphenylphosphate	68937-40-6	Aquatic Acute1;	0,25 - 0,99
butylated (2.5-<25%	273-065-8 / 01-	H400	
TPP)	2119519251-50	Aquatic Chronic1;	
		H410	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

Protection of first-aiders : When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

If inhaled : No treatment necessary under normal conditions of use.

If symptoms persist, obtain medical advice.

In case of skin contact : Remove contaminated clothing. Flush exposed area with

water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.

When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait

for symptoms to develop.

Obtain medical attention even in the absence of apparent

wounds.

Regulation 1907/2006/EC

AeroShell SSF

Version 4.0 Revision Date 08.07.2015 Print Date 10.07.2015

In case of eye contact : Flush eye with copious quantities of water.

If persistent irritation occurs, obtain medical attention.

If swallowed : If swallowed, do not induce vomiting: transport to nearest

medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : If material enters lungs, signs and symptoms may include

coughing, choking, wheezing, difficulty in breathing, chest

congestion, shortness of breath, and/or fever.

The onset of respiratory symptoms may be delayed for

several hours after exposure.

Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance. Ingestion may result in nausea, vomiting and/or diarrhoea.

Local necrosis is evidenced by delayed onset of pain and

tissue damage a few hours following injection.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Notes to doctor/physician:

Treat symptomatically.

Call a doctor or poison control center for guidance.

High pressure injection injuries require prompt surgical intervention and possibly steroid therapy, to minimise tissue

damage and loss of function.

Because entry wounds are small and do not reflect the seriousness of the underlying damage, surgical exploration to determine the extent of involvement may be necessary. Local anaesthetics or hot soaks should be avoided because they can contribute to swelling, vasospasm and ischaemia. Prompt surgical decompression, debridement and evacuation of foreign material should be performed under general

foreign material should be performed under ger anaesthetics, and wide exploration is essential.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon

dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing

media

: Do not use water in a jet.

5.2 Special hazards arising from the substance or mixture

4 / 20 80000100145<u>4</u>

Regulation 1907/2006/EC

AeroShell SSF

Version 4.0 Revision Date 08.07.2015 Print Date 10.07.2015 Specific hazards during : Hazardous combustion products may include: A complex

firefighting mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic

compounds.

5.3 Advice for firefighters

Special protective equipment

for firefighters

: Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : 6.1.1 For non emergency personnel:

> Avoid contact with skin and eyes. 6.1.2 For emergency responders: Avoid contact with skin and eyes.

6.2 Environmental precautions

Environmental precautions : Use appropriate containment to avoid environmental

> contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate

barriers.

Local authorities should be advised if significant spillages

cannot be contained.

6.3 Methods and materials for containment and cleaning up

: Slippery when spilt. Avoid accidents, clean up immediately. Methods for cleaning up

Prevent from spreading by making a barrier with sand, earth

or other containment material.

Reclaim liquid directly or in an absorbent.

Soak up residue with an absorbent such as clay, sand or other

suitable material and dispose of properly.

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.

Regulation 1907/2006/EC

AeroShell SSF

Version 4.0 Revision Date 08.07.2015 Print Date 10.07.2015

SECTION 7: Handling and storage

General Precautions : Use local exhaust ventilation if there is risk of inhalation of

vapours, mists or aerosols.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine

appropriate controls for safe handling, storage and disposal of

this material.

7.1 Precautions for safe handling

Advice on safe handling : Avoid prolonged or repeated contact with skin.

Avoid inhaling vapour and/or mists.

When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning

materials in order to prevent fires.

Product Transfer : This material has the potential to be a static accumulator.

Proper grounding and bonding procedures should be used

during all bulk transfer operations.

7.2 Conditions for safe storage, including any incompatibilities

Other data : Keep container tightly closed and in a cool, well-ventilated

place. Use properly labeled and closable containers.

Storage temperature : -50 - 50 °C

Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

Packaging material : Suitable material: For containers or container linings, use mild

steel or high density polyethylene.

Unsuitable material: PVC.

Container Advice : Polyethylene containers should not be exposed to high

temperatures because of possible risk of distortion.

7.3 Specific end use(s)

Specific use(s) : Not applicable

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Version 4.0 Revision Date 08.07.2015 Print Date 10.07.2015

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Oil mist, mineral		TWA	5 mg/m3	US. ACGIH Threshold Limit Values
Oil mist, mineral		TWA	5 mg/m3	Italy. OELs

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

8.2 Exposure controls

Engineering measures The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Version 4.0 Revision Date 08.07.2015 Print Date 10.07.2015

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Do not ingest. If swallowed then seek immediate medical assistance

Personal protective equipment

The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : If material is handled such that it could be splashed into eyes,

> protective eyewear is recommended. Approved to EU Standard EN166.

Hand protection

Remarks : Where hand contact with the product may occur the use of

> gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

> For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.

Skin and body protection Skin protection is not ordinarily required beyond standard

work clothes.

It is good practice to wear chemical resistant gloves.

Respiratory protection No respiratory protection is ordinarily required under normal

Version 4.0 Revision Date 08.07.2015 Print Date 10.07.2015

conditions of use.

In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material.

If engineering controls do not maintain airborne

concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an

appropriate combination of mask and filter.

Select a filter suitable for combined particulate/organic gases and vapours [Type A/Type P boiling point > 65°C (149°F)]

meeting EN14387 and EN143.

Thermal hazards : Not applicable

Environmental exposure controls

General advice : Take appropriate measures to fulfill the requirements of

relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Chapter 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant

before discharge to surface water.

Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing

vapour.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : yellow

Odour : Slight hydrocarbon Odour Threshold : Data not available Hq : Not applicable

: -62 °CMethod: Unspecified pour point

Initial boiling point and boiling : > 280 °Cestimated value(s)

range

Flash point : 108 °C

Method: Unspecified

Regulation 1907/2006/EC

AeroShell SSF

Version 4.0 Revision Date 08.07.2015 Print Date 10.07.2015

Evaporation rate : Data not available Flammability (solid, gas) : Data not available

Upper explosion limit : Typical 10 %(V)

Lower explosion limit : Typical 1 %(V)

Vapour pressure : < 0,5 Pa (20 °C)

estimated value(s)

Relative vapour density : > 1estimated value(s)

Relative density : 0,880 (15 °C)

Density : 880 kg/m3 (15,0 °C)

Method: Unspecified

Solubility(ies)

Water solubility : negligible

Solubility in other solvents : Data not available

Partition coefficient: n-

octanol/water

: Pow: > 6(based on information on similar products)

Auto-ignition temperature : >

320 °C

Viscosity

Viscosity, dynamic : Data not available

Viscosity, kinematic : 14,5 mm2/s (40,0 °C)

Method: Unspecified

560 mm2/s (-40 °C) Method: Unspecified

2.640 mm2/s (-54 °C) Method: Unspecified

Explosive properties : Not classified

Oxidizing properties : Data not available

9.2 Other information

Conductivity : This material is not expected to be a static accumulator.

Regulation 1907/2006/EC

AeroShell SSF

Version 4.0 Revision Date 08.07.2015 Print Date 10.07.2015

Decomposition temperature : Data not available

SECTION 10: Stability and reactivity

10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

10.2 Chemical stability

Stable.

No hazardous reaction is expected when handled and stored according to provisions

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with strong oxidising agents.

10.4 Conditions to avoid

Conditions to avoid : Extremes of temperature and direct sunlight.

10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

10.6 Hazardous decomposition products

Hazardous decomposition

products

: Hazardous decomposition products are not expected to form

during normal storage.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information given is based on data on the components and Basis for assessment

the toxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a

whole, rather than for individual component(s).

Information on likely routes of :

exposure

Skin and eye contact are the primary routes of exposure

although exposure may occur following accidental ingestion.

Acute toxicity

Product:

: LD50 rat: > 5.000 mg/kg Acute oral toxicity

Remarks: Expected to be of low toxicity:

Remarks: Aspiration into the lungs may cause chemical

Regulation 1907/2006/EC

AeroShell SSF

Version 4.0 Revision Date 08.07.2015 Print Date 10.07.2015

pneumonitis which can be fatal.

Acute inhalation toxicity : Remarks: Not considered to be an inhalation hazard under

normal conditions of use.

Acute dermal toxicity : LD50 Rabbit: > 5.000 mg/kg

Remarks: Expected to be of low toxicity:

Skin corrosion/irritation

Product:

Remarks: Expected to be slightly irritating., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Serious eye damage/eye irritation

Product:

Remarks: Expected to be slightly irritating.

Components:

Zinc alkyl dithiophosphate:

Remarks: Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: For respiratory and skin sensitisation:, Not expected to be a sensitiser.

Germ cell mutagenicity

Product:

: Remarks: Not considered a mutagenic hazard.

Carcinogenicity

Product:

Remarks: Not expected to be carcinogenic.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

Material GHS/CLP Carcinogenicity Classification

Regulation 1907/2006/EC

AeroShell SSF

1/	Davidsian Data 00 07 0045	Duint Data 40 07 0045
Version 4.0	Revision Date 08.07.2015	Print Date 10.07.2015

Highly refined mineral oil	No carcinogenicity classification.
Butylated hydroxytoluene	No carcinogenicity classification.

Reproductive toxicity

Product:

Remarks: Not expected to impair fertility., Not expected to be a developmental toxicant.

STOT - single exposure

Product:

Remarks: Not expected to be a hazard.

STOT - repeated exposure

Product:

Remarks: Not expected to be a hazard.

Aspiration toxicity

Product:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.

Remarks: Slightly irritating to respiratory system.

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

Summary on evaluation of the CMR properties

Germ cell mutagenicity- : This product does not meet the criteria for classification in

Assessment categories 1A/1B.

Regulation 1907/2006/EC

AeroShell SSF

Version 4.0 Revision Date 08.07.2015 Print Date 10.07.2015

Carcinogenicity -Assessment

This product does not meet the criteria for classification in

categories 1A/1B.

Reproductive toxicity -

Assessment

: This product does not meet the criteria for classification in

categories 1A/1B.

SECTION 12: Ecological information

12.1 Toxicity

Basis for assessment : Ecotoxicological data have not been determined specifically

for this product.

Information given is based on a knowledge of the components

and the ecotoxicology of similar products.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test

extract).

Product:

Toxicity to fish (Acute

toxicity)

: Remarks: Expected to be harmful:

LL/EL/IL50 10-100 mg/l

Toxicity to crustacean (Acute

toxicity)

: Remarks: Expected to be harmful:

LL/EL/IL50 10-100 mg/l

Toxicity to algae/aquatic

plants (Acute toxicity)

: Remarks: Expected to be harmful:

LL/EL/IL50 10-100 mg/l

: Remarks: Data not available

Toxicity to fish (Chronic

toxicity)

Toxicity to crustacean

(Chronic toxicity)

Toxicity to microorganisms

(Acute toxicity)

: Remarks: Data not available

Remarks: Data not available

Components:

Butylated hydroxytoluene:

M-Factor (Acute aquatic

: 1

toxicity)

12.2 Persistence and degradability

Product:

14/20 800001001454 IT

Regulation 1907/2006/EC

AeroShell SSF

Version 4.0 Revision Date 08.07.2015 Print Date 10.07.2015

Biodegradability : Remarks: Expected to be not readily biodegradable., Major

constituents are expected to be inherently biodegradable, but contains components that may persist in the environment.

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Contains components with the potential to

bioaccumulate.

Partition coefficient: n-

octanol/water

: Pow: > 6Remarks: (based on information on similar products)

12.4 Mobility in soil

Product:

Mobility : Remarks: Liquid under most environmental conditions., If it

enters soil, it will adsorb to soil particles and will not be

mobile.

Remarks: Floats on water.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This mixture does not contain any REACH registered

substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects

Product:

Additional ecological

information

: Product is a mixture of non-volatile components, which are not

expected to be released to air in any significant quantities.,

Not expected to have ozone depletion potential,

photochemical ozone creation potential or global warming

potential.

Poorly soluble mixture., May cause physical fouling of aquatic

organisms.

Mineral oil is not expected to cause any chronic effects to aquatic organisms at concentrations less than 1 mg/l.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Waste product should not be allowed to contaminate soil or

ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.

Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local regulations may be more stringent than regional or

national requirements and must be complied with.

Version 4.0 Revision Date 08.07.2015 Print Date 10.07.2015

Contaminated packaging : Dispose in accordance with prevailing regulations, preferably

to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local legislation

Waste catalogue : EU Waste Disposal Code (EWC):

Waste Code : 13 01 10*

Remarks : Classification of waste is always the responsibility of the end

user.

For the disposal of waste arising from the product, including empty containers not cleared, follow the Legislative Decree

152/06 and subsequent amendments.

SECTION 14: Transport information

14.1 UN number

ADN : Not regulated as a dangerous good ADR : Not regulated as a dangerous good RID : Not regulated as a dangerous good IMDG : Not regulated as a dangerous good IATA : Not regulated as a dangerous good IATA

14.2 Proper shipping name

ADN : Not regulated as a dangerous good ADR : Not regulated as a dangerous good RID : Not regulated as a dangerous good IMDG : Not regulated as a dangerous good IATA : Not regulated as a dangerous good IATA : Not regulated as a dangerous good

14.3 Transport hazard class

ADN : Not regulated as a dangerous good ADR : Not regulated as a dangerous good RID : Not regulated as a dangerous good IMDG : Not regulated as a dangerous good IATA : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good ADR : Not regulated as a dangerous good RID : Not regulated as a dangerous good IMDG : Not regulated as a dangerous good

Regulation 1907/2006/EC

AeroShell SSF

Version 4.0 Revision Date 08.07.2015 Print Date 10.07.2015

IATA : Not regulated as a dangerous good

14.5 Environmental hazards

ADN : Not regulated as a dangerous good ADR : Not regulated as a dangerous good RID : Not regulated as a dangerous good IMDG : Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Special Precautions: Refer to Chapter 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pollution category : Not applicable
Ship type : Not applicable
Product name : Not applicable
Special precautions : Not applicable

Additional Information: MARPOL Annex 1 rules apply for bulk shipments by sea.

ADN - Classified ID9006 only when carried in tank vessels.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation : Product is not subject to

(Annex XIV) Authorisation under REACH.

Volatile organic compounds : 0 %

Other regulations : Classification, packaging and labeling of dangerous

substances (D.Lgs.52/1997 and subsequent amendments).

Classification, packaging and labeling of dangerous preparations (D.Lgs.65/2003). Safeguard of health and safety

in the workplaces (D.Lgs.81/2008 and subsequent

amendments). For waste disposal refer to D.Lgs.152/06 and

subsequent amendments.

The components of this product are reported in the following inventories:

EINECS : All components listed or polymer exempt.

TSCA : All components listed.

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

Version 4.0 Revision Date 08.07.2015 Print Date 10.07.2015

SECTION 16: Other information

REGULATION (EC) No 1272/2008 Classification procedure:

Aspiration hazard, Category 1, H304	Expert judgement and weight of evidence
	determination.
Chronic aquatic toxicity, Category 3, H412	Expert judgement and weight of evidence
H412	determination.

Full text of H-Statements

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	Acute toxicity
Aquatic Acute	Acute aquatic toxicity
Aquatic Chronic	Chronic aquatic toxicity
Asp. Tox.	Aspiration hazard
Eye Dam.	Serious eye damage
Skin Irrit	Skin irritation

Skiii iiiii. Skiii iiiilali

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial Hygienists

ADR = European Agreement concerning the International

Carriage of Dangerous Goods by Road

AICS = Australian Inventory of Chemical Substances ASTM = American Society for Testing and Materials

BEL = Biological exposure limits

BTEX = Benzene, Toluene, Ethylbenzene, Xylenes

CAS = Chemical Abstracts Service

CEFIC = European Chemical Industry Council CLP = Classification Packaging and Labelling

COC = Cleveland Open-Cup

DIN = Deutsches Institut fur Normung
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
DSL = Canada Domestic Substance List

EC = European Commission EC50 = Effective Concentration fifty

ECETOC = European Center on Ecotoxicology and

Toxicology Of Chemicals

ECHA = European Chemicals Agency

18 / 20 80000100145<u>4</u>

Version 4.0 Revision Date 08.07.2015 Print Date 10.07.2015

EINECS = The European Inventory of Existing Commercial

Chemical Substances

EL50 = Effective Loading fifty

ENCS = Japanese Existing and New Chemical Substances

Inventory

EWC = European Waste Code

GHS = Globally Harmonised System of Classification and

Labelling of Chemicals

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IC50 = Inhibitory Concentration fifty

IL50 = Inhibitory Level fifty

IMDG = International Maritime Dangerous Goods

INV = Chinese Chemicals Inventory

IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables

KECI = Korea Existing Chemicals Inventory

LC50 = Lethal Concentration fifty

LD50 = Lethal Dose fifty per cent.

LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading

LL50 = Lethal Loading fifty

MARPOL = International Convention for the Prevention of

Pollution From Ships

NOEC/NOEL = No Observed Effect Concentration / No

Observed Effect Level

OE_HPV = Occupational Exposure - High Production Volume

PBT = Persistent, Bioaccumulative and Toxic

PICCS = Philippine Inventory of Chemicals and Chemical

Substances

PNEC = Predicted No Effect Concentration

REACH = Registration Evaluation And Authorisation Of

Chemicals

RID = Regulations Relating to International Carriage of

Dangerous Goods by Rail SKIN_DES = Skin Designation STEL = Short term exposure limit TRA = Targeted Risk Assessment

TSCA = US Toxic Substances Control Act

TWA = Time-Weighted Average

vPvB = very Persistent and very Bioaccumulative

Further information

Other information : A vertical bar (|) in the left margin indicates an amendment

from the previous version.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

Regulation 1907/2006/EC

AeroShell SSF

 Version 4.0
 Revision Date 08.07.2015
 Print Date 10.07.2015