

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Turbine Oil 500

Version	Revision Date:	SDS Number:	Date of last issue: 15.09.2023
7.1	12.05.2025	800001001487	Print Date 13.05.2025

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name	: AeroShell Turbine Oil 500
Product code	: 001A0083

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- stance/Mixture	: Synthetic lubricating oil for aircraft turbine engines., For further details consult the AeroShell Book on <a href="http://www.shell.com/aviation">www.shell.com/aviation</a> .
Uses advised against	: This product must be used, handled, and applied in accordance with the requirements of the equipment manufacturer's manuals, bulletins and other documentation. This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier.

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier	: <b>Shell Italia Oil Products SRL</b> Via Vittor Pisani 16 I-20124 Milano MI
Telephone	: (+39) 0200695000
Telefax	: (+39) 022484260
Contact for Safety Data Sheet	: If you have any enquiries about the content of this SDS please email <a href="mailto:lubricantSDS@shell.com">lubricantSDS@shell.com</a>

#### 1.4 Emergency telephone number

: SHELL: (+39 02 3800.4461/2 (available 24h a day)  
Poison Centers (CAV) eligible for access to information for health emergency response:  
CAV Osp. Bambin Gesù Roma 06 68593726; CAV Policlinico "Umberto I" Roma 06-49978000;  
CAV Policlinico "A. Gemelli" Roma 06 3054343; CAV Milano 02 66101029; CAV Bergamo 800883300;  
CAV Pavia 0382 24444; CAV Verona 800011858; CAV Firenze 055 7947819; CAV Napoli 081 5453333;  
CAV Foggia 800183459.

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification (REGULATION (EC) No 1272/2008)**

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Turbine Oil 500

Version	Revision Date:	SDS Number:	Date of last issue: 15.09.2023
7.1	12.05.2025	800001001487	Print Date 13.05.2025

Long-term (chronic) aquatic hazard, Category 3

H412: Harmful to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms : No symbol  
Signal word : No signal word

Hazard statements : PHYSICAL HAZARDS:  
Not classified as a physical hazard according to CLP criteria.  
HEALTH HAZARDS:  
Not classified as a health hazard under CLP criteria.  
ENVIRONMENTAL HAZARDS:  
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**  
P273 Avoid release to the environment.  
**Response:**  
No precautionary phrases.  
**Storage:**  
No precautionary phrases.  
**Disposal:**  
P501 Dispose of contents/ container to an approved waste disposal plant.

Sensitising components : Contains N-phenyl-1-naphthylamine.  
May produce an allergic reaction.

### 2.3 Other hazards

This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.  
Used oil may contain harmful impurities.  
Not classified as flammable but will burn.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Turbine Oil 500

Version 7.1      Revision Date: 12.05.2025      SDS Number: 800001001487      Date of last issue: 15.09.2023  
Print Date 13.05.2025

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

Chemical nature : Blend of synthetic esters and additives.

##### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
N-phenyl-1-naphthylamine	90-30-2 201-983-0 01-2119488704-27	Acute Tox. 4; H302 Skin Sens. 1B; H317 STOT RE 2; H373 Aquatic Acute 1; H400 Aquatic Chronic 1; H410  M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	0,25 - 0,99
Triaryl phosphate (<0.2% Ortho-TCP)	1330-78-5 215-548-8	Repr. 2; H361 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	0,25 - 0,99

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
- If inhaled : No treatment necessary under normal conditions of use.  
If symptoms persist, obtain medical advice.
- In case of skin contact : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.  
If persistent irritation occurs, obtain medical attention.
- In case of eye contact : Flush eye with copious quantities of water.  
Remove contact lenses, if present and easy to do. Continue

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Turbine Oil 500

Version	Revision Date:	SDS Number:	Date of last issue: 15.09.2023
7.1	12.05.2025	800001001487	Print Date 13.05.2025

rinsing.

If persistent irritation occurs, obtain medical attention.

If swallowed : In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Notes to doctor/physician:  
Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media : Do not use water in a jet.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Hazardous combustion products may include:  
A complex mixture of airborne solid and liquid particulates and gases (smoke).  
Carbon monoxide may be evolved if incomplete combustion occurs.  
Unidentified organic and inorganic compounds.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : 6.1.1 For non emergency personnel:

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Turbine Oil 500

Version	Revision Date:	SDS Number:	Date of last issue: 15.09.2023
7.1	12.05.2025	800001001487	Print Date 13.05.2025

---

Avoid contact with skin and eyes.  
6.1.2 For emergency responders:  
Avoid contact with skin and eyes.

### 6.2 Environmental precautions

Environmental precautions : Use appropriate containment to prevent uncontrolled release. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.

### 6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.,  
For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Technical measures : Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.  
Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

Advice on safe handling : Avoid prolonged or repeated contact with skin.  
Avoid inhaling vapour and/or mists.  
When handling product in drums, safety footwear should be worn and proper handling equipment should be used.  
Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.

Product Transfer : Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation.

### 7.2 Conditions for safe storage, including any incompatibilities

Further information on storage stability : Keep container tightly closed and in a cool, well-ventilated place.  
Use properly labeled and closable containers.  
Store at ambient temperature.

Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Turbine Oil 500

Version	Revision Date:	SDS Number:	Date of last issue: 15.09.2023
7.1	12.05.2025	800001001487	Print Date 13.05.2025

Packaging material : Suitable material: For containers or container linings, use mild steel or high density polyethylene.  
Unsuitable material: PVC.

Container Advice : Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

### 7.3 Specific end use(s)

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Biological occupational exposure limits

No biological limit allocated.

### 8.2 Exposure controls

#### Engineering measures

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

#### General Information

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

#### Personal protective equipment

The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : If material is handled such that it could be splashed into eyes, protective eyewear is recommended.  
Approved to EU Standard EN166.

Hand protection

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Turbine Oil 500

Version 7.1	Revision Date: 12.05.2025	SDS Number: 800001001487	Date of last issue: 15.09.2023 Print Date 13.05.2025
----------------	------------------------------	-----------------------------	---

---

Remarks : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.

Skin and body protection : Skin protection is not ordinarily required beyond standard work clothes.  
It is good practice to wear chemical resistant gloves.

Respiratory protection : No respiratory protection is ordinarily required under normal conditions of use.  
In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material.  
If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation.  
Check with respiratory protective equipment suppliers.  
Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.  
Select a filter suitable for combined particulate/organic gases and vapours [Type A/Type P boiling point > 65°C (149°F)] meeting EN14387 and EN143.

Thermal hazards : Not applicable

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Turbine Oil 500

Version	Revision Date:	SDS Number:	Date of last issue: 15.09.2023
7.1	12.05.2025	800001001487	Print Date 13.05.2025

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state	: Liquid at room temperature.
Colour	: Various colours
Odour	: Slight hydrocarbon
Odour Threshold	: Data not available
Melting / freezing point	: Data not available
Pour point	<= -54 °C Method: ASTM D5950
Initial boiling point and boiling range	: > 280 °Cestimated value(s)
Flammability	
Flammability (solid, gas)	: Not applicable
Flammability (liquids)	: Not classified as flammable but will burn.
Lower explosion limit and upper explosion limit / flammability limit	
Upper explosion limit / Upper flammability limit	: Typical 10 %(V)
Lower explosion limit / Lower flammability limit	: Typical 1 %(V)
Flash point	: 264 °C Method: ASTM D92 (COC)
Auto-ignition temperature	: > 320 °C
Decomposition temperature	
Decomposition temperature	: Data not available
pH	: Not applicable
Viscosity	
Viscosity, dynamic	: Data not available
Viscosity, kinematic	: 25,4 mm <sup>2</sup> /s (40,0 °C) Method: ASTM D445  5,11 mm <sup>2</sup> /s (100 °C)



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Turbine Oil 500

Version	Revision Date:	SDS Number:	Date of last issue: 15.09.2023
7.1	12.05.2025	800001001487	Print Date 13.05.2025

Method: ASTM D445

9215 mm<sup>2</sup>/s (-40 °C)  
Method: ASTM D2532

Solubility(ies)  
Water solubility : negligible  
  
Solubility in other solvents : Data not available

Partition coefficient: n-octanol/water : log Pow: > 6  
(based on information on similar products)

Vapour pressure : < 0,5 Pa (20 °C)  
estimated value(s)

Relative density : 1,005 (15 °C)

Density : 1.005 kg/m<sup>3</sup> (15,0 °C)  
Method: Unspecified

Relative vapour density : > 1  
estimated value(s)

Particle characteristics  
Particle size : Data not available

### 9.2 Other information

Explosive properties : Classification Code: Not classified  
  
Oxidizing properties : Data not available  
  
Flammability (liquids) : Not classified as flammable but will burn.  
  
Evaporation rate : Data not available  
  
Conductivity : This material is not expected to be a static accumulator.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

### 10.2 Chemical stability

Stable.  
No hazardous reaction is expected when handled and stored according to provisions

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with strong oxidising agents.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Turbine Oil 500

Version	Revision Date:	SDS Number:	Date of last issue: 15.09.2023
7.1	12.05.2025	800001001487	Print Date 13.05.2025

---

### 10.4 Conditions to avoid

Conditions to avoid : Extremes of temperature and direct sunlight.

### 10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

#### Acute toxicity

##### Product:

Acute oral toxicity : LD50 (rat): > 5.000 mg/kg  
Remarks: Based on available data, the classification criteria are not met.  
Low toxicity

Acute inhalation toxicity : Remarks: Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg  
Remarks: Based on available data, the classification criteria are not met.  
Low toxicity

#### Skin corrosion/irritation

##### Product:

Remarks : Based on available data, the classification criteria are not met.  
Slightly irritating to skin.  
Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

#### Serious eye damage/eye irritation

##### Product:

Remarks : Based on available data, the classification criteria are not met.  
Slightly irritating to the eye.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Turbine Oil 500

Version 7.1      Revision Date: 12.05.2025      SDS Number: 800001001487      Date of last issue: 15.09.2023  
Print Date 13.05.2025

### Respiratory or skin sensitisation

#### Product:

Remarks : For respiratory and skin sensitisation:  
Based on available data, the classification criteria are not met.  
Not a sensitiser.

#### Components:

##### **N-phenyl-1-naphthylamine:**

Remarks : May cause an allergic skin reaction in sensitive individuals.

### Germ cell mutagenicity

#### Product:

Genotoxicity in vivo : Remarks: Based on available data, the classification criteria are not met.  
Non mutagenic

Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.

### Carcinogenicity

#### Product:

Remarks : Based on available data, the classification criteria are not met.  
Not a carcinogen.

Carcinogenicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Material	GHS/CLP Carcinogenicity Classification
N-phenyl-1-naphthylamine	No carcinogenicity classification.
Triaryl phosphate (<0.2% Ortho-TCP)	No carcinogenicity classification.

### Reproductive toxicity

#### Product:

Effects on fertility :  
Remarks: Based on available data, the classification criteria are not met., Not a developmental toxicant., Does not impair

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Turbine Oil 500

Version 7.1	Revision Date: 12.05.2025	SDS Number: 800001001487	Date of last issue: 15.09.2023 Print Date 13.05.2025
----------------	------------------------------	-----------------------------	---

fertility.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

### STOT - single exposure

#### Product:

Remarks : Based on available data, the classification criteria are not met.

### STOT - repeated exposure

#### Product:

Remarks : Based on available data, the classification criteria are not met.

### Aspiration toxicity

#### Product:

Based on available data, the classification criteria are not met., Not an aspiration hazard.

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### Further information

#### Product:

Remarks : Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal.  
ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks : Slightly irritating to respiratory system.

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

Remarks : Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Turbine Oil 500

Version 7.1	Revision Date: 12.05.2025	SDS Number: 800001001487	Date of last issue: 15.09.2023 Print Date 13.05.2025
----------------	------------------------------	-----------------------------	---

Remarks : Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

### SECTION 12: Ecological information

#### 12.1 Toxicity

##### Product:

Toxicity to fish : Remarks: LL/EL/IL50 10-100 mg/l  
Harmful

Toxicity to daphnia and other aquatic invertebrates : Remarks: LL/EL/IL50 10-100 mg/l  
Harmful

Toxicity to algae/aquatic plants : Remarks: LL/EL/IL50 10-100 mg/l  
Harmful

Toxicity to fish (Chronic toxicity) : Remarks: Data not available

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: Data not available

Toxicity to microorganisms : Remarks: Data not available

##### Components:

##### **N-phenyl-1-naphthylamine:**

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

#### 12.2 Persistence and degradability

##### Product:

Biodegradability : Remarks: Not readily biodegradable.  
Major constituents are inherently biodegradable, but contains components that may persist in the environment.

#### 12.3 Bioaccumulative potential

##### Product:

Bioaccumulation : Remarks: Contains components with the potential to bioaccumulate.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Turbine Oil 500

Version	Revision Date:	SDS Number:	Date of last issue: 15.09.2023
7.1	12.05.2025	800001001487	Print Date 13.05.2025

### 12.4 Mobility in soil

**Product:**

Mobility : Remarks: Liquid under most environmental conditions., If it enters soil, it will adsorb to soil particles and will not be mobile.

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB..

### 12.6 Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

**Product:**

Additional ecological information : Does not have ozone depletion potential, photochemical ozone creation potential or global warming potential.  
Product is a mixture of non-volatile components, which will not be released to air in any significant quantities under normal conditions of use.

Poorly soluble mixture.  
Causes physical fouling of aquatic organisms.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Recover or recycle if possible.  
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.  
Do not dispose into the environment, in drains or in water courses.

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Turbine Oil 500

Version	Revision Date:	SDS Number:	Date of last issue: 15.09.2023
7.1	12.05.2025	800001001487	Print Date 13.05.2025

Waste, spills or used product is dangerous waste.  
Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.  
Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.

Contaminated packaging : Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local legislation

Waste catalogue :  
EU Waste Disposal Code (EWC):

Waste Code :  
13 02 06\*

Remarks : Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Classification of waste is always the responsibility of the end user.

For the disposal of waste arising from the product, including empty containers not cleared, follow the Legislative Decree 152/06 and subsequent amendments.

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADN	: Not regulated as a dangerous good
ADR	: Not regulated as a dangerous good

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Turbine Oil 500

Version	Revision Date:	SDS Number:	Date of last issue: 15.09.2023
7.1	12.05.2025	800001001487	Print Date 13.05.2025

**RID** : Not regulated as a dangerous good

**IMDG** : Not regulated as a dangerous good

**IATA** : Not regulated as a dangerous good

### 14.2 UN proper shipping name

**ADN** : Not regulated as a dangerous good

**ADR** : Not regulated as a dangerous good

**RID** : Not regulated as a dangerous good

**IMDG** : Not regulated as a dangerous good

**IATA** : Not regulated as a dangerous good

### 14.3 Transport hazard class(es)

**ADN** : Not regulated as a dangerous good

**ADR** : Not regulated as a dangerous good

**RID** : Not regulated as a dangerous good

**IMDG** : Not regulated as a dangerous good

**IATA** : Not regulated as a dangerous good

### 14.4 Packing group

**ADN** : Not regulated as a dangerous good

**ADR** : Not regulated as a dangerous good

**RID** : Not regulated as a dangerous good

**IMDG** : Not regulated as a dangerous good

**IATA** : Not regulated as a dangerous good

### 14.5 Environmental hazards

**ADN** : Not regulated as a dangerous good

**ADR** : Not regulated as a dangerous good

**RID** : Not regulated as a dangerous good

**IMDG** : Not regulated as a dangerous good

### 14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

### 14.7 Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

**Additional Information** : ADN - Classified ID9006 when carried in tank vessels.



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Turbine Oil 500

Version	Revision Date:	SDS Number:	Date of last issue: 15.09.2023
7.1	12.05.2025	800001001487	Print Date 13.05.2025

---

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Product is not subject to Authorisation under REACH.

Volatile organic compounds : Volatile organic compounds (VOC) content: 0 %

#### Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Safeguard of health and safety in the workplaces refer to D.Lgs.81/2008 and subsequent amendments.

For waste disposal refer to D.Lgs.152/2006 and subsequent amendments.

#### The components of this product are reported in the following inventories:

REACH : Notified with Restrictions.

TSCA : All components listed.

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

---

### SECTION 16: Other information

#### Full text of H-Statements

H302	: Harmful if swallowed.
H317	: May cause an allergic skin reaction.
H361	: Suspected of damaging fertility or the unborn child.
H373	: May cause damage to organs through prolonged or repeated exposure if swallowed.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.

#### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Repr.	: Reproductive toxicity
Skin Sens.	: Skin sensitisation
STOT RE	: Specific target organ toxicity - repeated exposure

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Turbine Oil 500

Version	Revision Date:	SDS Number:	Date of last issue: 15.09.2023
7.1	12.05.2025	800001001487	Print Date 13.05.2025

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Training advice : Provide adequate information, instruction and training for operators.

Other information : A vertical bar (|) in the left margin indicates an amendment from the previous version.

There has been a significant change in compositional information in section 2 & 3.

Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID data base, EC 1272 regulation, etc).

### Classification of the mixture:

Aquatic Chronic 3                      H412

### Classification procedure:

Expert judgement and weight of evi-

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Turbine Oil 500

Version	Revision Date:	SDS Number:	Date of last issue: 15.09.2023
7.1	12.05.2025	800001001487	Print Date 13.05.2025

---

dence determination.

### Identified Uses according to the Use Descriptor System

#### Uses - Worker

Title : General use of lubricants and greases in vehicles or machinery.  
- Professional

#### Uses - Worker

Title : General use of lubricants and greases in vehicles or machinery.  
- Industrial

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

IT / EN

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Turbine Oil 500

Version 7.1      Revision Date: 12.05.2025      SDS Number: 800001001487      Date of last issue: 15.09.2023  
Print Date 13.05.2025

### Exposure Scenario - Worker

**300000000200**

SECTION 1	EXPOSURE SCENARIO TITLE
Title	General use of lubricants and greases in vehicles or machinery.- Professional
Use Descriptor	<b>Sector of Use:</b> SU 22 <b>Process Categories:</b> PROC 1, PROC 2, PROC 8a, PROC 8b, PROC 20 <b>Environmental Release Categories:</b> ERC9a, ERC9b, ATIEL-ATC SPERC 9.Bp.v1
Scope of process	Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Additional Information	No exposure assessment presented for human health.
Section 2.1	Control of Worker Exposure
Product Characteristics	
Contributing Scenarios	Risk Management Measures
Section 2.2	Control of Environmental Exposure
Amounts Used	
EU tonnage (tonnes per year):	5,39E+03
Fraction of EU tonnage used in region:	0,1
Fraction of Regional tonnage used locally:	0,1
Frequency and Duration of Use	
Emission Days (days/year):	365
Environmental factors not influenced by risk management	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
Other Operational Conditions affecting Environmental Exposure	
Negligible wastewater emissions as process operates without water contact.	
Release fraction to air from process (after typical onsite RMMs) :	1,00E-04
Release fraction to wastewater from process (after typical onsite RMMs and before (municipal) sewage treatment plant):	5,00E-04
Release fraction to soil from process (after typical onsite RMMs):	1E-03
Technical conditions and measures at process level (source) to prevent release	
Common practices vary across sites thus conservative process release estimates used.	
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
Organisational measures to prevent/limit release from site	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Turbine Oil 500

Version 7.1      Revision Date: 12.05.2025      SDS Number: 800001001487      Date of last issue: 15.09.2023  
Print Date 13.05.2025

Do not apply industrial sludge to natural soils.  
Sludge should be incinerated, contained or reclaimed.

### Conditions and Measures related to municipal sewage treatment plant

Estimated substance removal from wastewater via domestic sewage treatment (%)	9,23E-02
Assumed domestic sewage treatment plant flow (m3/d)	2,00E+03
Maximum allowable site quantity (MSafe) based on OCs and RMMs as above (kg/day) :	2,707E+02

### Conditions and Measures related to external treatment of waste for disposal

External treatment and disposal of waste should comply with applicable local and/or regional regulations.

### Conditions and measures related to external recovery of waste

External recovery and recycling of waste should comply with applicable local and/or regional regulations.

## SECTION 3      EXPOSURE ESTIMATION

### Section 3.1 - Health

No exposure assessment presented for human health.

### Section 3.2 -Environment

Used ECETOC TRA model.

## SECTION 4      GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

### Section 4.1 - Health

No exposure assessment presented for human health.

### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org>).

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

For further information see [www.ATIEL.org/REACH\\_GES](http://www.ATIEL.org/REACH_GES).

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Turbine Oil 500

Version 7.1      Revision Date: 12.05.2025      SDS Number: 800001001487      Date of last issue: 15.09.2023  
Print Date 13.05.2025

### Exposure Scenario - Worker

<b>300000000199</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	General use of lubricants and greases in vehicles or machinery.- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU 3 <b>Process Categories:</b> PROC 1, PROC 2, PROC 8b, PROC 9 <b>Environmental Release Categories:</b> ERC4, ERC7, ATIEL-ATC SPERC 4.Bi.v1
<b>Scope of process</b>	Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for human health.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Contributing Scenarios	Risk Management Measures	
Section 2.2	Control of Environmental Exposure	
Amounts Used		
EU tonnage (tonnes per year):		2,63E+03
Fraction of EU tonnage used in region:		0,1
Fraction of Regional tonnage used locally:		0,1
Frequency and Duration of Use		
Emission Days (days/year):		300
Environmental factors not influenced by risk management		
Local freshwater dilution factor:		10
Local marine water dilution factor:		100
Other Operational Conditions affecting Environmental Exposure		
Negligible wastewater emissions as process operates without water contact.		
Release fraction to air from process (after typical onsite RMMs) :		5,00E-05
Release fraction to wastewater from process (after typical onsite RMMs and before (municipal) sewage treatment plant):		2,00E-11
Release fraction to soil from process (after typical onsite RMMs):		0
Technical conditions and measures at process level (source) to prevent release		
Common practices vary across sites thus conservative process re-lease estimates used.		
Technical onsite conditions and measures to reduce or limit discharges, air emis-sions and releases to soil		
Treat air emission to provide a typical removal efficiency of (%)		70
Prevent discharge of undissolved substance to or recover from onsite wastewater.		
User sites are assumed to be provided with oil/water separators or		

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Turbine Oil 500

Version 7.1      Revision Date: 12.05.2025      SDS Number: 800001001487      Date of last issue: 15.09.2023  
Print Date 13.05.2025

equivalent and for waste water to be discharged via public sewer system.	
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	9,23E-02
Assumed domestic sewage treatment plant flow (m3/d)	2,00E+03
Maximum allowable site quantity (MSafe) based on OCs and RMMs as above (kg/day) :	2,39485E+04
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
No exposure assessment presented for human health.	

<b>Section 3.2 -Environment</b>	
Used ECETOC TRA model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
No exposure assessment presented for human health.	

<b>Section 4.2 -Environment</b>	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	
Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org">http://cefic.org</a> ).	
If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.	
For further information see <a href="http://www.ATIEL.org/REACH_GES">www.ATIEL.org/REACH_GES</a> .	