According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Turbine Oil 308

Version	Revision Date:	SDS Number:	Date
3.6	14.04.2025	800001016070	Print

Date of last issue: 11.04.2023 Print Date 15.04.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	: AeroShell Turbine Oil 308
Product code	: 001A0080
Unique Formula Identifier (UFI)	: XAQ0-X04Q-G00H-1C4A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- stance/Mixture	Synthetic lubricating oil for aircraft turbine engir details consult the AeroShell Book on www.she	
Uses advised against	This product must be used, handled, and applie ance with the requirements of the equipment m manuals, bulletins and other documentation. This product must not be used in applications o listed in Section 1 without first seeking the advic plier.	anufacturer's ther than those

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier	: Shell Italia Oil Products SRL Via Vittor Pisani 16 I-20124 Milano MI
Telephone Telefax Contact for Safety Data Sheet	 : (+39) 0200695000 : (+39) 022484260 : If you have any enquiries about the content of this SDS please email lubricantSDS@shell.com

1.4 Emergency telephone number

: SHELL: (+39 02 3800.4461/2 (available 24h a day) Poison Centers (CAV) eligible for access to information for health emergency response: CAV Osp. Bambin Gesù Roma 06 68593726; CAV Policlinico "Umberto I" Roma 06-49978000; CAV Policlinico "A. Gemelli" Roma 06 3054343; CAV Milano 02 66101029; CAV Bergamo 800883300; CAV Pavia 0382 24444; CAV Verona 800011858; CAV Firenze 055 7947819; CAV Napoli 081 5453333; CAV Foggia 800183459.

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Turbine Oil 308

Version 3.6 Revision Date: 14.04.2025 SDS Number: 800001016070

Date of last issue: 11.04.2023 Print Date 15.04.2025

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)			
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.		
Long-term (chronic) aquatic hazard, Cat- egory 2	H411: Toxic to aquatic life with long lasting effects.		

2.2 Label elements

Signal word

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



J
 PHYSICAL HAZARDS: Not classified as a physical hazard according to CLP criteria. HEALTH HAZARDS: H317 May cause an allergic skin reaction. ENVIRONMENTAL HAZARDS: H411 Toxic to aquatic life with long lasting effects.
Prevention:
P273 Avoid release to the environment.P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P391 Collect spillage.
Storage:
No precautionary phrases.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.
nust be listed on the label: nine. : Contains 2,6-di-tert-butyl dimethylamino p-cresol.

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Turbine Oil 308

Version	Revision Date:	SDS Number:	Date of last issue: 11.04.2023
3.6	14.04.2025	800001016070	Print Date 15.04.2025

2.3 Other hazards

This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. Used oil may contain harmful impurities. Not classified as flammable but will burn.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Blend of synthetic esters and additives.

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No. Index-No.		(% w/w)
	Registration number		
Triaryl phosphate	1330-78-5 215-548-8	Repr. 2; H361f Aquatic Acute 1; H400 Aquatic Chronic 1; H410	1 - 2,49
		M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	
N-phenyl-1-naphthylamine	90-30-2 201-983-0 01-2119488704-27	Acute Tox. 4; H302 Skin Sens. 1B; H317 STOT RE 2; H373 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	1 - 2,49

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Turbine Oil 308

Version	Revision Date:	SDS Number:	Date of last issue: 11.04.2023	
3.6	14.04.2025	800001016070	Print Date 15.04.2025	
2,6-di creso	-tert-butyl dimethylamin	o p- 88-27-7 201-816-1	Acute Tox. 4; H302 Skin Sens. 1B; H317 Eye Irrit. 2; H319 Aquatic Chronic 1; H410	0,1 - 0,25

For explanation of abbreviations see section 16.

SECTION	4: F	irst aid	measures
		not and	moduluo

4.1 Description of first aid measures

Protection of first-aiders	: When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
If inhaled	: No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	: Remove contaminated clothing. Immediately flush skin with large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.
In case of eye contact	 Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.
If swallowed	: In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
4.2 Most important symptoms a	nd effects, both acute and delayed
Symptoms	 Skin sensitisation (allergic skin reaction) signs and symptoms may include itching and/or a rash. Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.
4.3 Indication of any immediate	medical attention and special treatment needed
Treatment	: Notes to doctor/physician: Treat symptomatically.

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Turbine Oil 308

Version	Revision Date:	SDS Number:
3.6	14.04.2025	800001016070

Date of last issue: 11.04.2023 Print Date 15.04.2025

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	:	Foam, water spray or fog. Dry chemical powder, carbon diox- ide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	:	Do not use water in a jet.
5.2 Special hazards arising from	the	e substance or mixture
Specific hazards during fire- fighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
5.3 Advice for firefighters		
Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).
Specific extinguishing meth-	:	Use extinguishing measures that are appropriate to local cir-

SECTION 6: Accidental release measures

ods

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions :	6.1.1 For non emergency personnel:Avoid contact with skin and eyes.6.1.2 For emergency responders:Avoid contact with skin and eyes.
6.2 Environmental precautions	
Environmental precautions :	Use appropriate containment to prevent uncontrolled release. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
6.3 Methods and material for conta	inment and cleaning up
Methods for cleaning up :	Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other

cumstances and the surrounding environment.

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Turbine Oil 308

Version	Revision Date:	SDS Number:	Date of last issue: 11.04.2023
3.6	14.04.2025	800001016070	Print Date 15.04.2025

suitable material and dispose of properly.

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures	 Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk as- sessment of local circumstances to help determine appropri- ate controls for safe handling, storage and disposal of this material.
Advice on safe handling	 Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning mate- rials in order to prevent fires.
Product Transfer	: Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation.
7.2 Conditions for safe storage	including any incompatibilities
7.2 Conditions for safe storage, Further information on stor- age stability	 including any incompatibilities Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers. Must be stored in a diked (bunded) area. Store at ambient temperature.
Further information on stor-	 Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers. Must be stored in a diked (bunded) area.

7.3 Specific end use(s)

Specific use(s)	:	Not applicable
-----------------	---	----------------

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Turbine Oil 308

Version 3.6 Revision Date: 14.04.2025

SDS Number: 800001016070

Date of last issue: 11.04.2023 Print Date 15.04.2025

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Biological occupational exposure limits

8.2 Exposure controls

Engineering measures

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Personal protective equipment

The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection	Wear full face shield if splashes are likely to occur. Approved to EU Standard EN166.
Hand protection	
Remarks	Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care.

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Turbine Oil 308

Version 3.6	Revision Date: 14.04.2025	SDS Number: 800001016070	Date of last issue: 11.04.2023 Print Date 15.04.2025
		gloves, hands cation of a no For continuou through time 480 minutes short-term/sp recognize tha may not be a time maybe a and replacem a good predic dependent or Glove thickne	only be worn on clean hands. After using s should be washed and dried thoroughly. Appli- on-perfumed moisturizer is recommended. us contact we recommend gloves with break- of more than 240 minutes with preference for > where suitable gloves can be identified. For lash protection we recommend the same but at suitable gloves offering this level of protection vailable and in this case a lower breakthrough acceptable so long as appropriate maintenance nent regimes are followed. Glove thickness is not ctor of glove resistance to a chemical as it is in the exact composition of the glove material. ess should be typically greater than 0.35 mm in the glove make and model.
Sk	in and body protection	risk of splash	al resistant gloves/gauntlets and boots. Where ing, also wear an apron. hthing approved to EU Standard EN14605.
Re	espiratory protection	conditions of In accordance	y protection is ordinarily required under normal use. e with good industrial hygiene practices, precau- be taken to avoid breathing of material.
Th	ermal hazards	: Not applicabl	e

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	:	Liquid at room temperature.
Colour	:	amber
Odour	:	Slight hydrocarbon
Odour Threshold	:	Data not available
Pour point	:	<= -62 °C Method: Unspecified
Melting point/freezing point		Data not available
Initial boiling point and boiling range	:	> 280 °Cestimated value(s)
Flammability Flammability (solid, gas)	:	Not applicable

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Turbine Oil 308

Vers 3.6	ion Revision Date: 14.04.2025	SDS Number:Date of last issue: 11.04.2023800001016070Print Date 15.04.2025	
	Flammability (liquids)	: Not classified as flammable but will burn.	
	Lower explosion limit and uppe	r explosion limit / flammability limit	
	Upper explosion limit / Upper flammability limit	: Typical 10 %(V)	
	Lower explosion limit / Lower flammability limit	: Typical 1 %(V)	
	Flash point	: 225 °C Method: ASTM D92 (COC)	
	Auto-ignition temperature	: > 320 °C	
	Decomposition temperature Decomposition tempera- ture	: Data not available	
	рН	: Not applicable	
	Viscosity Viscosity, dynamic	: Data not available	
	Viscosity, kinematic	: 12 mm2/s (40,0 °C) Method: Unspecified	
		3,1 mm2/s (100 °C) Method: Unspecified	
		7600 mm2/s (-51,0 °C) Method: ASTM D2532	
	Solubility(ies) Water solubility	: negligible	
	Solubility in other solvents	: Data not available	
	Partition coefficient: n- octanol/water	: log Pow: > 6 (based on information on similar products)	
	Vapour pressure	: < 0,5 Pa (20 °C) estimated value(s)	
	Relative density	: 0,956 (15 °C)	
	Density	: 956 kg/m3 (15,0 °C) Method: Unspecified	
	Relative vapour density	: > 1 estimated value(s)	

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Turbine Oil 308

Version 3.6	Revision Date: 14.04.2025	SDS Number: 800001016070	Date of last issue: 11.04.2023 Print Date 15.04.2025		
	rticle characteristics Particle size	: Data not a	vailable		
9.2 Oth	er information				
Ex	plosive properties	: Classificati	on Code: Not classified		
Ox	idizing properties	: Data not a	Data not available		
Fla	mmability (liquids)	: Not classif	Not classified as flammable but will burn.		
Eva	aporation rate	: Data not a	vailable		
Co	nductivity	: This mater	ial is not expected to be a static accumulator.		

SECTION 10: Stability and reactivity

10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

10.2 Chemical stability

Stable.

No hazardous reaction is expected when handled and stored according to provisions

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with strong oxidising agents.

10.4 Conditions to avoid

Conditions to avoid

: Extremes of temperature and direct sunlight.

10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of : Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Acute toxicity

Product:

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Turbine Oil 308

ersion Revision Dat 6 14.04.2025	e: SDS Number: Date of last issue: 11.04.2023 800001016070 Print Date 15.04.2025
Acute oral toxicity	: LD50 (rat): > 5.000 mg/kg Remarks: Low toxicity Based on available data, the classification criteria are not met
Acute inhalation toxic	ty : Remarks: Based on available data, the classification criteria are not met.
Acute dermal toxicity	 LD50 (Rabbit): > 5.000 mg/kg Remarks: Low toxicity Based on available data, the classification criteria are not met
Skin corrosion/irrita	tion
<u>Product:</u> Remarks	 Slightly irritating to skin. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as o acne/folliculitis. Based on available data, the classification criteria are not met
Serious eye damage	/eye irritation
<u>Product:</u> Remarks	: Slightly irritating to the eye. Based on available data, the classification criteria are not met
Respiratory or skin	sensitisation
Product:	
Remarks	: For skin sensitisation: Expected to be a skin sensitizer.
Remarks	: For respiratory sensitisation: Not a sensitiser. Based on available data, the classification criteria are not met
Components:	
N-phenyl-1-naphthy	amine:
Remarks	: May cause an allergic skin reaction in sensitive individuals.
2,6-di-tert-butyl dim Remarks	ethylamino p-cresol: : May cause an allergic skin reaction in sensitive individuals.
Germ cell mutageni	
<u>Product:</u> Genotoxicity in vivo	: Remarks: Non mutagenic Based on available data, the classification criteria are not met
	11/27

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Turbine Oil 308

Version 3.6	Revision Date: 14.04.2025		DS Number: 0001016070	Date of last issue: 11.04.2023 Print Date 15.04.2025
	n cell mutagenicity- As- ment	:	This product does categories 1A/1B.	s not meet the criteria for classification in
Carc	inogenicity			
Proc	luct:			
Rem	arks	:	Not a carcinogen. Based on availab	le data, the classification criteria are not met.
Caro men	inogenicity - Assess- t	:	This product does categories 1A/1B	s not meet the criteria for classification in

Material	GHS/CLP Carcinogenicity Classification
Triaryl phosphate	No carcinogenicity classification.
N-phenyl-1-naphthylamine	No carcinogenicity classification.
2,6-di-tert-butyl dimethyla- mino p-cresol	No carcinogenicity classification.

Reproductive toxicity

Product: Effects on fertility	:	Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.
Reproductive toxicity - As- sessment	:	This product does not meet the criteria for classification in categories 1A/1B.
STOT - single exposure		
Product: Remarks	:	Based on available data, the classification criteria are not met.
STOT - repeated exposure		
Product: Remarks	:	Based on available data, the classification criteria are not met.

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Turbine Oil 308

Version	Revision Date:	SDS Number:	Date of last issue: 11.04.2023
3.6	14.04.2025	800001016070	Print Date 15.04.2025

Aspiration toxicity

Product:

Not an aspiration hazard., Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

Product: Assessment	:	The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
Further information		
<u>Product:</u> Remarks	:	Used oils may contain harmful impurities that have accumu- lated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal. ALL used oil should be handled with caution and skin contact avoided as far as possible.
Remarks	:	Slightly irritating to respiratory system.
Remarks	:	Classifications by other authorities under varying regulatory frameworks may exist.
Remarks	:	Unless indicated otherwise, the data presented is representa- tive of the product as a whole, rather than for individual com- ponent(s).

SECTION 12: Ecological information

12.1 Toxicity

Product:		
Toxicity to fish	:	Remarks: LL/EL/IL50 > 1 <= 10 mg/l Toxic
Toxicity to daphnia and other aquatic invertebrates	:	Remarks: LL/EL/IL50 > 1 <= 10 mg/l Toxic
Toxicity to algae/aquatic plants	:	Remarks: LL/EL/IL50 > 1 <= 10 mg/l Toxic
Toxicity to fish (Chronic tox-	:	Remarks: Data not available

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Turbine Oil 308

Vers 3.6	ion	Revision Date: 14.04.2025		DS Number: 00001016070	Date of last issue: 11.04.2023 Print Date 15.04.2025	
	icity)					
	Toxicity to daphnia and other aquatic invertebrates (Chron-ic toxicity)			Remarks: Data not available		
	Toxicit	y to microorganisms	:	Remarks: Data not	available	
	Comp	onents:				
	Triaryl	phosphate:				
	-	or (Acute aquatic tox-	:	1		
	M-Fact toxicity	or (Chronic aquatic)	:	1		
	N-nho	nyl-1-naphthylamine:				
	-	· · · ·	:	1		
	M-Fact toxicity	or (Chronic aquatic)	:	1		
12.2	Persis	tence and degradabil	lity			
	Produ	ct.				
		radability	:		ily biodegradable. are inherently biodegradable, but contains com- ersist in the environment.	
12.3	Bioaco	cumulative potential				
	Produ	ct:				
		umulation	:	Remarks: Contains	components with the potential to bioaccumulate.	
12.4	Mobili	ty in soil				
	<u>Produ</u> Mobilit <u>y</u>		:		under most environmental conditions., If it adsorb to soil particles and will not be mo-	
				Remarks: Floats	on water.	
10 E	Deculé	e of PRT and vPvR a		aamant		

12.5 Results of PBT and vPvB assessment

Product:

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Turbine Oil 308

Version 3.6	Revision Date: 14.04.2025	SDS Number: 800001016070	Date of last issue: 11.04.2023 Print Date 15.04.2025			
Assessment			This mixture does not contain any REACH registered sub- stances that are assessed to be a PBT or a vPvB			
12.6 Endo	crine disrupting prop	erties				
<u>Produ</u>	ict:					
Asses	sment	have endocrine 57(f) or Comm	mixture does not contain components considered to e disrupting properties according to REACH Article hission Delegated regulation (EU) 2017/2100 or egulation (EU) 2018/605 at levels of 0.1% or higher.			
12.7 Other	adverse effects					
<u>Produ</u>	ict:					
Addition mation	onal ecological infor- า	tion potential of Product is a mi	ozone depletion potential, photochemical ozone crea- or global warming potential. ixture of non-volatile components, which will not be in any significant quantities under normal conditions			
		Poorly soluble Causes physica	mixture. al fouling of aquatic organisms.			
			ed otherwise, the data presented is representative of a whole, rather than for individual component(s).			

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	 Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses.
	Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste. Waste arising from a spillage or tank cleaning should be dis- posed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand. Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.
	MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides tech-

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Turbine Oil 308

Version 3.6	Revision Date: 14.04.2025	SDS Number:Date of last issue: 11.04.2023800001016070Print Date 15.04.2025	
		nical aspects at controlling pollutions from ships.	
Cont	aminated packaging	: Dispose in accordance with prevailing regulations, pre to a recognized collector or contractor. The competer the collector or contractor should be established befor Disposal should be in accordance with applicable reg national, and local laws and regulations.	nce of rehand.
Loca	llegislation		
Wast	e catalogue	:	
		EU Waste Disposal Code (EWC):	
Wast	e Code	:	
		13 02 06*	
Rem	arks	: Disposal should be in accordance with applicable reg	onal.
		national, and local laws and regulations.	,
		Classification of waste is always the responsibility of t user.	he end
		For the disposal of waste arising from the product, inc empty containers not cleared, follow the Legislative D 152/06 and subsequent amendments.	

SECTION 14: Transport information

14.1 UN number or ID number		
ADN	:	3082
ADR	:	3082
RID	:	3082
IMDG IATA	:	3082 3082
14.2 UN proper shipping name		
ADN	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (N-phenyl-1-naphthylamine and Triaryl phosphate)
ADR	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Turbine Oil 308

Versio 3.6	n Revision Date: 14.04.2025	SDS Number:Date of last issue: 11.04.2023800001016070Print Date 15.04.2025
		(N-phenyl-1-naphthylamine and Triaryl phosphate)
R	ID	 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (N-phenyl-1-naphthylamine and Triaryl phosphate)
IN	IDG	 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (N-phenyl-1-naphthylamine and Triaryl phosphate)
IA	TA	 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (N-phenyl-1-naphthylamine and Triaryl phosphate)
	ransport hazard class(es)	
	DN	: 9
	DR	: 9
	ID IDG	: 9 : 9
	ATA	· 9
A Pa C	acking group DN acking group lassification Code	: III : M6
A Pi C H	abels DR acking group lassification Code azard Identification Number abels	: 9 (N2, F) : III : M6 : 90 : 9
R Pi C H	ID acking group lassification Code azard Identification Number abels	: III : M6
P: La	IDG acking group abels \TA	: III : 9
P	acking group abels	: III : 9
	nvironmental hazards	
Α	DN nvironmentally hazardous	: yes
E	DR nvironmentally hazardous ID	: yes
ĸ		

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Turbine Oil 308

Version 3.6	Revision Date: 14.04.2025		DS Number: 00001016070	Date of last issue: 11.04.2023 Print Date 15.04.2025
IMDG	nmentally hazardous	:	yes yes	
14.6 Special precautions for user Remarks		er :	for special precau	ons: Refer to Section 7, Handling & Storage, utions which a user needs to be aware of or with in connection with transport.

14.7 Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	: Not applicable
REACH - List of substances subject to authorisation (Annex XIV)	: Product is not subject to Authorisa- tion under REACH.
Seveso III: Directive 2012/18/EU of the Euro- pean Parliament and of the Council on the control of major-accident hazards involving dangerous substances.	ENVIRONMENTAL HAZARDS
Volatile organic compounds : Volatile organic com	pounds (VOC) content: 0 %

volatile organic compounds . volatile organic compounds (voc) com

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Safeguard of health and safety in the workplaces refer to D.Lgs.81/2008 and subsequent amendments.

For waste disposal refer to D.Lgs.152/2006 and subsequent amendments.

The components of this product are	reported in the following inventories:
------------------------------------	--

REACH	:	All components listed or polymer exempt.
TSCA	:	All components listed.

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Turbine Oil 308

Version	Rev
3.6	14.0

vision Date: 04.2025 SDS Number: 800001016070 Date of last issue: 11.04.2023 Print Date 15.04.2025

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements H302 Harmful if swallowed. H317 May cause an allergic skin reaction. Causes serious eve irritation. H319 Suspected of damaging fertility. H361f May cause damage to organs through prolonged or repeated H373 exposure if swallowed. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. Full text of other abbreviations Acute Tox. : Acute toxicity Short-term (acute) aquatic hazard Aduatic Acute

Aqualic Acule	. Short-term (acute) aquatic hazaru
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Irrit.	: Eye irritation
Repr.	: Reproductive toxicity
Skin Sens.	: Skin sensitisation
STOT RE	: Specific target organ toxicity - repeated exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association: IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Turbine Oil 308

Version	Revision Date:	SDS Number:	Date of last issue: 11.04.2023
3.6	14.04.2025	800001016070	Print Date 15.04.2025

Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information	:	A vertical bar () in the left margin indicates an amendment
		from the previous version.

Classification of the mixture:		Classification procedure:	
Skin Sens. 1	H317	Expert judgement and weight of evi- dence determination.	
Aquatic Chronic 2	H411	Expert judgement and weight of evi- dence determination.	
Identified Uses accordin Uses - Worker Title	g to the Use Descriptor Sy		
i ilie	. General use of lubric	ants and greases in vehicles or machin-	

ery.
- Professional

Title	: General use of lubricants and greases in vehicles or machin-
	ery.
	- Industrial

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

IT / EN

Uses - Worker

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Turbine Oil 308

Version	Revision Date:
3.6	14.04.2025

SDS Number: 800001016070

Date of last issue: 11.04.2023 Print Date 15.04.2025

Exposure Scenario - Worker

Exposure Scenario - Work	ÇI
30000010727	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	General use of lubricants and greases in vehicles or machin-
	ery Professional
Use Descriptor	Sector of Use: SU 22
	Process Categories: PROC 1, PROC 2, PROC 8a, PROC 8b, PROC 20
	Environmental Release Categories: ERC9a, ERC9b,
	ATIEL-ATC SPERC 9.Bp.v1
Scope of process	Covers general use of lubricants and greases in vehicles or
	machinery in closed systems. Includes filling and draining of
	containers and operation of enclosed machinery (including
	engines) and associated maintenance and storage activities.
SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT
	MEASURES
Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Sub-	Covers use of substance/product up to 100% (unless stated
stance in Mixture/Article	differently).,
Frequency and Duration o	f Use
	o 8 hours (unless stated differently).
Other Operational Condition	ons affecting Exposure
	an 20°C above ambient temperature (unless stated differently).
Assumes a good basic stand	dard of occupational hygiene is implemented.
Contributing Scenarios	Risk Management Measures
General measures applica-	Avoid direct skin contact with product. Identify potential areas
ble to all activities.	for indirect skin contact. Wear gloves (tested to EN374) if
	hand contact with substance likely. Clean up contamina-
	tion/spills as soon as they occur. Wash off any skin contami-
	nation immediately. Provide basic employee training to pre-
	vent / minimise exposures and to report any skin problems
	that may develop.
	Use suitable eye protection.
	Avoid direct eye contact with product, also via contamination

Avoid direct eye contact with product, also via contamination on hands.

	on hands.
Operation of equipment containing engine oils and similar.Use in contained systemsUse in closed pro- cess, no likelihood of expo- sure	No other specific measures identified.

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Turbine Oil 308

Version	Revision Date:	SDS Number:	Date of last issue: 11.04.2023
3.6	14.04.2025	800001016070	Print Date 15.04.2025

Material transform Niero	A satisfier and the second section of the second states and	
Material transfersNon-	Avoid carrying out activities involving e	exposure for more than
dedicated facilityTransfer of	4 hours	
substance or preparation	Wear chemically resistant gloves (teste	ed to EIN374) in combi-
(charging/ discharging)	nation with specific activity training.	
from/ to vessels/ large con- tainers at non-dedicated		
facilities		
	Drain down overtem prior to aquinment	opoping or mainta
Equipment cleaning and maintenanceTransfer of	Drain down system prior to equipment nance.	opening of mainte-
substance or preparation	Retain drain downs in sealed storage p	oonding disposal or for
(charging/ discharging)	subsequent recycle.	benuing disposal of for
from/ to vessels/ large con-	subsequent recycle.	
tainers at dedicated facili-		
tiesHeat and pressure		
transfer fluids in dispersive,		
professional use but closed		
systems		
Storage.Use in closed pro-	Store substance within a closed syster	n.
cess, no likelihood of expo-		
sureUse in closed, continu-		
ous process with occasion-		
al controlled exposure		
Section 2.2	Control of Environmental Exposure	
Amounts Used		
EU tonnage (tonnes per year		5.387,2
Fraction of EU tonnage used		0,1
Fraction of Regional tonnage		0,1
Frequency and Duration of		
Frequency and Duration of Emission Days (days/year):	Use	365
Frequency and Duration of Emission Days (days/year): Environmental factors not i	Use influenced by risk management	365
Frequency and Duration of Emission Days (days/year): Environmental factors not in Local freshwater dilution factor	Use influenced by risk management or:	365
Frequency and Duration of Emission Days (days/year): Environmental factors not in Local freshwater dilution factors Local marine water dilution factors	Use influenced by risk management or: actor:	365 10 100
Frequency and Duration of Emission Days (days/year): Environmental factors not in Local freshwater dilution factor Local marine water dilution factor Other Operational Condition	Use influenced by risk management or: actor: ns affecting Environmental Exposure	365 10 100
Frequency and Duration of Emission Days (days/year): Environmental factors not in Local freshwater dilution factor Local marine water dilution factor Other Operational Condition Negligible wastewater emissi	Use influenced by risk management or: actor:	365 10 100
Frequency and Duration of Emission Days (days/year): Environmental factors not in Local freshwater dilution factor Local marine water dilution factor Other Operational Condition Negligible wastewater emissis contact.	Use influenced by risk management or: actor: ins affecting Environmental Exposure tions as process operates without water	365 10 100
Frequency and Duration of Emission Days (days/year): Environmental factors not in Local freshwater dilution factor Local marine water dilution factor Other Operational Condition Negligible wastewater emissis contact. Release fraction to air from p	Use influenced by risk management or: actor: ins affecting Environmental Exposure ions as process operates without water rocess (after typical onsite RMMs) :	365 10 100 100 1,00E-04
Frequency and Duration of Emission Days (days/year): Environmental factors not in Local freshwater dilution factor Local marine water dilution factor Other Operational Condition Negligible wastewater emissis contact. Release fraction to air from p Release fraction to wastewater	Use influenced by risk management or: actor: ins affecting Environmental Exposure ions as process operates without water rocess (after typical onsite RMMs) : er from process (after typical onsite	365 10 100
Frequency and Duration of Emission Days (days/year): Environmental factors not in Local freshwater dilution factor Local marine water dilution factor Other Operational Condition Negligible wastewater emissin contact. Release fraction to air from p Release fraction to wastewater RMMs and before (municipal	Use influenced by risk management or: actor: ins affecting Environmental Exposure ions as process operates without water rocess (after typical onsite RMMs) : er from process (after typical onsite) sewage treatment plant):	365 10 100 100 1,00E-04 5,00E-04
Frequency and Duration of Emission Days (days/year): Environmental factors not it Local freshwater dilution factor Local marine water dilution factor Other Operational Conditio Negligible wastewater emissi contact. Release fraction to air from p Release fraction to wastewater RMMs and before (municipal Release fraction to soil from p	Use influenced by risk management or: actor: ms affecting Environmental Exposure ions as process operates without water rocess (after typical onsite RMMs) : er from process (after typical onsite) sewage treatment plant): process (after typical onsite RMMs):	365 10 100 100 1,00E-04 5,00E-04 1E-03
Frequency and Duration of Emission Days (days/year): Environmental factors not in Local freshwater dilution factor Local marine water dilution factor Other Operational Condition Negligible wastewater emissis contact. Release fraction to air from p Release fraction to air from p Release fraction to soil from p Release fraction to soil from p Technical conditions and m	Use influenced by risk management or: actor: ons affecting Environmental Exposure ions as process operates without water rocess (after typical onsite RMMs) : er from process (after typical onsite) sewage treatment plant): process (after typical onsite RMMs): neasures at process level (source) to	365 10 100 100 1,00E-04 5,00E-04 1E-03
Frequency and Duration of Emission Days (days/year): Environmental factors not in Local freshwater dilution factor Local marine water dilution factor Other Operational Condition Negligible wastewater emissis contact. Release fraction to air from p Release fraction to wastewater RMMs and before (municipal Release fraction to soil from p Technical conditions and m Common practices vary across	Use influenced by risk management or: actor: ms affecting Environmental Exposure ions as process operates without water rocess (after typical onsite RMMs) : er from process (after typical onsite) sewage treatment plant): process (after typical onsite RMMs):	365 10 100 100 1,00E-04 5,00E-04 1E-03
Frequency and Duration of Emission Days (days/year): Environmental factors not it Local freshwater dilution factor Local marine water dilution factor Other Operational Condition Negligible wastewater emissis contact. Release fraction to air from p Release fraction to wastewater RMMs and before (municipal Release fraction to soil from p Technical conditions and m Common practices vary across lease estimates used.	Use influenced by risk management or: actor: ms affecting Environmental Exposure ions as process operates without water rocess (after typical onsite RMMs) : er from process (after typical onsite) sewage treatment plant): process (after typical onsite RMMs): measures at process level (source) to ss sites thus conservative process re-	365 10 100 100 1,00E-04 5,00E-04 1E-03 prevent release
Frequency and Duration of Emission Days (days/year): Environmental factors not in Local freshwater dilution factor Local marine water dilution factor Other Operational Condition Negligible wastewater emissis contact. Release fraction to air from p Release fraction to wastewater RMMs and before (municipal Release fraction to soil from p Technical conditions and m Common practices vary across lease estimates used. Technical onsite conditions	Use influenced by risk management or: actor: ons affecting Environmental Exposure ions as process operates without water rocess (after typical onsite RMMs) : er from process (after typical onsite) sewage treatment plant): process (after typical onsite RMMs): neasures at process level (source) to	365 10 100 100 1,00E-04 5,00E-04 1E-03 prevent release
Frequency and Duration of Emission Days (days/year): Environmental factors not it Local freshwater dilution factor Local marine water dilution factor Other Operational Condition Negligible wastewater emissi contact. Release fraction to air from p Release fraction to air from p Release fraction to wastewater RMMs and before (municipal Release fraction to soil from p Technical conditions and m Common practices vary across lease estimates used. Technical onsite conditions sions and releases to soil	Use influenced by risk management or: actor: ms affecting Environmental Exposure ions as process operates without water rocess (after typical onsite RMMs) : er from process (after typical onsite) sewage treatment plant): process (after typical onsite RMMs): measures at process level (source) to ss sites thus conservative process re- s and measures to reduce or limit disc	365 10 100 100 1,00E-04 5,00E-04 1E-03 prevent release charges, air emis-
Frequency and Duration of Emission Days (days/year): Environmental factors not it Local freshwater dilution factor Local marine water dilution factor Other Operational Condition Negligible wastewater emissi contact. Release fraction to air from p Release fraction to air from p Release fraction to wastewater RMMs and before (municipal Release fraction to soil from p Technical conditions and m Common practices vary across lease estimates used. Technical onsite conditions sions and releases to soil	Use influenced by risk management or: actor: ms affecting Environmental Exposure ions as process operates without water rocess (after typical onsite RMMs) : er from process (after typical onsite) sewage treatment plant): process (after typical onsite RMMs): measures at process level (source) to ss sites thus conservative process re-	365 10 100 100 1,00E-04 5,00E-04 1E-03 prevent release charges, air emis-
Frequency and Duration of Emission Days (days/year): Environmental factors not in Local freshwater dilution factor Local marine water dilution factor Other Operational Condition Negligible wastewater emissis contact. Release fraction to air from p Release fraction to air from p Release fraction to soil from p Technical conditions and m Common practices vary across lease estimates used. Technical onsite conditions sions and releases to soil Prevent discharge of undisson wastewater.	Use influenced by risk management or: actor: ons affecting Environmental Exposure ions as process operates without water rocess (after typical onsite RMMs) : er from process (after typical onsite) sewage treatment plant): process (after typical onsite RMMs): neasures at process level (source) to ss sites thus conservative process re- s and measures to reduce or limit disc	365 10 100 100 1,00E-04 5,00E-04 1E-03 prevent release charges, air emis-
Frequency and Duration of Emission Days (days/year): Environmental factors not in Local freshwater dilution factor Local marine water dilution factor Other Operational Condition Negligible wastewater emissis contact. Release fraction to air from p Release fraction to air from p Release fraction to soil from p Release fraction to soil from p Technical conditions and m Common practices vary across lease estimates used. Technical onsite conditions sions and releases to soil Prevent discharge of undisso wastewater. Organisational measures to	Use influenced by risk management or: actor: ons affecting Environmental Exposure ions as process operates without water rocess (after typical onsite RMMs) : er from process (after typical onsite) sewage treatment plant): process (after typical onsite RMMs): neasures at process level (source) to ss sites thus conservative process re- s and measures to reduce or limit disc obved substance to or recover from onsite o prevent/limit release from site	365 10 100 100 1,00E-04 5,00E-04 1E-03 prevent release charges, air emis-
Frequency and Duration of Emission Days (days/year): Environmental factors not in Local freshwater dilution factor Local marine water dilution factor Other Operational Condition Negligible wastewater emissis contact. Release fraction to air from p Release fraction to air from p Release fraction to soil from p Technical conditions and m Common practices vary across lease estimates used. Technical onsite conditions sions and releases to soil Prevent discharge of undisson wastewater.	Use influenced by risk management or: actor: ms affecting Environmental Exposure ions as process operates without water rocess (after typical onsite RMMs) : er from process (after typical onsite) sewage treatment plant): process (after typical onsite RMMs): neasures at process level (source) to ss sites thus conservative process re- s and measures to reduce or limit disc prevent/limit release from site e to natural soils.	365 10 100 100 1,00E-04 5,00E-04 1E-03 prevent release charges, air emis-

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Turbine Oil 308

Version	Revision Date:	SDS Number:	Date of last issue: 11.04.2023
3.6	14.04.2025	800001016070	Print Date 15.04.2025

 Estimated substance removal from wastewater via domestic sewage
 0,1

 treatment (%)
 2,00E+03

 Assumed domestic sewage treatment plant flow (m3/d)
 2,00E+03

 Maximum allowable site quantity (MSafe) based on OCs and RMMs as above (kg/day) :
 107,4

 Conditions and Measures related to external treatment of waste for disposal
 External treatment and disposal of waste should comply with applicable local and/or regional regulations.

 Conditions and measures related to external recovery of waste
 Image: Conditions and measures related to external recovery of waste

External recovery and recycling of waste should comply with applicable local and/or regional regulations.

SECTION 3

EXPOSURE ESTIMATION

Section 3.1 - Health

The Risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 3.2 - Environment

Used ECETOC TRA model.

SECTION 4 GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

Section 4.1 - Health

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org).

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a sitespecific chemical safety assessment is required.

For further information see www.ATIEL.org/REACH_GES.

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Turbine Oil 308

Version	Revision Date:
3.6	14.04.2025

SDS Number: 800001016070 Date of last issue: 11.04.2023 Print Date 15.04.2025

٦

Exposure Scenario - Worker

30000010720	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	General use of lubricants and greases in vehicles or machin- ery Industrial
Use Descriptor	Sector of Use: SU 3 Process Categories: PROC 1, PROC 2, PROC 8b, PROC 9 Environmental Release Categories: ERC4, ERC7, ATIEL- ATC SPERC 4.Bi.v1
Scope of process	Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Sub- stance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,
Frequency and Duration of	
Covers daily exposures up to	8 hours (unless stated differently).
Other Operational Conditio	ns affecting Exposure
	in 20°C above ambient temperature (unless stated differently). ard of occupational hygiene is implemented.
Contributing Scenarios	Risk Management Measures
General measures applicable to all activities.	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamina- tion/spills as soon as they occur. Wash off any skin contami- nation immediately. Provide basic employee training to pre- vent / minimise exposures and to report any skin problems that may develop. Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.
General exposures (closed systems)Use in closed pro- cess, no likelihood of expo- sure	No other specific measures identified.
Initial factory fill of equip- mentUse in contained sys- temsUse in closed, contin-	No other specific measures identified.

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Turbine Oil 308

Version	Rev
3.6	14.

evision Date: 4.04.2025 SDS Number: 800001016070

Date of last issue: 11.04.2023 Print Date 15.04.2025

uous process with occa-			
sional controlled exposure-			
Transfer of substance or			
preparation into small con-			
tainers (dedicated filling			
line, including weighing)			
Initial factory fill of equip-	Provide a good standard of general or co	ntrolled ventilation (5	
ment(open sys-	to 15 air changes per hour).		
tems)Transfer of substance	Avoid carrying out activities involving exp	osure for more than	
or preparation (charging/	4 hours		
discharging) from/ to ves-			
sels/ large containers at			
dedicated facilities			
Operation of equipment	No other specific measures identified.		
containing engine oils and			
similar.Use in contained			
systemsUse in closed pro-			
cess, no likelihood of expo-			
sure			
Equipment cleaning and	Drain down system prior to equipment op	ening or mainte-	
maintenanceTransfer of	nance.		
substance or preparation	Provide a good standard of general venti	lation (not less than	
(charging/ discharging)	3 to 5 air changes per hour).		
from/ to vessels/ large con-	Wear chemically resistant gloves (tested	to EN374) in combi-	
tainers at dedicated facili-	nation with specific activity training.	- l'a a d'an a a l'a a fau	
ties	Retain drain downs in sealed storage per	naing disposal or for	
	subsequent recycle.		
Equipment cleaning and	Drain down system prior to equipment op	ening or mainte-	
maintenanceOperation is	nance.	ching of mainte	
carried out at elevated tem-	Provide extract ventilation to emission po	ints when contact	
perature (> 20°C above	with warm (>50oC) product is likely.		
ambient tempera-	Wear chemically resistant gloves (tested	to FN374) in combi-	
ture).Transfer of substance	nation with intensive management superv		
or preparation (charging/	Retain drain downs in sealed storage per		
discharging) from/ to ves-	subsequent recycle.		
sels/ large containers at			
dedicated facilities			
Storage.Use in closed pro-	Store substance within a closed system.		
cess, no likelihood of expo-	,		
sureUse in closed, continu-			
ous process with occasion-			
al controlled exposure			
Section 2.2	Control of Environmental Exposure		
Amounts Used	· · · · ·		
EU tonnage (tonnes per year):	2.361,1	
Fraction of EU tonnage used		0,1	
Fraction of Regional tonnage		0,1	
Frequency and Duration of	*		
Emission Days (days/year): 300			
Environmental factors not influenced by risk management			
Local freshwater dilution factor	or:	10	
Local freshwater dilution factor	Local freshwater dilution factor: 10		

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Turbine Oil 308

Version	Revision Date:	SDS Number:	D
3.6	14.04.2025	800001016070	P

Date of last issue: 11.04.2023 Print Date 15.04.2025

Local marine water dilution factor:	100
Other Operational Conditions affecting Environmental Exposure	
Negligible wastewater emissions as process operates without water contact.	
Release fraction to air from process (after typical onsite RMMs) :	5,00E-05
Release fraction to wastewater from process (after typical onsite RMMs and before (municipal) sewage treatment plant):	2,00E-11
Release fraction to soil from process (after typical onsite RMMs):	0
Technical conditions and measures at process level (source) to pr	revent release
Common practices vary across sites thus conservative process re- lease estimates used.	
Technical onsite conditions and measures to reduce or limit disch sions and releases to soil	arges, air emis-
Treat air emission to provide a typical removal efficiency of (%)	70
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
User sites are assumed to be provided with oil/water separators or equivalent and for waste water to be discharged via public sewer sys- tem.	
Organisational measures to prevent/limit release from site	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment p	olant
Estimated substance removal from wastewater via domestic sewage treatment (%)	0,1
Assumed domestic sewage treatment plant flow (m3/d)	2,00E+03
Maximum allowable site quantity (MSafe) based on OCs and RMMs as above (kg/day) :	9.521,6
Conditions and Measures related to external treatment of waste for	or disposal
External treatment and disposal of waste should comply with applicable regulations.	e local and/or regiona
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable regulations.	e local and/or regional
SECTION 3 EXPOSURE ESTIMATION	
Section 3.1 - Health	

The Risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 3.2 - Environment

Used ECETOC TRA model.

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Turbine Oil 308

Version	Revision
3.6	14.04.20

ision Date: 04.2025 SDS Number: 800001016070

Date of last issue: 11.04.2023 Print Date 15.04.2025

SECTION 4 GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

Section 4.1 - Health

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org).

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a sitespecific chemical safety assessment is required.

For further information see www.ATIEL.org/REACH_GES.